



AOTF470 N-Channel Enhancement Mode Field Effect Transistor


General Description

The AOTF470 uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. This device is suitable for use in PWM, load switching and general purpose applications.

-RoHS Compliant

Features

V_{DS} (V) = 75V
 I_D = 50 A (V_{GS} = 10V)
 $R_{DS(ON)} < 11.5\text{m}\Omega$ ($V_{GS} = 10\text{V}$)



Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	AOTF470	Units
Drain-Source Voltage	V_{DS}	75	V
Gate-Source Voltage	V_{GS}	± 25	V
Continuous Drain Current ^A	I_D	50	A
$T_C=100^\circ\text{C}$		36	
Pulsed Drain Current ^C	I_{DM}	200	
Avalanche Current ^C	I_{AR}	45	A
Repetitive avalanche energy $L=0.3\text{mH}$ ^C	E_{AR}	300	mJ
Power Dissipation ^B	P_D	54	W
$T_C=25^\circ\text{C}$		27	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 175	°C

Thermal Characteristics

Parameter	Symbol	AOTF470	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	60	°C/W
Maximum Junction-to-Case ^B	$R_{\theta JC}$	2.8	°C/W

AOTF470

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	75			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=60\text{V}, V_{GS}=0\text{V}$			1	μA
			$T_J=55^\circ\text{C}$		5	
I_{GSS}	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 25\text{V}$			1	uA
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2	2.7	4	V
$I_{D(\text{ON})}$	On state drain current	$V_{GS}=10\text{V}, V_{DS}=5\text{V}$	200			A
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=30\text{A}$		9.8	11.5	$\text{m}\Omega$
			$T_J=125^\circ\text{C}$		16.0	
g_{FS}	Transconductance	$V_{DS}=5\text{V}, I_D=50\text{A}$		90		S
V_{SD}	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.7	1	V
I_S	Maximum Body-Diode Continuous Current				20	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=30\text{V}, f=1\text{MHz}$		4700	5640	pF
C_{oss}	Output Capacitance			400		pF
C_{rss}	Reverse Transfer Capacitance			180		pF
R_g	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		3	4.5	Ω
SWITCHING PARAMETERS						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=30\text{V}, I_D=30\text{A}$		114	140	nC
Q_{gs}	Gate Source Charge			33		nC
Q_{gd}	Gate Drain Charge			18		nC
$t_{D(\text{on})}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=30\text{V}, R_L=1\Omega, R_{\text{GEN}}=3\Omega$		21		ns
t_r	Turn-On Rise Time			39		ns
$t_{D(\text{off})}$	Turn-Off Delay Time			70		ns
t_f	Turn-Off Fall Time			24		ns
t_{rr}	Body Diode Reverse Recovery Time	$I_F=30\text{A}, dI/dt=100\text{A}/\mu\text{s}$		53	70	ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F=30\text{A}, dI/dt=100\text{A}/\mu\text{s}$		143		nC

A: The value of $R_{\theta JA}$ is measured with the device in a still air environment with $T_A=25^\circ\text{C}$.

B. The power dissipation P_D is based on $T_{J(\text{MAX})}=175^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C: Repetitive rating, pulse width limited by junction temperature $T_{J(\text{MAX})}=175^\circ\text{C}$.

D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using $<300\ \mu\text{s}$ pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(\text{MAX})}=175^\circ\text{C}$.

G. The maximum current rating is limited by bond-wires.

Rev0: Feb. 2009

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Single Pulse Avalanche capability

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 10: Current De-rating (Note B)




Figure 11: Power De-rating (Note B)




Figure 12: Maximum Forward Biased Safe Operating Area (Note F)




Figure 13: Normalized Maximum Transient Thermal Impedance (Note F)