## VCO Product Specification



Customer: SIRENZA MICRODEVICES, INC.

**Operating Temperature Range:** (-55 ° to 100 ° C)

						THE WWW.
Parameter	Min	Тур	Max	Units	Х	Remarks
Frequency Range -	1500		2725	MHz	X	
Tuning Voltage:	-13	TOP		100		
1500 MHz	0	0.8		Vdc	Х	
2725 MHz	W.W.D	18.5	20	Vdc	Х	
Tuning Sensitivity:						
1500 MHz	107	142.7	178.3	MHz/V	Х	- 5
1806.25 MHz	57.2	76.2	95.3	MHz/V	Х	一生切四
2112.5 MHz	69.4	92.5	115.7	MHz/V	Х	- CO
2418.75 MHz	54.6	72.9	91.1	MHz/V	Х	W.D.Z.S.
2725 MHz	27.6	36.8	46	MHz/V	Х	Marie
Output Power -	10	12	16	dBm	Х	
Output Phase Noise:		- 47-10	3	W		
10 kHz	24-11	-78	-70	dBc/Hz	Х	
100 kHz	- fu 10	-100	-92	dBc/Hz	Х	
1000 kHz	AL WILL	-122	-116	dBc/Hz	Х	
Power Supply -	14.75	15	15.25	Volts	Х	
Supp <mark>l</mark> y Current -		19	21	mA	Х	- EA
Harmonic Suppression:						
2nd Harmonic		-15	-10	dBc	Х	- C.C.
3rd Harmonic		-15	-10	dBc 👚	Х	W.W.W.
Spurious (Non-Harmonic) -			-80	dBc		The Waster
Frequency Pushing - 14.75- 15.25 V		5	10	MHz p-p		
Frequency Pulling - 22 dB RL		25	35	MHz p-p		
Output Impedance -	- Su 10	50		Ω		
Modula <mark>tion:                                    </mark>	dd an					
Bandwidth	10000	20000		kHz		
Input Impedance		0.05		kΩ		_ 17,100

## **Package Information**

Package Type:	TO-8 (Cir)	Drawing Number:	A8678
Dimensions:	0.504 x 0.504 x 0.27 inches	Drawing Revision:	Р

## Comments

X Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.