



查询SPI250EP供应商  
Sparkle Power Inc.

A Leading Power Supply Manufacturer  
Web site: [www.sparklepower.com](http://www.sparklepower.com)

捷多邦, 专业PCB打样工厂, 24小时加急出货

## SPI250EP (80PLUS, RoHS Compliant) 250 Watts ATX+12V Switching Power Supply

### Features

- Complied with ATX12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Noise Killer (thermal fan speed control function)
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CUL/UL60950-1, CSA C22.2 NO. 60950-1, TUV EN60950-1, NEMKO EN60950-1+CB report, FCC, EMC

### Input Characteristics

**Input Range:** 100 ~ 264Vac , Full Range Input

**Frequency:** 47 ~ 63Hz

**Input Current:** Max 4A @ 115Vac, 2A @ 230Vac

**Inrush Current:** No damage

### Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.5A	7.0A	14A	± 5%	± 1%	50mV P-P
+5V	0.3A	6.0A	12A	± 5%	± 1%	50mV P-P
+12V1	1.0A	4.0A	8A	± 5%	± 1%	120mV P-P
+12V2	1.0A	6.5A	13A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.15A	0.3A	± 10%	± 1%	120mV P-P
+5Vsb	0.0A	1.25A	2.5A	± 5%	± 1%	50mV P-P



### Specification

- **Temperature Range:** Operating: 0°C ~ +45°C , Full load at 25°C ; De-rate 1.5W/°C ; storage & shipping: -20°C ~ +65°C
- **Humidity:** 90% on operating, 95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 1 second
- **Efficiency: 80%** minimum
- **Rise time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 140x150x86mm / 5.5x5.9x3.4inch

\*+3.3V and +5V total output not exceed 106W. When +3.3V is load to 14A, the +5V maximum load is 12A.

\*+12V1&+12V2 total output not exceed 204W.

\* Total output for this subject power supply is 250W