

**REVISIONS**

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED

REV																				
SHEET																				
REV																				
SHEET																				

REV STATUS OF SHEETS	REV																			
	SHEET	1	2	3	4	5	6	7	8	9										

PMIC N/A	PREPARED BY Rick C. Officer	DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	
<p align="center"><b>STANDARDIZED MILITARY DRAWING</b></p> THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE  AMSC N/A	CHECKED BY Charles E. Besore	MICROCIRCUIT, LINEAR, HIGH SPEED, OPERATIONAL AMPLIFIER, MONOLITHIC SILICON	
	APPROVED BY Michael A. Frye	SIZE      CAGE CODE <b>A            67268</b>	
	DRAWING APPROVAL DATE 93-01-11	SHEET      1                      OF      9 <b>1</b>	
	REVISION LEVEL		

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part or Identifying Number (PIN). The complete PIN shall be as shown in the following example:



1.2.1 Device type(s). The device type(s) shall identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	AD846	High speed operational amplifier

1.2.2 Case outline(s). The case outline(s) shall be as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
P	GDIP1-T8 or CDIP2-T8	8	Dual-in-line

1.2.3 Lead finish. The lead finish shall be as specified in MIL-M-38510. Finish letter "X" shall not be marked on the microcircuit or its packaging. The "X" designation is for use in specifications when lead finishes A, B, and C are considered acceptable and interchangeable without preference.

1.3 Absolute maximum ratings.

Supply voltage ( $V_S$ ) . . . . .	±18 V
Storage temperature range . . . . .	-65°C to +150°C
Common-mode input voltage . . . . .	$ V_S  - 3$ V
Output short circuit duration . . . . .	Indefinite
Differential input voltage . . . . .	±1 V
Continuous input current:	
Inverting or noninverting . . . . .	2.0 mA
Lead temperature (soldering, 60 seconds) . . . . .	+300°C
Internal power dissipation: <u>2/</u>	
Cavity package . . . . .	1.3 W
Thermal resistance, junction-to-case ( $\theta_{JC}$ ) . . . . .	+30°C/W
Thermal resistance, junction-to-ambient ( $\theta_{JA}$ ) . . . . .	+110°C/W

1.4 Recommended operating conditions.

Positive supply voltage ( $+V_S$ ) . . . . .	+15 V
Negative supply voltage ( $-V_S$ ) . . . . .	-15 V
Ambient operating temperature range ( $T_A$ ) . . . . .	-55°C to +125°C

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.  
2/ Maximum internal power dissipation is specified so that  $T_J$  does not exceed +175°C at an ambient temperature of +25°C, derate P package at 8.7 mW/°C.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89646
		REVISION LEVEL	SHEET 2

2. APPLICABLE DOCUMENTS.

2.1 Government specification, standards, and bulletin. Unless otherwise specified, the following specification, standards, and bulletin of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARDS

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.  
MIL-STD-1835 - Microcircuit Case Outlines.

BULLETIN

MILITARY

MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

(Copies of the specification, standards, and bulletin required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.2 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-BUL-103 (see 6.6 herein).

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.6 herein). The certificate of compliance submitted to DESC-EC prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89646
		REVISION LEVEL	SHEET 3

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C ≤ T <sub>A</sub> ≤ +125°C V <sub>S</sub> = ±15 V unless otherwise specified	Group A subgroups	Device type	Limits 1/		Unit
					Min	Max	
Input offset voltage	V <sub>IO</sub>	V <sub>CM</sub> = 0 V 2/	1	01	-200	+200	μV
			2,3		-350	+350	
Power supply rejection ratio	+PSRR	+V <sub>S</sub> = +5 V to +18 V, -V <sub>S</sub> = -15 V	1	01	110		dB
			2,3		94		
	-PSRR	+V <sub>S</sub> = +15 V, -V <sub>S</sub> = -5 V to -18 V	1	01	110		dB
			2,3		94		
Output voltage swing	+V <sub>OUT</sub>	R <sub>L</sub> = 500Ω, T <sub>A</sub> = +25°C	1	01	10		V
	-V <sub>OUT</sub>				-10		
Quiescent current	I <sub>Q</sub>	V <sub>OUT</sub> = 0 V	1	01		6	mA
			2,3			7	
Input bias current	+I <sub>IB</sub>	V <sub>CM</sub> = 0 V 3/	1	01	-15	+15	μA
			2,3		-20	+20	
	-I <sub>IB</sub>	3/	1	01	-450	+450	nA
			2,3		-1.5	+1.5	
Common mode input voltage range	+IVR	4/	1,2,3	01	+10		V
	-IVR				-10		
Open loop transresistance		V <sub>OUT</sub> = ±10 V, R <sub>L</sub> = 500Ω	1	01	100		MΩ
			2,3		50		
Input bias current versus temperature	$\frac{\Delta +I_{IB}}{\Delta T}$	3/ 5/	4,5,6	01	-80	+80	nA/°C
	$\frac{\Delta -I_{IB}}{\Delta T}$				-20	+20	

See footnotes at end of table.

STANDARDIZED  
MILITARY DRAWING  
DEFENSE ELECTRONICS SUPPLY CENTER  
DAYTON, OHIO 45444

SIZE  
A

5962-89646

REVISION LEVEL

SHEET

4

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C ≤ T <sub>A</sub> ≤ +125°C V <sub>S</sub> = ±15 V unless otherwise specified	Group A subgroups	Device type	Limits 1/		Unit
					Min	Max	
Input bias current versus supply	$\frac{\Delta I_{IB}}{\Delta V_S}$	V <sub>S</sub> = 5 V to 18 V 3/ 5/	4	01	-15	+15	nA/V
			5,6		-20	+20	
	$\frac{\Delta -I_{IB}}{\Delta V_S}$		4		-15	+15	
			5,6		-25	+25	
Input bias current versus common-mode	$\frac{\Delta I_{IB}}{\Delta V_{CM}}$	V <sub>CM</sub> = ±10 V 3/ 5/	4	01	-15	+15	nA/V
			5,6		-20	+20	
	$\frac{\Delta -I_{IB}}{\Delta V_{CM}}$		4		-10	+10	
			5,6		-20	+20	
Input resistance	+R <sub>IN</sub>	T <sub>A</sub> = +25°C 5/	4	01	6		kΩ
	-R <sub>IN</sub>				30		Ω
Common-mode rejection ratio	CMRR	V <sub>CM</sub> = ±10 V	1	01	110		dB
			2,3		94		
Small signal bandwidth (-3 dB)	SSBW	A <sub>V</sub> = -1, R <sub>F</sub> = 1 kΩ, 5/ T <sub>A</sub> = +25°C	4	01	50		MHz
Slew rate	+SR	A <sub>V</sub> = -1, R <sub>L</sub> = 1 kΩ, 5/ V <sub>OUT</sub> = -5.0 V to 5.0 V, measured from 10 percent to 90 percent point, rising edge	4	01	300		V/μs
			5,6		200		
	-SR		4		300		
			5,6		200		
Rise time	t <sub>R</sub>	A <sub>V</sub> = -1, T <sub>A</sub> = +25°C 5/	4	01		13	ns

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89646
		REVISION LEVEL	SHEET 5

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ $V_S = \pm 15\text{ V}$ unless otherwise specified	Group A subgroups	Device type	Limits <sup>1/</sup>		Unit
					Min	Max	
Overshoot	OS	$A_V = -1, T_A = +25^{\circ}\text{C},$ <sup>5/</sup> $R_L = \infty$	4	01		35	%
Settling time	$t_s$	$A_V = -1, T_A = +25^{\circ}\text{C},$ <sup>5/</sup> 10 V step at 0.1 percent of the fixed value, $R_L = \infty$	4	01		120	ns

- 1/ The algebraic convention, whereby the most negative value is a minimum and the most positive is a maximum, is used in this table. Negative current shall be defined as conventional current flow out of a device terminal.
- 2/ Input offset voltage parameters are guaranteed after the equivalent of 5 minutes at  $T_A = +25^{\circ}\text{C}$ .
- 3/ Bias current parameters are guaranteed maximum after the equivalent of 5 minutes at  $T_A = +25^{\circ}\text{C}$ .
- 4/ This parameter is guaranteed by testing common-mode rejection ratio.
- 5/ If not tested, this parameter shall be guaranteed to the limits specified in table I herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DESC-EC shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.9 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-89646
		REVISION LEVEL	SHEET 6

Device type	01
Case outline	P
Terminal number	Terminal symbol
1	NC
2	-INPUT
3	+INPUT
4	-V <sub>S</sub>
5	COMPENSATION
6	OUTPUT
7	+V <sub>S</sub>
8	NC

NC = No connection

FIGURE 1. Terminal connections.

<b>STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444</b>	<b>SIZE A</b>		<b>5962-89646</b>
		<b>REVISION LEVEL</b>	<b>SHEET 7</b>

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition B. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.

(2)  $T_A = +125^\circ\text{C}$ , minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 7, 8, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test conditions, method 1005 of MIL-STD-883.

(1) Test condition B. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.

(2)  $T_A = +125^\circ\text{C}$ , minimum.

(3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89646
		REVISION LEVEL	SHEET 8



TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (in accordance with method 5005, table I)
Interim electrical parameters (method 5004)	1
Final electrical test parameters (method 5004)	1*, 2, 3, 4, 5, 6
Group A test requirements (method 5005)	1, 2, 3, 4, 5, 6
Groups C and D end-point electrical parameters (method 5005)	1

\* PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for original equipment manufacturer application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.4 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and the applicable SMD. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DESC-EC, telephone (513) 296-6047.

6.5 Comments. Comments on this drawing should be directed to DESC-EC, Dayton, Ohio 45444, or telephone (513) 296-5377.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-EC.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89646
		REVISION LEVEL	SHEET 9