

# 74LVT16245B; 74LVTH16245B

3.3 V 16-bit transceiver; 3-state

Rev. 8 — 17 June 2011

Product data sheet

## 1. General description

---

The 74LVT16245B; 74LVTH16245B is a high-performance BiCMOS product designed for  $V_{CC}$  operation at 3.3 V.

This device is a 16-bit transceiver featuring non-inverting 3-state bus compatible outputs in both send and receive directions. The control function implementation minimizes external timing requirements. The device features an output enable input ( $\overline{nOE}$ ) for easy cascading and a direction input ( $nDIR$ ) for direction control.

## 2. Features and benefits

---

- 16-bit bidirectional bus interface
- 3-state buffers
- Output capability: +64 mA and -32 mA
- TTL input and output switching levels
- Input and output interface capability to systems at 5 V supply
- Bus hold data inputs eliminate need for external pull-up resistors to hold unused inputs
- Live insertion and extraction permitted
- Power-up 3-state
- No bus current loading when output is tied to 5 V bus
- Latch-up protection:
  - ◆ JESD78B Class II exceeds 500 mA
- ESD protection:
  - ◆ HBM JESD22-A114F exceeds 2000 V
  - ◆ MM JESD22-A115-A exceeds 200 V




### 3. Ordering information

Table 1. Ordering information


| Type number                       | Package           |          |  | Version   |
|-----------------------------------|-------------------|----------|--|-----------|
|                                   | Temperature range | Name     | Description  |           |
| 74LVT16245BDL<br>74LVTH16245BDL   | -40 °C to +85 °C  | SSOP48   | plastic shrink small outline package; 48 leads;<br>body width 7.5 mm   | SOT370-1  |
| 74LVT16245BDGG<br>74LVTH16245BDGG | -40 °C to +85 °C  | TSSOP48  | plastic thin shrink small outline package; 48 leads;<br>body width 6.1 mm  | SOT362-1  |
| 74LVT16245BEV                     | -40 °C to +85 °C  | VFPGA56  | plastic very thin fine-pitch ball grid array package;<br>56 balls; body 4.5 × 7 × 0.65 mm                                | SOT702-1  |
| 74LVT16245BBX<br>74LVTH16245BBX   | -40 °C to +85 °C  | HXQFN60U | plastic thermal enhanced extremely thin quad flat<br>package; no leads; 60 terminals; UTLP based;<br>body 4 × 6 × 0.5 mm | SOT1134-1 |

### 4. Functional diagram



Pin numbers are shown for SSOP48 and TSSOP48 packages only.

Fig 1. Logic symbol



Pin numbers are shown for SSOP48 and TSSOP48 packages only.

**Fig 2. IEC logic symbol**

## 5. Pinning information

### 5.1 Pinning





Fig 3. Pin configuration for SSOP48 and TSSOP48

Fig 4. Pin configuration for VFBGA56



## 5.2 Pin description

Table 2. Pin description

| Symbol          | Pin                            |                                |  | Description                      |
|-----------------|--------------------------------|--------------------------------|--|----------------------------------|
|                 | SOT370-1 and SOT362-1          | SOT702-1                       | SOT1134-1  |                                  |
| 1DIR, 2DIR      | 1, 24                          | A1, K1                         | A30, A13   | direction control input          |
| 1B0 to 1B7      | 2, 3, 5, 6, 8, 9, 11, 12       | B2, B1, C2, C1, D2, D1, E2, E1 | B20, A31, D5, D1, A2, B2, B3, A5                     | data input/output                |
| 2B0 to 2B7      | 13, 14, 16, 17, 19, 20, 22, 23 | F1, F2, G1, G2, H1, H2, J1, J2 | A6, B5, B6, A9, D2, D6, A12, B8                      | data input/output                |
| GND             | 4, 10, 15, 21, 28, 34, 39, 45  | B3, D3, G3, J3, J4, G4, D4, B4 | A32, A3, A8, A11, A16, A19, A24, A27                 | ground (0 V)                     |
| V <sub>CC</sub> | 7, 18, 31, 42                  | C3, H3, H4, C4                 | A1, A10, A17, A26                                    | supply voltage                   |
| 1OE, 2OE        | 48, 25                         | A6, K6                         | A29, A14   | output enable input (active LOW) |
| 2A0 to 2A7      | 36, 35, 33, 32, 30, 29, 27, 26 | F6, F5, G6, G5, H6, H5, J6, J5 | A21, B13, B12, A18, D3, D7, A15, B10                 | data input/output                |
| 1A0 to 1A7      | 47, 46, 44, 43, 41, 40, 38, 37 | B5, B6, C5, C6, D5, D6, E5, E6 | B18, A28, D8, D4, A25, B16, B15, A22                 | data input/output                |
| n.c.            | -                              | A2, A3, A4, A5, K2, K3, K4, K5 | A4, A7, A20, A23, B1, B4, B7, B9, B11, B14, B17, B19 | not connected                    |

## 6. Functional description

### 6.1 Function table

Table 3. Function table [1]

| Control |      | Input/output     |                  |
|---------|------|------------------|------------------|
| nOE     | nDIR | nAn              | nBn              |
| L       | L    | output nAn = nBn | input            |
| L       | H    | input            | output nBn = nAn |
| H       | X    | Z                | Z                |

[1] H = HIGH voltage level;  
 L = LOW voltage level;  
 X = don't care;  
 Z = high-impedance OFF-state.

## 7. Limiting values

**Table 4. Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol    | Parameter               | Conditions                        | Min      | Max  | Unit |
|-----------|-------------------------|-----------------------------------|----------|------|------|
| $V_{CC}$  | supply voltage          |                                   | -0.5     | +4.6 | V    |
| $V_I$     | input voltage           |                                   | [1] -0.5 | +7.0 | V    |
| $V_O$     | output voltage          | output in OFF-state or HIGH-state | [1] -0.5 | +7.0 | V    |
| $I_{IK}$  | input clamping current  | $V_I < 0$ V                       | -50      | -    | mA   |
| $I_{OK}$  | output clamping current | $V_O < 0$ V                       | -50      | -    | mA   |
| $I_O$     | output current          | output in LOW-state               | -        | 128  | mA   |
|           |                         | output in HIGH-state              | -64      | -    | mA   |
| $T_{stg}$ | storage temperature     |                                   | -65      | +150 | °C   |
| $T_j$     | junction temperature    |                                   | [2] -    | 150  | °C   |
| $P_{tot}$ | total power dissipation | $T_{amb} = -40$ °C to +85 °C;     |          |      |      |
|           |                         | (T)SSOP48 package                 | [3] -    | 500  | mW   |
|           |                         | VFBGA56 package                   | [4] -    | 1000 | mW   |
|           |                         | HXQFN60U package                  | [4] -    | 1000 | mW   |

- [1] The input and output negative voltage ratings may be exceeded if the input and output clamp current ratings are observed.
- [2] The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.
- [3] Above 60 °C the value of  $P_{tot}$  derates linearly with 5.5 mW/K.
- [4] Above 70 °C the value of  $P_{tot}$  derates linearly with 1.8 mW/K.

## 8. Recommended operating conditions

**Table 5. Recommended operating conditions**

| Symbol              | Parameter                           | Conditions  | Min | Typ | Max | Unit |
|---------------------|-------------------------------------|---|-----|-----|-----|------|
| $V_{CC}$            | supply voltage                      |   | 2.7 | -   | 3.6 | V    |
| $V_I$               | input voltage                       |   | 0   | -   | 5.5 | V    |
| $V_{IH}$            | HIGH-level input voltage            |   | 2.0 | -   | -   | V    |
| $V_{IL}$            | LOW-level input voltage             |   | -   | -   | 0.8 | V    |
| $I_{OH}$            | HIGH-level output current           |   | -32 | -   | -   | mA   |
| $I_{OL}$            | LOW-level output current            | none  | -   | -   | 32  | mA   |
|                     |                                     | current duty cycle $\leq 50$ %;<br>$f_i \geq 1$ kHz | -   | -   | 64  | mA   |
| $T_{amb}$           | ambient temperature                 | in free-air   | -40 | -   | +85 | °C   |
| $\Delta t/\Delta V$ | input transition rise and fall rate | outputs enabled                                     | -   | -   | 10  | ns/V |

## 9. Static characteristics

**Table 6. Static characteristics**

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol  | Parameter                          | Conditions   | Min                   | Typ             | Max  | Unit    |
|---|------------------------------------|--|-----------------------|-----------------|------|---------|
| <b>T<sub>amb</sub> = -40 °C to +85 °C</b> [1] |                                    |  |                       |                 |      |         |
| V <sub>IK</sub>                               | input clamping voltage             | V <sub>CC</sub> = 2.7 V; I <sub>IK</sub> = -18 mA  | -1.2                  | -0.85           | -    | V       |
| V <sub>OH</sub>                               | HIGH-level output voltage          | I <sub>OH</sub> = -100 μA; V <sub>CC</sub> = 2.7 V to 3.6 V  | V <sub>CC</sub> - 0.2 | V <sub>CC</sub> | -    | V       |
|   |                                    | I <sub>OH</sub> = -8 mA; V <sub>CC</sub> = 2.7 V   | 2.4                   | 2.5             | -    | V       |
|   |                                    | I <sub>OH</sub> = -32 mA; V <sub>CC</sub> = 3.0 V  | 2.0                   | 2.3             | -    | V       |
| V <sub>OL</sub>                               | LOW-level output voltage           | V <sub>CC</sub> = 2.7 V  |                       |                 |      |         |
|   |                                    | I <sub>OL</sub> = 100 μA   | -                     | 0.07            | 0.2  | V       |
|   |                                    | I <sub>OL</sub> = 24 mA  | -                     | 0.3             | 0.5  | V       |
|   |                                    | V <sub>CC</sub> = 3.0 V  |                       |                 |      |         |
|   |                                    | I <sub>OL</sub> = 16 mA  | -                     | 0.25            | 0.4  | V       |
|   |                                    | I <sub>OL</sub> = 32 mA  | -                     | 0.3             | 0.5  | V       |
| I <sub>I</sub>                                | input leakage current              | control pins   |                       |                 |      |         |
|   |                                    | V <sub>CC</sub> = 3.6 V; V <sub>I</sub> = V <sub>CC</sub> or GND   | -                     | 0.1             | ±1   | μA      |
|   |                                    | V <sub>CC</sub> = 0 V or 3.6 V; V <sub>I</sub> = 5.5 V   | -                     | 0.1             | 10   | μA      |
|   |                                    | input/output data pins; V <sub>CC</sub> = 3.6 V  | [2]                   |                 |      |         |
|   |                                    | V <sub>I</sub> = 5.5 V   | -                     | 0.1             | 20   | μA      |
|   |                                    | V <sub>I</sub> = V <sub>CC</sub>   | -                     | 0.5             | 10   | μA      |
| I <sub>OFF</sub>                              | power-off leakage current          | V <sub>CC</sub> = 0 V; V <sub>I</sub> or V <sub>O</sub> = 0 V to 4.5 V   | -                     | 0.1             | ±100 | μA      |
|   |                                    | V <sub>CC</sub> = 3 V; V <sub>I</sub> = 0.8 V  | [3]                   | 75              | 135  | μA      |
| I <sub>BHL</sub>                              | bus hold LOW current               | V <sub>CC</sub> = 3 V; V <sub>I</sub> = 0.8 V  | [3]                   | 75              | 135  | μA      |
| I <sub>BHH</sub>                              | bus hold HIGH current              | V <sub>CC</sub> = 3 V; V <sub>I</sub> = 2.0 V  | -                     | -135            | -75  | μA      |
| I <sub>BHLO</sub>                             | bus hold LOW overdrive current     | nAn input; V <sub>I</sub> = 0 V to 3.6 V; V <sub>CC</sub> = 3.6 V  | 500                   | -               | -    | μA      |
| I <sub>BHHO</sub>                             | bus hold HIGH overdrive current    | nAn input; V <sub>I</sub> = 0 V to 3.6 V; V <sub>CC</sub> = 3.6 V  | -                     | -               | -500 | μA      |
| I <sub>LO</sub>                               | output leakage current             | output in HIGH-state when V <sub>O</sub> > V <sub>CC</sub> ; V <sub>O</sub> = 5.5 V; V <sub>CC</sub> = 3.0 V   | -                     | 75              | 125  | μA      |
| I <sub>O(pu/pd)</sub>                         | power-up/power-down output current | V <sub>CC</sub> ≤ 1.2 V; V <sub>O</sub> = 0.5 V to V <sub>CC</sub> ; V <sub>I</sub> = GND or V <sub>CC</sub> ; n $\overline{\text{OE}}$ = don't care | [4]                   | -               | 40   | ±100 μA |
| I <sub>CC</sub>                               | supply current                     | V <sub>CC</sub> = 3.6 V; V <sub>I</sub> = GND or V <sub>CC</sub> ; I <sub>O</sub> = 0 A  |                       |                 |      |         |
|   |                                    | outputs HIGH   | -                     | 0.07            | 0.12 | mA      |
|   |                                    | outputs LOW  | -                     | 4.7             | 6.0  | mA      |
|   |                                    | outputs disabled   | [5]                   | -               | 0.07 | 0.12    |
| ΔI <sub>CC</sub>                              | additional supply current          | per input pin; V <sub>CC</sub> = 3.0 V to 3.6 V; one input at V <sub>CC</sub> - 0.6 V, other inputs at V <sub>CC</sub> or GND                        | [6]                   | -               | 0.1  | 0.2 mA  |
| C <sub>I</sub>                                | input capacitance                  | pins nDIR and n $\overline{\text{OE}}$ , V <sub>O</sub> = 0 V or 3.0 V   | -                     | 3               | -    | pF      |



**Table 6. Static characteristics ...continued**

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol        | Parameter                          | Conditions   | Min | Typ | Max | Unit |
|---------------|------------------------------------|--|-----|-----|-----|------|
| $C_{iO(off)}$ | off-state input/output capacitance | pins nAn and nBn, outputs disabled;<br>$V_O = GND$ or $V_{CC}$ | -   | 9   | -   | pF   |

- [1] Typical values are measured at  $V_{CC} = 3.3$  V and at  $T_{amb} = 25$  °C.
- [2] Unused pins at  $V_{CC}$  or GND.
- [3] This is the bus hold overdrive current required to force the input to the opposite logic state.
- [4] This parameter is valid for any  $V_{CC}$  between 0 V and 1.2 V with a transition time of up to 10 ms. From  $V_{CC} = 1.2$  V to  $V_{CC} = 3.3$  V  $\pm$  0.3 V a transition time of 100  $\mu$ s is permitted. This parameter is valid for  $T_{amb} = 25$  °C only.
- [5]  $I_{CC}$  is measured with outputs pulled to  $V_{CC}$  or GND.
- [6] This is the increase in supply current for each input at the specified voltage level other than  $V_{CC}$  or GND.

## 10. Dynamic characteristics


**Table 7. Dynamic characteristics**

Voltages are referenced to GND (ground = 0 V); for test circuit see [Figure 8](#).

| Symbol  | Parameter                           | Conditions   | Min | Typ <sup>[1]</sup> | Max | Unit |
|---|-------------------------------------|--|-----|--------------------|-----|------|
| <b><math>T_{amb} = -40</math> °C to <math>+85</math> °C</b> |                                     |  |     |                    |     |      |
| $t_{PLH}$   | LOW to HIGH propagation delay       | nAn to nBn or nBn to nAn;<br>see <a href="#">Figure 6</a>    |     |                    |     |      |
|   |                                     | $V_{CC} = 2.7$ V   | -   | -                  | 3.5 | ns   |
|   |                                     | $V_{CC} = 3.0$ V to 3.6 V                                    | 1.0 | 1.9                | 3.3 | ns   |
| $t_{PHL}$   | HIGH to LOW propagation delay       | nAn to nBn or nBn to nAn;<br>see <a href="#">Figure 6</a>    |     |                    |     |      |
|   |                                     | $V_{CC} = 2.7$ V   | -   | -                  | 3.5 | ns   |
|   |                                     | $V_{CC} = 3.0$ V to 3.6 V                                    | 1.0 | 1.7                | 3.3 | ns   |
| $t_{PZH}$   | OFF-state to HIGH propagation delay | $\overline{nOE}$ to nAn or nBn; see <a href="#">Figure 7</a> |     |                    |     |      |
|   |                                     | $V_{CC} = 2.7$ V   | -   | -                  | 5.3 | ns   |
|   |                                     | $V_{CC} = 3.0$ V to 3.6 V                                    | 1.0 | 2.8                | 4.5 | ns   |
| $t_{PZL}$   | OFF-state to LOW propagation delay  | $\overline{nOE}$ to nAn or nBn; see <a href="#">Figure 7</a> |     |                    |     |      |
|   |                                     | $V_{CC} = 2.7$ V   | -   | -                  | 5.1 | ns   |
|   |                                     | $V_{CC} = 3.0$ V to 3.6 V                                    | 1.0 | 2.8                | 4.1 | ns   |
| $t_{PHZ}$   | HIGH to OFF-state propagation delay | $\overline{nOE}$ to nAn or nBn; see <a href="#">Figure 7</a> |     |                    |     |      |
|   |                                     | $V_{CC} = 2.7$ V   | -   | -                  | 5.7 | ns   |
|   |                                     | $V_{CC} = 3.0$ V to 3.6 V                                    | 1.5 | 3.2                | 5.1 | ns   |
| $t_{PLZ}$   | LOW to OFF-state propagation delay  | $\overline{nOE}$ to nAn or nBn; see <a href="#">Figure 7</a> |     |                    |     |      |
|   |                                     | $V_{CC} = 2.7$ V   | -   | -                  | 4.6 | ns   |
|   |                                     | $V_{CC} = 3.0$ V to 3.6 V                                    | 1.5 | 3.0                | 4.6 | ns   |


- [1] All typical values are at  $V_{CC} = 3.3$  V and  $T_{amb} = 25$  °C.

11. Waveforms



Measurements points are given in [Table 8](#).  
 $V_{OL}$  and  $V_{OH}$  are typical voltage output levels that occur with the output load.

**Fig 6. Propagation delay input (nAn, nBn) to output (nBn, nAn)**




Measurements points are given in [Table 8](#).  
 $V_{OL}$  and  $V_{OH}$  are typical voltage output levels that occur with the output load.

**Fig 7. 3-state output enable and disable times**

**Table 8. Measurement points**

| Input | Output |                  |                  |
|-------|--------|------------------|------------------|
| $V_M$ | $V_M$  | $V_X$            | $V_Y$            |
| 1.5 V | 1.5 V  | $V_{OL} + 0.3 V$ | $V_{OH} - 0.3 V$ |



Test data is given in [Table 9](#).

Definitions test circuit:

$R_L$  = Load resistance.

$C_L$  = Load capacitance including jig and probe capacitance.

$R_T$  = Termination resistance should be equal to output impedance  $Z_o$  of the pulse generator.

$V_{EXT}$  = External voltage for measuring switching times.

**Fig 8. Test circuit for measuring switching times**

**Table 9. Test data**

| Input |               |        |               | Load  |              | $V_{EXT}$          |                    |                    |
|-------|---------------|--------|---------------|-------|--------------|--------------------|--------------------|--------------------|
| $V_I$ | $f_i$         | $t_W$  | $t_r, t_f$    | $C_L$ | $R_L$        | $t_{PHZ}, t_{PZH}$ | $t_{PLZ}, t_{PZL}$ | $t_{PLH}, t_{PHL}$ |
| 2.7 V | $\leq 10$ MHz | 500 ns | $\leq 2.5$ ns | 50 pF | 500 $\Omega$ | GND                | 6 V                | open               |

12. Package outline

SSOP48: plastic shrink small outline package; 48 leads; body width 7.5 mm

SOT370-1




Fig 9. Package outline SOT370-1 (SSOP48)

TSSOP48: plastic thin shrink small outline package; 48 leads; body width 6.1 mm

SOT362-1




Fig 10. Package outline SOT362-1 (TSSOP48)

VFBGA56: plastic very thin fine-pitch ball grid array package; 56 balls; body 4.5 x 7 x 0.65 mm

SOT702-1




Fig 11. Package outline SOT702-1 (VFBGA56)

**HXQFN60U: plastic thermal enhanced extremely thin quad flat package; no leads;**  
**60 terminals; UTLP based; body 4 x 6 x 0.5 mm**

SOT1134-1




Fig 12. Package outline SOT1134-1 (HXQFN60U)

## 13. Abbreviations

**Table 10. Abbreviations**

| Acronym | Description                                     |
|---------|---|
| BiCMOS  | Bipolar Complementary Metal Oxide Semiconductor |
| DUT     | Device Under Test                               |
| ESD     | ElectroStatic Discharge                         |
| HBM     | Human Body Model                                |
| MM      | Machine Model                                   |
| TTL     | Transistor-Transistor Logic                     |

## 14. Revision history

**Table 11. Revision history**

| Document ID          | Release date   | Data sheet status     | Change notice | Supersedes           |
|----------------------|--|-----------------------|---------------|----------------------|
| 74LVT_LVTH16245B v.8 | 20110617   | Product data sheet    | -             | 74LVT_LVTH16245B v.7 |
| Modifications:       | <ul style="list-style-type: none"> <li>74LVT16245BBQ and 74LVTH16245BBQ changed to 74LVT16245BBX and 74LVTH16245BBX for HXQFN60U (SOT1134-1) package.</li> </ul> |                       |               |                      |
| 74LVT_LVTH16245B v.7 | 20100329   | Product data sheet    | -             | 74LVT_LVTH16245B v.6 |
| Modifications:       | <ul style="list-style-type: none"> <li>74LVT16245BBQ and 74LVTH16245BBQ changed from HUQFN60U (SOT1025-1) to HXQFN60U (SOT1134-1) package.</li> </ul>            |                       |               |                      |
| 74LVT_LVTH16245B v.6 | 20090409   | Product data sheet    | -             | 74LVT_LVTH16245B v.5 |
| 74LVT_LVTH16245B v.5 | 20090312   | Product data sheet    | -             | 74LVT_LVTH16245B v.4 |
| 74LVT_LVTH16245B v.4 | 20060323   | Product data sheet    | -             | 74LVT16245B v.3      |
| 74LVT16245B v.3      | 20021031   | Product data sheet    | -             | 74LVT16245B v.2      |
| 74LVT16245B v.2      | 19980219   | Product specification | -             | 74LVT16245B v.1      |
| 74LVT16245B v.1      | 19940523   | Product specification | -             | -                    |



## 15. Legal information

### 15.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

### 15.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 15.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use in automotive applications** — This NXP Semiconductors product has been qualified for use in automotive applications. The product is not designed, authorized or warranted to be

suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

## 15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 16. Contact information

---

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

## 17. Contents

---

|           |   |           |
|-----------|---|-----------|
| <b>1</b>  | <b>General description</b> .....              | <b>1</b>  |
| <b>2</b>  | <b>Features and benefits</b> .....            | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> .....             | <b>2</b>  |
| <b>4</b>  | <b>Functional diagram</b> .....               | <b>2</b>  |
| <b>5</b>  | <b>Pinning information</b> .....              | <b>4</b>  |
| 5.1       | Pinning .....                                 | 4         |
| 5.2       | Pin description .....                         | 6         |
| <b>6</b>  | <b>Functional description</b> .....           | <b>6</b>  |
| 6.1       | Function table .....                          | 6         |
| <b>7</b>  | <b>Limiting values</b> .....                  | <b>7</b>  |
| <b>8</b>  | <b>Recommended operating conditions</b> ..... | <b>7</b>  |
| <b>9</b>  | <b>Static characteristics</b> .....           | <b>8</b>  |
| <b>10</b> | <b>Dynamic characteristics</b> .....          | <b>9</b>  |
| <b>11</b> | <b>Waveforms</b> .....                        | <b>10</b> |
| <b>12</b> | <b>Package outline</b> .....                  | <b>12</b> |
| <b>13</b> | <b>Abbreviations</b> .....                    | <b>16</b> |
| <b>14</b> | <b>Revision history</b> .....                 | <b>16</b> |
| <b>15</b> | <b>Legal information</b> .....                | <b>17</b> |
| 15.1      | Data sheet status .....                       | 17        |
| 15.2      | Definitions .....                             | 17        |
| 15.3      | Disclaimers .....                             | 17        |
| 15.4      | Trademarks .....                              | 18        |
| <b>16</b> | <b>Contact information</b> .....              | <b>18</b> |
| <b>17</b> | <b>Contents</b> .....                         | <b>19</b> |

---

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

---

© NXP B.V. 2011.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 17 June 2011

Document identifier: 74LVT\_LVTH16245B