



APT PART NUMBER	DRAIN-SOURCE VOLTAGE BVDSS (VOLTS)	ON RESISTANCE RDS(ON) (OHMS)	DRAIN CURRENT		INPUT CAPACITANCE CISS (pF)	POWER DISSIPATION PD(MAX) (WATTS)	NOTES	CASE STYLE AND DEVICE TYPE
			ID (CONT) (AMPS)	IDM (PULSED) (AMPS)				
APT1001RBN	1000	1.00	11.0	44.0	2450	310	3	TO-3P (TO-247 AD PROPOSED)
APT1001R2BN	1000	1.20	10.0	40.0	2450	310	3	
APT1002RBN	1000	2.00	7.0	28.0	1750	240	3	
APT1002R4BN	1000	2.40	6.5	26.0	1750	240	3	
APT1003R5BN	1000	3.50	4.5	18.0	880	180	3	
APT1004R2BN	1000	4.20	4.0	16.0	880	180	3	
APT901RBN	900	1.00	11.0	44.0	2450	310	3	
APT901R2BN	900	1.20	10.0	40.0	2450	310	3	
APT902RBN	900	2.00	7.0	28.0	1750	240	3	
APT902R4BN	900	2.40	6.5	26.0	1750	240	3	
APT903R5BN	900	3.50	4.5	18.0	880	180	3	
APT904R2BN	900	4.20	4.0	16.0	880	180	3	
APT8075BN	800	0.75	13.0	52.0	2450	310	3	
APT8090BN	800	0.90	12.0	48.0	2450	310	3	
APT801R2BN	800	1.20	9.0	36.0	1750	240	3	
APT801R4BN	800	1.40	8.5	34.0	1750	240	3	
APT802RBN	800	2.00	6.0	24.0	880	180	3	
APT802R4BN	800	2.40	5.5	22.0	880	180	3	
APT7575BN	750	0.75	13.0	52.0	2450	310	3	
APT7590BN	750	0.90	12.0	48.0	2450	310	3	
APT751R2BN	750	1.20	9.0	36.0	1750	240	3	
APT751R4BN	750	1.40	8.5	34.0	1750	240	3	
APT752RBN	750	2.00	6.0	24.0	880	180	3	
APT752R4BN	750	2.40	5.5	22.0	880	180	3	
APT6040BN	600	0.40	18.0	72.0	2400	310	1	
APT6045BN	600	0.45	17.0	68.0	2400	310	1	
APT6060BN	600	0.60	13.0	52.0	1700	240	1	
APT6070BN	600	0.70	12.0	48.0	1700	240	1	
APT601R2BN	600	1.20	8.0	32.0	850	180	1	
APT601R6BN	600	1.60	6.5	26.0	850	180	1	
APT5540BN	550	0.40	18.0	72.0	2400	310	1	
APT5545BN	550	0.45	17.0	68.0	2400	310	1	
APT5560BN	550	0.60	13.0	52.0	1700	240	1	
APT5570BN	550	0.70	12.0	48.0	1700	240	1	
APT551R2BN	550	1.20	8.0	32.0	850	180	1	
APT551R6BN	550	1.60	6.5	26.0	850	180	1	
APT5025BN	500	0.25	23.0	92.0	2400	310	1	
APT5030BN	500	0.30	21.0	84.0	2400	310	1	
APT5040BN	500	0.40	16.0	64.0	1700	240	1	
APT5050BN	500	0.50	14.0	56.0	1700	240	1	
APT5085BN	500	0.85	9.5	38.0	850	180	1	
APT501R1BN	500	1.10	8.0	32.0	850	180	1	
APT4525BN	450	0.25	23.0	92.0	2400	310	1	
APT4530BN	450	0.30	21.0	84.0	2400	310	1	
APT4540BN	450	0.40	16.0	64.0	1700	240	1	
APT4550BN	450	0.50	14.0	56.0	1700	240	1	
APT4585BN	450	0.85	9.5	38.0	850	180	1	
APT451R1BN	450	1.10	8.0	32.0	850	180	1	
APT4020BN	400	0.20	26.0	104.0	2400	310	1	
APT4025BN	400	0.25	23.0	92.0	2400	310	1	
APT4030BN	400	0.30	18.5	74.0	1700	240	1	
APT4040BN	400	0.40	16.0	64.0	1700	240	1	
APT4055BN	400	0.55	12.0	48.0	850	180	1	
APT4080BN	400	0.80	10.0	40.0	850	180	1	
APT3520BN	350	0.20	26.0	104.0	2400	310	1	
APT3525BN	350	0.25	23.0	92.0	2400	310	1	
APT3530BN	350	0.30	18.5	74.0	1700	240	1	
APT3540BN	350	0.40	16.0	64.0	1700	240	1	
APT3555BN	350	0.55	12.0	48.0	850	180	1	
APT3580BN	350	0.80	10.0	40.0	850	180	1	



COMMERCIAL PLASTIC N-CHANNEL MOSFET



NOTE 1. - CURRENTLY AVAILABLE
NOTE 3. - AVAILABLE DECEMBER 1988