

# SURFACE MOUNT 10BASE-T INTERFACE MODULE

## Designed for Level One's LXT907



- ☑ Integrated for adapter, hub, and motherboard applications
- ☑ Designed to meet IEEE 802.3 10Base-T specifications
- ☑ Low profile, surface mount package
- ☑ 235°C peak solder reflow temperature rating

### Electrical Specifications @ 25°C — Operating Temperature 0°C to +70°C

Part Number	Insertion Loss to 10MHz (db MAX)	Attenuation (dB MIN) XMIT			Return Loss 5 to 10 MHz (dB MIN)		Crosstalk (dB MIN) 5-10 MHz	Common Mode Rejection (dB MIN) XMIT					Hi-Pot (Vrms MIN)
		30 MHz	50 MHz	70 MHz	100 Ω	98 ± 13 Ω		30 MHz	50 MHz	100 MHz	200 MHz	500 MHz	
E2015	-1.2	-24	-30	-35	-18	-15	-35	-45	-40	-30	-20	-10	1500

U.S. Patent No. 5,015,981




#### NOTE:

1. For Tape & Reel packaging add a "T" suffix to the part number (i.e.: E2015T).
2. XMIT = Transmit Channel

### Mechanical

### Schematic

#### E2015



Weight ..... 1.1 grams  
Tape & Reel ..... 600/reel  
Tube ..... 40/tube

Dimensions: Inches  
mm

Unless otherwise specified, all tolerances are ± .010 / 0,25

### For More Information :

**Corporate**  
12220 World Trade Drive  
San Diego, CA 92128  
Tel: 619 674 8100  
FAX: 619 674 8262  
http://www.pulseeng.com  
Quick-Facts: 619 674 9672

**Europe**  
Millpool House  
Mill Lane, Godalming  
Surrey GU7 1EY  
U.K.  
Tel: 441 483 428 877  
FAX: 441 483 416 011

**Asia**  
P.O. Box 26-11, KEPZ  
6 Central Sixth Road  
KEPZ, Kaohsiung  
Taiwan, R.O.C.  
Tel: 886 7 821 3141  
FAX: 886 7 841 9707

### Distributor

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other products mentioned herein may be trademarks or registered trademarks of their respective owners.

♻️ Printed on recycled paper. ©1997, Pulse Engineering, Inc.

**PRELIMINARY E118.P (11/97)**