

PULSE TRANSFORMER



A. Electrical specification (@ 25°C)

1. Power rating; 500mW
2. Dielectric strength; 500VDC 1 minute
3. Insulation resistance; 10,000MΩ MIN @ 500VDC
4. Turns ratio;
(1-5):(6-2)=1CT:1.4CT ±5%
5. Primary open circuit inductance;
1000μH MIN @ 1KHz, 40mV (1-5)
6. Primary ET-constant
10.5V-μs MIN
7. Rise time;
7.3ns MAX
8. Interwinding capacitance between primary and secondary;
32.0pF MAX @ 100KHz
9. Primary leakage inductance with shorted secondary;
1.5μH MAX @ 100KHz
10. DC Resistance;
Primary (1-5) 1.5Ω MAX
Secondary (6-2) 1.5Ω MAX


B. Marking;

G517, TAM, date code and country of origin

C. Schematic diagram



D. Mechanical Specification



PREPARED BY:

D. Rund

ENGINEER:

Y. Sekiguchi

QUALITY CONTROL:

D. Kelley

APPROVED:

J. Coleman

DWG CONTROL NO.
P-A1-10854
ACAD\G-SER\A1108541.DWG

REV
A

PULSE
TRANSFORMER

TAMURA CORPORATION OF AMERICA
43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

G517

MODEL SPECIFICATION

DIM: mm[In] SCL: 2/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.