

Spice Model




M100FF3



Electrical Characteristics and Maximum Ratings

Part Number	Working Reverse Voltage	Average Rectified Current		Reverse Current @ V _{rw}		Forward Voltage		1 Cycle Surge Current tp=8.3ms (I _{fsm})	Repetitive Surge Current (I _{frm})	Reverse Recovery Time (3) (T _{rr})	Thermal Impedance			Junction Cap. @50VDC @ 1kHz (C _j)
	(V _{rw})	(I _o)		(I _r)		(V _f)					θ_{J-L}			
	Volts	55°C(1) Amps	100°C(2) Amps	25°C μA	100°C μA	25°C		25°C Amps	25°C Amps	25°C ns	L=.000 °C/W	L=.125 °C/W	L=.250 °C/W	25°C pF
M100FF3	10000	0.020	0.010	0.1	10	25.0	20	1	0.2	30	18	30	50	0.5



Part	A
M50FFX M100FFX	.300(7.62) MAX.
M160FFX	.350(8.89) MAX.

Name	Parameter	Value	Units
IS	Reverse leakage current	1.00E-07	Amps
N	Emission coefficient	70	
T	Temperature	25	C
RS	Diode series resistance	30	Ohm
TT	Transit time	30	nS
CJ0	Zero-bias junction capacitance	0.66	pF
VJ	Bulk junction potential	15.52	Volts
M	Grading coefficient	0.5	
EG	Energy-band gap	1.11	Volts
XTI	Temperature coefficient	3	
KF	Flicker-noise coefficient	0	
AF	Flicker-noise exponent	1	
FC	Coefficient for capacitance	0.5	
BV	Diode breakdown voltage	12000	Volts
IBV	Diode breakdown current	100	uAmps

Dimensions: In. (mm) * All temperatures are ambient unless otherwise noted. * Data subject to change without notice.



Voltage Multipliers, Inc.
8711 W. Roosevelt Ave.
Visalia, CA 93291

Tel (559) 651-1402
Fax (559) 651-0740
www.voltagemultipliers.com