# Opening STATSHIELD® ATTENTION Length (L) & P9 Date & Lot Code Printed for QC Traceablility Side Weld Seals 3/8 in. (± 1/8) Soft Fold Bottom

## STATSHIELD® STANDARD MOISTURE BARRIER BAG



## **Specifications:**

**Standard Document** ANSI/ESD S541 (ANSI/ESD S20.20) ANSI/ESD S11.4

Electrical Properties

Surface Resistance (both exterior and interior) Discharge Shielding Static Shielding Charge Generation

Teflon Quartz

MVTR

**Physical Properties** 

Film Thickness Width (Inside Dimensions) Length (Inside Dimensions) Puncture Strength Heat Seal Strength (Vetrod bar sealer) Seal Strength

Silicone Non-corrosive Marking Adhesion **Typical Values** 

 $1 \times 10^4$  to  $< 1 \times 10^{11}$  ohms

<10 nJ 20 volts

-0.09 nC/sq. in. +0.10 nC/sq. in.

Nominal 0.0035" (.0889mm) ±10% MIL-STD-3010, 1003

Nominal -0" / + 0.125" Nominal ± 1/8" Offset 0 to 1/4"

>20 lbs

>11 (lb/in width)

>12 PSI ≤0.02/g/100sq.in/24hours

Not detected

Pass Pass Meets Requirements of:

**ESD Protective Packaging** Level 2 Technical Requirements

Test Procedures/Method

ANSI/ESD STM11.11 ANSI/ESD STM11.31

EIA 541

Modified incline plane Modified incline plane

MIL-STD-3010, 2065

ASTM D1876-93 ASTM D882 **ASTM F1249** 

**FTIR** 

MIL-STD-3010, M3005 IPC-TM-650 2.4.1

NOTE: The complete dry package concept of packaging for electronics requires three elements:

Statshield® Moisture Barrier Bags - To Protect

**Dessicant - To Absorb Moisture** 

Heavy Duty Static

Dissipative Polvester

Aluminum Shielding

Polyester Layer Aluminum Shielding Layer High Performance Polyethylene

Humidity Indicator Card - To Monitor Performance

For detailed instructions see Technical Bulletin TB-2031 -Moisture Barrier Bags Application Instructions.

#### ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

### **RoHS 2, REACH and Conflict Minerals Statement**

None of the RoHS 2 restricted materials, REACH substances of very high concern as of 2016/06/20, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at Desco.com.



United States of America

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.

Specifications and procedures subject to change without notice.

STATSHIELD® STANDARD, MOISTURE BARRIER BAG, 0.0035" (0.0889mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021 PHONE (781) 821-8370

**DRAWING** NUMBER 13806

DATE: August 2016