

**Desktop Products** 

# M-5400 Series PowerWheel Mouse



## **Key Features**

- Optical sensor for precise movement of the mouse pointer
- PC- and MAC-compatible with USB interface
- Precise performance with 800 dpi resolution
- Easy scrolling with PowerWheel
- Elegant design, ideally suited for right-handed and left-handed users
- Connection and disconnection during operation with USB connector
- Adapter for PS/2 interface

#### **Part Numbers**

M-5400 light grey

M-5450 black



**Desktop Products** 

## M-5400 Series PowerWheel Mouse

#### **Part Number Legend**





#### **Technical Data**

#### System Requirements

USB or PS/2 Interface

#### **Number of Buttons**

3 buttons

#### Cable Lengths

approx. 2.0 m

#### Weight

ca. 135 g (without packaging) ca. 155 g (with packaging)

#### **Dimensions**

approx. 121 x 63 x 38 mm (without packaging) approx. 136 x 89 x 48 mm (with packaging)

#### **Current Input**

max. 100 mA

#### Connection

USB (PS/2 via adapter)

## Resolution

800 dpi

#### **Packaging Units**

50 mice per master carton 1600 or 1200 mice per pallet

#### Storage Temperature

-20 °C to 60 °C

#### **Operating Temperature**

0 °C to 50 °C

#### Agency Approvals

FCC, cURus, GS, CE,GOST-R Microsoft Windows™ XP

#### **Delivery Volume**

- 1 WheelMouse optical
- 1 Adapter for PS/2 interface
- 1 Printed manual

#### Warranty

2 years

For information on repairs or warranty status contact: Cherry Technical Support

Phone: 800.510.1689

E-Mail: keyboardsupport@cherrycorp.com

## Contact

Call, fax or visit our website for more information.

Last Update: 1/01/07

### Cherry Electrical Products

11200 88th Avenue Pleasant Prairie, WI 53158

Phone: 262.942.6500 Web: www.cherrycorp.com

E-Mail: sales@cherrycorp.com Fax: 262.942.6566 The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.