

NYLON 6/6 UL 94 V-2 NATURAL	NYLON 6/6 UL 94 V-2 BLACK	*NYLON 6/6 UL 94 V-0 BLACK	*NYLON 6/6 UL 94 V-0 NATURAL	*UV STABILIZED NYLON 6/6 UL 94 V-2 BLACK	"D" HOLDING DIAMETER	"E" REF.	
N-1	N-1-BK	N-1-19-BK	N-1-19	N-1-UVB	1/16 [1.6]	.27 [6.7]	
N-2	N-2-BK	N-2-19-BK	N-2-19	N-2-UVB	1/8 [3.2]	21/64 [8.3]	
N-3	N-3-BK	N-3-19-BK	N-3-19	N-3-UVB	3/16 [4.8]	25/64 [9.9]	
N-4	N-4-BK	N-4-19-BK	N-4-19	N-4-UVB	1/4 [6.4]	27/64 [10.7]	
N-5	N-5-BK	N-5-19-BK	N-5-19	N-5-UVB	5/16 [7.9]	29/64 [11.5]	
N-6	N-6-BK	N-6-19-BK	N-6-19	N-6-UVB	3/8 [9.5]	31/64 [12.3]	
N-7	N-7-BK	N-7-19-BK	N-7-19	N-7-UVB	7/16 [11.1]	17/32 [13.5]	
N-8	N-8-BK	N-8-19-BK	N-8-19	N-8-UVB	1/2 [12.7]	9/16 [14.3]	



SHOWN AS MOLDED

## NOTES:

- 1. MATERIAL:
  - NYLON 6/6 UL 94 V-2 (RMS-01).
- \*NYLON 6/6 UL 94 V-2 (RMS-19) AVAILABLE BY SPECIAL ORDER ONLY.

  \*NYLON 6/6 UL 94 V-2, UV STABILIZED (RMS-46), COLOR BLACK, AVAILABLE BY SPECIAL ORDER ONLY.

  2. RECOMMENDED SCREW SIZE IS #8 [M4], (#4 [M2.5] FOR N-1).

  3. ALTERNATE UNITS ARE FOR REFERENCE ONLY

O. METERIA VITE ON TO THE PERENCE ONE!											
			TITLE: CABLE CLAMP, N SERIES					DWG IN IN [MM]			
			CREATED USING SOLIDWORKS	FILE #: N-SERIES		DWN: S.K.	APP: R.G.	FINAL			
	SEE CO 200516 FOR CHANGES		1/06/10	IULERANCES	SHEET:	1 OF 1	SHEET SIZE: A	DT: 04/01/2008	CHKD: S.J.	PART#	DDINIT
H	SEE CO 200485 FOR CHANGES	DZ 01/1	2/2010				10			1	PRINT TYPE
G	SEE CO 200152 FOR CHANGES	SK 04/03/2008		8 .XX=±.010 .XXX=±.005	EICHCO, INC.		RICHCO, INC.		SEE TAP		
	SEE ENGINEERING FOR REV A-F		FRAC.=±1/64	<i>'</i>		ENG@RICHCO-INC.COM		OEE TAD			
REV.	DESCRIPTION	ENGR.	DATE	ANG.=±1°				(7/3) 5	39-4060		Ο, ι