

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

MMSTA92

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epitaxial Planar Die Construction
- Ideal for Medium Power Amplification and Switching
- Ultra-small surface mount package
- Marking:K3R
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

 Maximum Ratings

Symbol	Rating	Rating	Unit
V_{CEO}	Collector-Emitter Voltage	300	V
V_{CBO}	Collector-Base Voltage	300	V
V_{EBO}	Emitter-Base Voltage	5.0	V
l _c	Collector Current-Continuous (1) (3)	100	mA
Pc	Power dissipation (1)	200	mW
T_J	Junction Temperature	-55 to +150	°C
T _{STG}	Storage Temperature	-55 to +150	°С

Electrical Characteristics @ 25°C Unless Otherwise Specified

			Units	
OFF CHARACTERISTICS				
Collector-Emitter Breakdown Voltage (L=1.0mAdc, I _B =0)	300		Vdc	
Collector-Base Breakdown Voltage (b=100uAdc, b=0)	300		Vdc	
Collector-Emitter Breakdown Voltage (½=100uAdc, l _C =0)	5.0		Vdc	
Collector-Base Cutoff Current (V _{CB} =200Vdc,I _E =0)		250	nAdc	
Emitter-Base Cutoff Current $(V_{CE}=3.0Vdc, I_{C}=0)$		100	nAdc	
	Collector-Emitter Breakdown Voltage (\$\mathbb{l}_{\}=1.0\text{mAdc}, \$\mathbb{l}_{\}=0)\$ Collector-Base Breakdown Voltage (\$\mathbb{l}_{\}=100\text{uAdc}, \$\mathbb{l}_{\}=0)\$ Collector-Emitter Breakdown Voltage (\$\mathbb{l}_{\}=100\text{uAdc}, \$\mathbr{l}_{\}=0)\$ Collector-Base Cutoff Current (\$\mathbf{V}_{\}_{\}=200\text{Vdc}, \$\mathbr{l}_{\}=0)\$ Emitter-Base Cutoff Current		$ \begin{array}{c cccc} \text{Collector-Emitter Breakdown Voltage} & 300 & \\ & & & & & & & & & & & & & & \\ & & & & & & & & & & & \\ & & & & & & & & & & \\ & & & & & & & & & \\ & & & & & & & & \\ & & & & & & & \\ & & & & & & & \\ & & & & & & & \\ & & & & & \\ & & & & & & \\ & & & & \\ & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & $	

ON CHARACTERISTICS⁽²⁾

h _{FE}	DC Current Gain			
	(I _C =1.0mAdc, V _{CE} =10Vdc)	25		
	$(I_C=10 \text{mAdc}, V_{CE}=10 \text{Vdc})$	40		
	$(I_C=30 \text{mAdc}, V_{CE}=10 \text{Vdc})$	25		
V _{CE(sat)}	Collector-Emitter Saturation Voltage	0.		Vdc
	$(l_c=20 \text{mAdc}, l_B=2.0 \text{mAdc})$			
V _{BE(sat)}	Base-Emitter Saturation Voltage		0.9	Vdc
	$(l_c=20 \text{mAdc}, l_B=2.0 \text{mAdc})$			


SMALL SIGNAL CHARACTERISTICS

f_{T}	Current-Gain-Bandwidth Product	50		MHz
	(V _{CE} =20V, f=100MHz, l _C =10mA)			
ССВ	Collector-Base Capacitance		6.0	pF
	(V _{CB} =20V, f=1.0MHz, l∈=0)			


Note: 1. Valid provided that terminals are kept at ambient temperature.

- 2. Pulse test: Pulse width<300us, duty cycle<2%
- 3. When operated within safe operating area constraints.

PNP Small Signal Transistors



DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.071	.087	1.80	2.20	
В	.045	.053	1.15	1.35	
С	.083	.096	2.10	2.45	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
Н	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.006	.016	.15	.40	





Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.