

# MMST3906

## Features

- Epitaxial Planar Die Construction
- Complementary NPN Type available (MMST3904)
- Ultra-small surface mount package
- Marking : K5N
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Halogen free available upon request by adding suffix "-HF"

## Maximum Ratings

Symbol	Rating	Rating	Unit
$V_{CEO}$	Collector-Emitter Voltage	40	V
$V_{CBO}$	Collector-Base Voltage	40	V
$V_{EBO}$	Emitter-Base Voltage	5.0	V
$I_C$	Collector Current-Continuous <sup>(1)</sup>	200	mA
$P_C$	Power dissipation <sup>(1)</sup>	200	mW
$T_J$	Junction Temperature	-55 to +150	°C
$T_{STG}$	Storage Temperature	-55 to +150	°C

## Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
--------	-----------	-----	-----	-------

### OFF CHARACTERISTICS <sup>(2)</sup>

$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ( $I_C=1.0mA$ , $I_B=0$ )	40	---	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ( $I_C=10uA$ , $I_E=0$ )	40	---	Vdc
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage ( $I_C=10uA$ , $I_C=0$ )	5.0	---	Vdc
$I_{CEX}$	Collector-Base Cutoff Current ( $V_{CE}=30Vdc$ , $V_{EB(OFF)}=3.0Vdc$ )	---	50	nAdc
$I_{BL}$	Emitter-Base Cutoff Current ( $V_{CE}=30Vdc$ , $V_{EB(OFF)}=3.0Vdc$ )	---	50	nAdc


### ON CHARACTERISTICS <sup>(2)</sup>

$h_{FE}$	DC Current Gain ( $I_C=100uA$ , $V_{CE}=1.0Vdc$ ) ( $I_C=1.0mA$ , $V_{CE}=1.0Vdc$ ) ( $I_C=10mA$ , $V_{CE}=1.0Vdc$ ) ( $I_C=50mA$ , $V_{CE}=1.0Vdc$ ) ( $I_C=500mA$ , $V_{CE}=1.0Vdc$ )	60 80 100 60 30	---	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ( $I_C=10mA$ , $I_B=1.0mA$ ) ( $I_C=50mA$ , $I_B=5.0mA$ )	---	0.20 0.30	Vdc	
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ( $I_C=10mA$ , $I_B=1.0mA$ ) ( $I_C=50mA$ , $I_B=5.0mA$ )	0.65 ---	0.85 0.95	Vdc	

Note: 1. Valid provided that terminals are kept at ambient temperature.  
2. Pulse test: Pulse width<300us, duty cycle<2%

## PNP Small Signal Transistors


### SOT-323



#### DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.071	.087	1.80	2.20	
B	.045	.053	1.15	1.35	
C	.083	.096	2.10	2.45	
D	.026 Nominal		0.65Nominal		
E	.047	.055	1.20	1.40	
F	.012	.016	.30	.40	
G	.000	.004	.000	.100	
H	.035	.039	.90	1.00	
J	.004	.010	.100	.250	
K	.006	.016	.15	.40	

### Suggested Solder Pad Layout



**SMALL SIGNAL CHARACTERISTICS**

$C_{obo}$	Output Capacitance ( $V_{CB}=5.0Vdc, f=1.0MHz, I_E=0$ )	---	4.5	pF	
$C_{ibo}$	Input Capacitance ( $V_{EB}=0.5Vdc, f=1.0MHz, I_C=0$ )	---	10	pF	
$h_{ie}$	Input Impedance	$V_{CE}=10Vdc, I_C=1.0mA, f=1.0KHz$	2.0	12	kohms
$h_{re}$	Voltage Feedback Ratio		0.1	10	$\times 10^{-4}$
$h_{fe}$	Small Signal Current Gain		100	400	---
$h_{oe}$	Output Admittance		3.0	60	$\mu S$
$f_T$	Current Gain-Bandwidth Product ( $V_{CE}=20Vdc, I_C=10mA, f=100MHz$ )	300	---	MHz	
NF	Noise Figure ( $V_{CE}=5.0Vdc, I_C=100\mu A, R_S=1.0KOHMS, f=1.0KHz$ )	---	4.0	dB	

**SWITCHING CHARACTERISTICS**

$t_d$	Delay Time	$V_{CC}=3.0Vdc, I_C=10mA, V_{BE(off)}=0.5Vdc, I_{B1}=1.0mA$	---	35	ns
$t_r$	Rise Time		---	35	ns
$t_s$	Storage Time	$V_{CC}=3.0Vdc, I_C=10mA, I_{B1}=I_{B2}=1.0mA$	---	225	ns
$t_f$	Fall Time		---	75	ns



Micro Commercial Components

### Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel; 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.