



## SPEAKER CABLE MODULAR CORD

### SPEAKER CABLE

#### APPLICATIONS:

For use in High Definition Speaker Systems, provides a cable with low capacitance and allows it to be used with all amplifiers as opposed to other specialized high capacitance speaker wires, which cause high frequency oscillation in amplifiers.

**STOCK COLOR:** Clear only

\* CL2 available upon request

OLYMPIC NO.	NUM. OF COND.	CONDUCTOR AWG	STRANDING	NOM. O.D.
2391	2	10	413 x 36	.240" x .485"
2392	2	12	259 x 36	.200" x .415"
2393	2	14	168 x 36	.200" x .415"
2394	2	16	105 x 36	.160" x .335"

### LAMP CORD/SPEAKER CABLE

#### DESCRIPTION:

Stranded bare copper conductors, UL Class 11 60°C PVC, rip type construction for easy separation of conductors, one conductor ribbed for polarity i.d., surface printed with manufacturer's UL identifying code and wire gage

#### APPLICATIONS:

For use with fans, lamps, hanging fixtures, radios, TV sets, stereo and HiFi, small appliances and other applications

#### PACKAGING:

All SPT-1 and SPT-2 wires available on bulk reels (consult factory for pricing and delivery)

\* Custom colors in production quantities available (consult factory for pricing and delivery)

OLYMPIC NO.	CURRENT RATING	CONDUCTOR AWG	STRANDING	UL TYPE	NOM. O.D.	AVAILABLE COLORS
2395	10 AMPS	18	41 x 34	SPT-1	.105" x .210"	BROWN, WHITE, BLACK, CLEAR
2396	10 AMPS	18	41 x 34	SPT-2	.145" x .300"	BROWN, WHITE, BLACK
2397	13 AMPS	16	65 x 34	SPT-2	.155" x .310"	BROWN, WHITE, BLACK, CLEAR
2398	4 AMPS	24	7 x 32		.050" x .120"	CLEAR

### MODULAR CORD 60°C 300V

26 GAGE (7 x 34)

#### UL LISTED

#### DESCRIPTION:

Stranded bare copper, vinyl insulated, conductors parallel, silver vinyl jacket

#### COLOR CODE:

Four Wire - Black, Red, Green, Yellow

Six Wire - White, Black, Red, Green, Yellow, Blue

Eight Wire - Blue, Orange, Black, Red, Green, Yellow, Brown, Grey

Ten Wire - Violet, Blue, Orange, Black, Red, Green, Yellow, Brown, Grey, White

OLYMPIC NO.	NUM. OF COND.	CONDUCTOR AWG	STRANDING	NOM. O.D.
3744-26	4	26	7 x 34	.090" x .193"
3746-26	6	26	7 x 34	.090" x .280"
3748-26	8	26	7 x 34	.090" x .335"
3750-26	10	26	7 x 34	.090" x .430"

VW-1 Flame Test