

ABBATRON

Premier Supplier of Electronic Hardware

HH Smith

[Custom Capabilities](#) [Test Accessories](#) [Plugs, Jacks, Posts](#) [Connectors](#) [Hardware](#) [Spacers/Standoffs](#)

- [Home](#)
- [About Abbatron](#)
- [Products](#)
- [Locate Distributor or Representative](#)
- [Contact Us](#)
- [Request Information](#)
- [Site Map](#)

Ceramic Spacers

- Ceramic spacers are Grade L-5 Steatite, glazed and fired at high temperature
- Threaded from each end as indicated in table
- Continuous safe operating Temperature Rating of 930°C(1700°F)
- Other size Options are available from factory in quantity, as are spacers with different tap sizes at each end for adaption applications



Ceramic
Spacers drawing

Inventory Search

Cross Reference

UPS Tracking

632 Arch Street, POB 726
Meadville, PA 16335 USA
814-724-6440

[Contact Webmaster](#)

© June 6, 2005

PART NO.	LENGTH	O.D.	THREAD		MIL NUMBER		
			SIZE	DEPTH			
2640	1/4	1/4	6-32	THRU	NL 523 WD1 004		
2642	3/8	3/8		5/32			
2641	1/2	1/4		3/16			
2643		3/8		5/32			
2600		1/2		9/64			
2644		3/8		1/4			
2601	5/8	1/2		8-32		3/16	NL 523 WD2 005
2602	3/4	3/8		6-32		1/4	NL 523 WD1 006
2645		1/2	8-32		NL 523 WD2 006		
2608		3/8	6-32	3/8	NL 523 WD1 008		
2603	1/2	8-32			NL 523 WD2 008		
2646	3/4	10-32			NL 523 WD3 008		
2609	1-1/4	3/8	6-32		NL 523 WD1 010		
2615		1/2	8-32		NL 523 WD2 010		
2616		3/4	10-32		NL 523 WD3 010		
2604	1	1/4-20	7/16	NL 523 WD4 010			
2647	1-1/2	1/2	6-32	9/16			
2605		3/8		3/8	NL 523 WD1 012		
2611		1/2	8-32		NL 523 WD2 012		
2617		3/4	10-32		NL 523 WD3 012		
2623		1	1/4-20	1/2	NL 523 WD4 012		
2606	2	3/8	6-32	3/8	NL 523 WD1 016		
2612		1/2	8-32		NL 523 WD2 016		
2618		3/4	10-32		NL 523 WD3 016		
2624		1	1/4-20		5/8	NL 523 WD4 016	
2648	2-1/2	1/2	6-32	1/2			
2613			8-32	3/8	NL 523 WD2 020		
2619		3/4	10-32	3/4	NL 523 WD3 020		
2649			1/4-20	5/8	NL 523 WD4 020		
2625		1	1/4-20	5/8	NL 523 WD4 020		
2614	3	1/2	8-32	3/8	NL 523 WD2 024		
2620		3/4	10-32		NL 523 WD3 024		
2626		1	1/4-20		5/8	NL 523 WD4 024	
2650	4	3/4	10-32	3/4			
2621				3/8	NL 523 WD3 032		
2627		1	1/4-20	5/8	NL 523 WD4 032		
2628	5	1	1/4-20	5/8	NL 523 WD4 040		
2629	6				NL 523 WD4 048		

Maximum Thread Depth					
Thread Size	2 - 56	4 - 40	6 - 32	8 - 32	10 - 32
Thread Length	0.375	0.500	1.000	1.000	1.000
Tapped Thru					
Thread Length	0.250	0.375	0.375	0.375	0.375
Tap each end					

