

## IGBT MODULE ( P-Series )


## Outline Drawing

### Features

- Square SC SOA at  $10 \times I_C$
- Simplified Parallel Connection
- Narrow Distribution of Characteristics
- High Short Circuit Withstand-Capability

### Applications

- High Power Switching
- A.C. Motor Controls
- D.C. Motor Controls
- Uninterruptible Power Supply




## Maximum Ratings and Characteristics

## Equivalent Circuit

### Absolute Maximum Ratings ( $T_c=25^\circ\text{C}$ )

Items	Symbols	Ratings	Units	
Collector-Emitter Voltage	$V_{CES}$	1400	V	
Gate -Emitter Voltage	$V_{GES}$	$\pm 20$	V	
Collector Current	Continuous $T_c=25^\circ\text{C}$	$I_C$	150	
		$I_C$	100	
	1ms $T_c=25^\circ\text{C}$	$I_C$ PULSE	300	
		1ms $T_c=80^\circ\text{C}$	$I_C$ PULSE	200
			$-I_C$	100
Max. Power Dissipation	$P_C$	780	W	
Operating Temperature	$T_j$	+150	$^\circ\text{C}$	
Storage Temperature	$T_{stg}$	-40 ~ +125	$^\circ\text{C}$	
Isolation Voltage	A.C. 1min. $V_{is}$	2500	V	
Screw Torque	Mounting *1	3.5	Nm	
	Terminals *2	3.5		

Note: \*1:Recommendable Value; 2.5 - 3.5 Nm (M5)









### Electrical Characteristics ( at $T_f=25^\circ\text{C}$ )







Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	$I_{CES}$	$V_{GE}=0V$ $V_{CE}=1400V$			2.0	mA
Gate-Emitter Leakage Current	$I_{GES}$	$V_{CE}=0V$ $V_{GE}=\pm 20V$			400	$\mu\text{A}$
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=20V$ $I_C=100\text{mA}$	6.0	8.0	9.0	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$T_f=25^\circ\text{C}$ $V_{GE}=15V$ $I_C=100A$		2.7	3.0	V
		$T_f=125^\circ\text{C}$ $V_{GE}=15V$ $I_C=100A$		3.3		
Input capacitance	$C_{ies}$	$V_{GE}=0V$		10000		pF
Output capacitance	$C_{oes}$	$V_{CE}=10V$		1500		
Reverse Transfer capacitance	$C_{res}$	$f=1\text{MHz}$		650		
Turn-on Time	$t_{ON}$	$V_{CC}=600V$ $I_C=100A$			1.2	$\mu\text{s}$
	$t_r$				0.6	
Turn-off Time	$t_{OFF}$	$V_{GE}=\pm 15V$ $R_G=9.1\Omega$			1.0	$\mu\text{s}$
	$t_f$				0.3	
Diode Forward On-Voltage	$V_F$	$I_F=100A$ $V_{GE}=0V$		2.4	3.3	V
Reverse Recovery Time	$t_{rr}$	$I_F=100A$			350	ns



### Thermal Characteristics

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	$R_{th(j-c)}$	IGBT			0.16	$^\circ\text{C/W}$
	$R_{th(j-e)}$	Diode			0.33	
	$R_{th(c-f)}$	With Thermal Compound		0.025		









For more information, contact:

**Collmer Semiconductor, Inc.**

P.O. Box 702708

Dallas, TX 75370

972-233-1589

972-233-0481 Fax

<http://www.collmer.com>