

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N5190
2N5191
2N5192

NPN Silicon Transistor
General Purpose Power

JEDEC TO-126 Case

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5190, 2N5191, and 2N5192 are Silicon NPN Epitaxial Base Power Transistors designed for Medium power amplifier and switching applications.

MAXIMUM RATINGS (T_A=25°C Unless otherwise noted)

	2N5190	2N5191	2N5192
Collector-Base Voltage	V _{CB0} 40V	60V	80V
Collector-Emitter Voltage	V _{CE0} 40V	60V	80V
Emitter-Base Voltage	V _{EB0}	5.0V	
Collector Current, Continuous	I _C	4.0A	
Collector Current, Peak	I _{CM}	7.0A	
Base Current	I _B	1.0A	
Power Dissipation (T _C =25°C)	P _D	40W	
Operating & Storage Junction Temperature	T _J , T _{stg}	-65 to +150°C	
Thermal Resistance, Junction to Case	θ _{J-C}	3.12°C/W	

ELECTRICAL CHARACTERISTICS (T_C=25°C)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
I _{CB0}	V _{CB} =Rated V _{CB}		100	uA
I _{CEV}	V _{CE} =Rated V _{CEO} , V _{EB} =1.5V		100	uA
I _{CEO}	V _{CE} =Rated V _{CEO}		1.0	mA
I _{EBO}	V _{EB} =5.0V		1.0	mA
BV _{CEO}	I _C =0.1A	40 (2N5190)		V
		60 (2N5191)		V
		80 (2N5192)		V
V _{CE(s)}	I _C =1.5A, I _B =0.15A		0.6	V
V _{CE(s)}	I _C =4.0A, I _B =1.0A		1.4	V
V _{BE(on)}	V _{CE} =2.0V, I _C =1.5A		1.2	V
h _{FE}	V _{CE} =2.0V, I _C =1.5A	25	100	-
		25	100	-
		20	80	-
h _{FE}	V _{CE} =2.0V, I _C =4.0A	10	-	-
		10	-	-
		7.0	-	-
f _T	V _{CE} =10V, I _C =1.0A, f=1.0 MHz	2.0		MHz

