



# TECHNICAL DATA

## PNP POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/514

### Devices

2N6274

2N6277

### Qualified Level

JAN  
JANTX  
JANTXV


### MAXIMUM RATINGS

| Ratings  | Symbol                      | 2N6274      | 2N6277 | Unit        |
|--|-----------------------------|-------------|--------|-------------|
| Collector-Emitter Voltage                      | $V_{CEO}$                   | 100         | 150    | Vdc         |
| Collector-Base Voltage                         | $V_{CBO}$                   | 120         | 180    | Vdc         |
| Emitter-Base Voltage                           | $V_{EBO}$                   | 6.0         |        | Vdc         |
| Base Current                                   | $I_B$                       | 20          |        | Adc         |
| Collector Current                              | $I_C$                       | 50          |        | Adc         |
| Total Power Dissipation                        | @ $T_C = +25^{\circ}C$ (1)  | 250         |        | W           |
|  | @ $T_C = +100^{\circ}C$ (2) | 143         |        | W           |
| Operating & Storage Junction Temperature Range | $T_j, T_{stg}$              | -65 to +200 |        | $^{\circ}C$ |

### THERMAL CHARACTERISTICS

| Characteristics                      | Symbol          | Max. | Unit          |
|--------------------------------------|-----------------|------|---------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 0.7  | $^{\circ}C/W$ |

1) Derate linearly 1.43 W/ $^{\circ}C$  between  $T_C = +25^{\circ}C$  and  $T_C = +200^{\circ}C$



\*See appendix A for package outline

### ELECTRICAL CHARACTERISTICS ( $T_C = 25^{\circ}C$ unless otherwise noted)

| Characteristics | Symbol | Min. | Max. | Unit |
|-----------------|--------|------|------|------|
|-----------------|--------|------|------|------|

### OFF CHARACTERISTICS

|  |                  |               |            |           |
|--|------------------|---------------|------------|-----------|
| Collector-Emitter Breakdown Voltage<br>$I_C = 50$ mAdc   | 2N6274<br>2N6277 | $V_{(BR)CEO}$ | 100<br>150 | Vdc       |
| Collector-Emitter Cutoff Current<br>$V_{CE} = 50$ Vdc<br>$V_{CE} = 75$ Vdc   | 2N6274<br>2N6277 | $I_{CEO}$     | 50<br>50   | $\mu$ Adc |
| Collector-Emitter Cutoff Current<br>$V_{CE} = 120$ Vdc, $V_{BE} = -1.5$ Vdc<br>$V_{CE} = 180$ Vdc, $V_{BE} = -1.5$ Vdc | 2N6274<br>2N6277 | $I_{CEX}$     | 10<br>10   | $\mu$ Adc |
| Emitter-Base Cutoff Current<br>$V_{EB} = 6.0$ Vdc  |                  | $I_{EBO}$     | 100        | $\mu$ Adc |
| Collector-Base Cutoff Current<br>$V_{CB} = 120$ Vdc<br>$V_{CB} = 180$ Vdc  | 2N6274<br>2N6277 | $I_{CBO}$     | 10<br>10   | $\mu$ Adc |



**2N6274, 2N6277 JAN SERIES**

**ELECTRICAL CHARACTERISTICS (con't)**

| Characteristics   | Symbol               | Min.           | Max.       | Unit |
|---|----------------------|----------------|------------|------|
| <b>ON CHARACTERISTICS <sup>(2)</sup></b>  |                      |                |            |      |
| Forward-Current Transfer Ratio<br>I <sub>C</sub> = 1.0 Adc, V <sub>CE</sub> = 4.0 Vdc<br>I <sub>C</sub> = 20 Adc, V <sub>CE</sub> = 4.0 Vdc<br>I <sub>C</sub> = 50 Adc, V <sub>CE</sub> = 4.0 Vdc | h <sub>FE</sub>      | 50<br>30<br>10 | 120        |      |
| Collector-Emitter Saturation Voltage<br>I <sub>C</sub> = 20 Adc, I <sub>B</sub> = 2.0 Adc<br>I <sub>C</sub> = 50 Adc, I <sub>B</sub> = 10 Adc   | V <sub>CE(sat)</sub> |                | 1.0<br>3.0 | Vdc  |
| Base-Emitter Saturation Voltage<br>I <sub>C</sub> = 20 Adc, I <sub>B</sub> = 2.0 Adc  | V <sub>BE(sat)</sub> |                | 1.8        | Vdc  |

**DYNAMIC CHARACTERISTICS**

|   |                  |     |     |    |
|---|------------------|-----|-----|----|
| Magnitude of Common Emitter Small-Signal Short-Circuit Forward Current Transfer Ratio<br>I <sub>C</sub> = 1.0 Adc, V <sub>CE</sub> = 10 Vdc, f = 10 MHz | h <sub>fe</sub>  | 3.0 | 12  |    |
| Output Capacitance<br>V <sub>CB</sub> = 10 Vdc, I <sub>E</sub> = 0, f = 1.0 MHz   | C <sub>obo</sub> |     | 600 | pF |

**SWITCHING CHARACTERISTICS**

|  |                  |  |      |    |
|--|------------------|--|------|----|
| Turn-On Time<br>V <sub>CC</sub> = 80 Vdc; I <sub>C</sub> = 20 Adc; I <sub>B</sub> = 2.0 Adc                      | t <sub>on</sub>  |  | 0.5  | μs |
| Turn-Off Time<br>V <sub>CC</sub> = 80 Vdc; I <sub>C</sub> = 20 Adc; I <sub>B1</sub> = -I <sub>B2</sub> = 2.0 Adc | t <sub>off</sub> |  | 1.05 | μs |

**SAFE OPERATING AREA**

|   |           |
|---|-----------|
| <b>DC Tests</b><br>T <sub>C</sub> = +25°C, 1 Cycle, t = 1.0 s         |           |
| <b>Test 1</b><br>V <sub>CE</sub> = 5.0 Vdc, I <sub>C</sub> = 50 Adc   | All Types |
| <b>Test 2</b><br>V <sub>CE</sub> = 8.6 Vdc, I <sub>C</sub> = 165 mAdc | All Types |
| <b>Test 3</b><br>V <sub>CE</sub> = 80 Vdc, I <sub>C</sub> = 29 mAdc   | 2N6274    |
| <b>Test 4</b><br>V <sub>CE</sub> = 120 Vdc, I <sub>C</sub> = 110 mAdc | 2N6277    |

(2) Pulse Test: Pulse Width = 300μs, Duty Cycle ≤ 2.0%.