

FUJITSU TRANSISTOR

2SC2043

2SC2043 is an NPN epitaxial planar type silicon transistor and is designed for use in output stage of 27MHz-citizen band SSB transceiver application. This transistor has the following outstanding features.

- * Power Output 12 Watts.(PEP)
- * Power Gain 15 dB. (12 W PEP)
- * Large Surge Capability.

MAXIMUM RATINGS (Ambient Temperature: 25 °C)

Item	Symbol	Condition	Rating	Unit
Collector-Base Voltage	V_{CB0}		70	V
Emitter-Base Voltage	V_{EBO}		5	V
Collector-Emitter Voltage	V_{CER}	$R_{BE}=100\text{ ohm}$	70	V
Collector Current	I_C	pulse width 20mS duty 50%	8	A
Total Power Dissipation	P_T	$T_C=25\text{ °C}$	25	W
Junction Temperature	T_j		+150	°C
Storage Temperature	T_{stg}		-55 ~ +150	°C

ELECTRICAL CHARACTERISTICS (Ambient Temperature: 25 °C)

Item	Symbol	Test Condition	Limit		Unit
			Min.	Typ. Max.	
Collector Cut-off Current	I_{CBO}	$V_{CB}=30\text{ V}, I_E=0$		10	μA
Collector-Base Breakdown Voltage	BV_{CB0}	$I_{CB}=0.1\text{ mA}, I_E=0$	70		V
Emitter-Base Breakdown Voltage	BV_{EBO}	$I_{EB}=0.1\text{ mA}, I_C=0$	5		V
Collector-Emitter Breakdown Voltage	BV_{CER}	$I_{CE}=1\text{ mA}, R_{BE}=100\text{ ohm}$	70		V
DC Current Gain	h_{FE}	$V_{CE}=5\text{ V}, I_C=0.5\text{ A}$	20	200	-
Cut-Off Frequency	f_T	$V_{CE}=5\text{ V}, I_C=150\text{ mA}$		220	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{ V}, I_E=0, f=1\text{MHz}$		70	100 pF
High Frequency Output Power	P_{out}	$f=27\text{MHz}, V_{CC}=12\text{V}, P_{in}=0.2\text{W}$	7.5	8.5	W



2SC2043

OUTLINE Unit mm

