

TRIPPLETT Analog Tester Selection Guide

Model Number Catalog Number		310 Cat. No. 3018	310-C Cat. No. 3022	60 Cat. No. 3145	60-NA Cat. No. 3151	666-R Cat. No. 3066
FUNCTIONS	DC Voltage	5 (3000mV to 1200V) 3% full scale 20KΩ / Volt	5 (3000mV to 600V) 3% full scale 20KΩ / Volt	8 (300mV to 1000V) 1.5% full scale 20KΩ / Volt	14 (150mV to 1000V) 1.5% full scale 20KΩ / 10KΩ / Volt	4 (10mV to 1000V) 3% full scale 1KΩ / Volt
	AC Voltage	5 (3V to 1200V) 4% full scale 5KΩ / Volt	5 (3V to 600V) 4% full scale 15KΩ / Volt	6 (3V to 100V) 3% full scale 5KΩ / Volt	10 (1.5V to 1000V) 3% full scale 10KΩ / 5KΩ / Volt	4 (10V to 1000V) 4% full scale 1KΩ / Volt
	AC Output Voltage Measurement	—	—	—	10 (1.5V to 1000V)	—
	DC Current	4 (0.6mA to 0.6A) 3% full scale 250mV / 330mV	4 (0.6mA to 0.6A) 3% full scale 250 / 330mV	4 (0.1mA to 1A) 1.5% full scale 320mV	4 (0.05mA to 1A) 1.5% full scale	3 (10mA to 1A) 3% full scale 250mV
	Resistance	4 (20KΩ to 20MΩ) 3% full scale	4 (20KΩ to 20MΩ) 3% full scale	5 (1KΩ to 10MΩ) 1.5% full scale	6 (1KΩ to 100MΩ) 1.5% full scale	3 (3KΩ to 3MΩ) 3% full scale
	dB Ranges	—	—	5 (-20dBm to +52dBm)	8 (-26dBm to +52dBm)	—
	Total Ranges / Functions	18	18	28	58	14
SAFETY	Meter Protection	Diode Meter Protection	Diode Meter Protection	Diode Meter Protection Gas Discharge Tube	Diode Meter Protection Gas Discharge Tube	—
	Fuse	1/16A / 250V	1/16A / 250V	1/8A / 250V 1A / 250V 2A / 1000V	1/8A / 250V 1A / 250V 2A / 1000V	—
FEATURES	Polarity Reversing Switch	—	▲	▲	▲	—
	Range Doubling Switch	—	—	—	▲	—
	High Accuracy	—	—	▲	▲	—
	Mirrored Scale	—	—	▲	▲	—
	X-tra Rugged Case	—	—	▲	▲	—
	Hand-Sized	▲	▲	—	—	▲
	Confidence Test	—	—	▲	▲	—
PHYSICAL	Optional AC Clamp-On	Model 10 (60-211)	Model 10-C (60-335)	Model 10 (60-211)	Model 10 (60-211)	—
	Battery	1 - 12V, 1 - N-Cell	1 - 12V, 1 - N-Cell	1 - 9V, 1 - D-Cell	1 - 30V, 1 - D-Cell	2 - AA, 1 - C-Cell
	Dimensions	2.75 x 1.3 x 4.25 in.	2.75 x 1.3 x 4.25 in.	3.25 x 5.25 x 7.25 in.	3.25 x 5.25 x 7.25 in.	2.6 x 3.2 x 5.9 in.
	Weight	2 lbs.	2 lbs.	4 lbs.	4 lbs.	3 lbs.