

# LINEAR SYSTEMS

*Linear Integrated Systems*

## FEATURES

6 LEAD SOT-23 SURFACE MOUNT PACKAGE\*

TIGHT MATCHING<sup>1</sup> 2mV

EXCELLENT THERMAL TRACKING<sup>1</sup> 3μV/°C

## ABSOLUTE MAXIMUM RATINGS<sup>2</sup>

@ 25 °C (unless otherwise stated)

## Maximum Temperatures

Storage Temperature -65 to +150 °C

Operating Junction Temperature -55 to +150 °C

## Maximum Power Dissipation

Continuous Power Dissipation TBD

## Maximum Currents


Collector Current 50mA

## Maximum Voltages

Collector to Collector Voltage 80V

# LS3550 SERIES

**MONOLITHIC DUAL  
PNP TRANSISTORS**



## MATCHING ELECTRICAL CHARACTERISTICS @25 °C (unless otherwise stated)

	CHARACTERISTIC	LS3250A						UNIT	CONDITIONS
		MIN	MAX	MIN	MAX	MIN	MAX		
$ V_{BE1} - V_{BE2} $	Base to Emitter Voltage Differential		2		5		10	mV	$I_C = -10\text{mA}$ , $V_{CE} = -5\text{V}$
$\frac{ V_{BE1} - V_{BE2} }{\Delta T}$	Base to Emitter Voltage Differential Change with Temperature		3		5		15	μV/°C	$I_C = -10\text{mA}$ , $V_{CE} = -5\text{V}$ $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$
$ I_{B1} - I_{B2} $	Base Current Differential		10		10		10	nA	$I_C = -10\mu\text{A}$ , $V_{CE} = -5\text{V}$
$\frac{ I_{B1} - I_{B2} }{\Delta T}$	Base Current Differential Change with Temperature		0.5		0.5		1.0	nA/°C	$I_C = -10\mu\text{A}$ , $V_{CE} = -5\text{V}$ $T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$
$\frac{h_{FE1}}{h_{FE2}}$	Current Gain Differential		10		10		15	%	$I_C = -10\mu\text{A}$ , $V_{CE} = -5\text{V}$


## ELECTRICAL CHARACTERISTICS @25 °C (unless otherwise stated)

SYMBOL	CHARACTERISTIC	LS3250A		LS3250B		LS3250C		UNIT	CONDITIONS
		MIN	MAX	MIN	MAX	MIN	MAX		
$BV_{CBO}$	Collector to Base Breakdown Voltage	-45		-40		-20		V	$I_C = -10\text{mA}$ , $I_E = 0\text{A}$
$BV_{CEO}$	Collector to Emitter Breakdown Voltage	-45		-40		-20			$I_C = -10\mu\text{A}$ , $I_E = 0\text{A}$
$BV_{CCO}$	Collector to Collector Breakdown Voltage	-80		-80		-80			$I_E = -10\mu\text{A}$ , $I_C = 0\text{A}$
$BV_{EBO}$	Emitter to Base Breakdown Voltage <sup>3</sup>	-6.2		-6.2		-6.2			$I_C = -100\text{mA}$ $I_B = -10\text{mA}$
$V_{CE(SAT)}$	Collector to Emitter Saturation Voltage		-0.25		-0.25		-1.2		


**ELECTRICAL CHARACTERISTICS CONT. @25 °C (unless otherwise stated)**

SYMBOL	CHARACTERISTIC	LS3250A		LS3250B		LS3250C		UNIT	CONDITIONS
		MIN	MAX	MIN	MAX	MIN	MAX		
$h_{FE}$	DC Current Gain	150		100		50			$I_C = -1mA, V_{CE} = -5V$
		120		80		40			$I_C = -10mA, V_{CE} = -5V$
		100		80		40			$I_C = -100mA, V_{CE} = -5V$
$I_{CBO}$	Collector Cutoff Current		-0.2		-0.2			nA	$I_E = 0A, V_{CB} = -30V$
							-0.2		$I_E = 0A, V_{CB} = -20V$
$I_{EBO}$	Emitter Cutoff Current		-0.2		-0.2		-0.2		$I_E = 0A, V_{CB} = -3V$
$I_{C1C2}$	Collector to Collector Leakage Current		-1		-1		-1		$V_{CC} = \pm 80V$
$C_{OBO}$	Output Capacitance		2		2		2	pF	$I_E = 0A, V_{CB} = -10V$
$f_T$	Gain Bandwidth Product (Current)		600		600		600	MHz	$I_C = -1mA, V_{CE} = -5V$
NF	Noise Figure (Narrow Band)		3		3		3	dB	$I_C = -100\mu A, V_{CE} = -5V$ $BW = 200Hz$ $R_B = 10\Omega, f = 1kHz$


## SOT-23




## TO-71 Six Lead




## TO-78



## PDIP



## SOIC



Standard package is SOT23 6 lead.  
Other packages listed are optional. Contact factory regarding availability of optional packages.

## NOTES:

- Maximum rating for LS3550A, SOT23-6.
- Absolute maximum ratings are limiting values above which serviceability may be impaired.
- The reverse Base to Emitter voltage must never exceed -6.2 Volts. The reverse Base to Emitter current must never exceed -10 $\mu$ A.

Information furnished by Linear Integrated Systems is believed to be accurate and reliable. However, no responsibility is assumed for its use; nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Linear Integrated Systems.