

查询3EZ12D5供应商

捷多邦, 专业PCB打样工厂, 24小时

加急出 **3EZ3.9D5**
thru
3EZ200D5



Microsemi Corp.
The diode experts.

SCOTTSDALE, AZ

For more information call:
(602) 941-6300

FEATURES

- ZENER VOLTAGE 3.9V to 200V
- HIGH SURGE CURRENT RATING
- 3 WATTS DISSIPATION IN A NORMALLY 1 WATT PACKAGE

MAXIMUM RATINGS

Junction and Storage Temperature: -65°C to +175°C
DC Power Dissipation: 3 Watts
Power Derating: 20 mW/°C above 25°C
Forward Voltage @ 200 mA: 1.2 volts

SILICON
3 WATT
ZENER DIODE

ELECTRICAL CHARACTERISTICS @ 25°C

MICRO TYPE NUMBER (Note 1)	NOMINAL ZENER VOLTAGE (Note 2)		MAXIMUM ZENER IMPEDANCE (Note 3)			MAXIMUM REVERSE LEAKAGE CURRENT		MAXIMUM ZENER CURRENT	MAXIMUM SURGE CURRENT (Note 4)
	V _Z	I _Z	Z _{0.1} @ I _{Z0.1}	Z _{0.5} @ I _{Z0.5}	I _k @ V _k	I _{ZM}	I _{surge}		
	VOLTS	mA	OHMS	OHMS	mA	mA	mA	A	
3EZ3.9D5	3.9	192	4.5	400	1.0	80	630	4.4	
3EZ4.3D5	4.3	174	4.5	400	1.0	30	590	4.1	
3EZ4.7D5	4.7	160	4.0	500	1.0	20	550	3.8	
3EZ5.1D5	5.1	147	3.5	550	1.0	5.0	520	3.5	
3EZ5.6D5	5.6	134	2.5	600	1.0	5.0	480	3.3	
3EZ6.2D5	6.2	121	1.5	700	1.0	5.0	435	3.1	
3EZ6.8D5	6.8	110	2.0	700	1.0	5.0	353	2.9	
3EZ7.5D5	7.5	100	2.0	700	0.5	5.0	360	2.66	
3EZ8.2D5	8.2	91	2.3	700	0.5	5.0	330	2.44	
3EZ9.1D5	9.1	82	2.5	700	0.5	3.0	297	2.2	
3EZ10D5	10	75	3.5	700	0.25	3.0	270	2.0	
3EZ11D5	11	68	4.0	700	0.25	1.0	225	1.82	
3EZ12D5	12	63	4.5	700	0.25	1.0	246	1.66	
3EZ13D5	13	58	4.5	700	0.25	0.5	208	1.54	
3EZ14D5	14	53	5.0	700	0.25	0.5	193	1.43	
3EZ15D5	15	50	5.5	700	0.25	0.5	180	1.33	
3EZ16D5	16	47	5.5	700	0.25	0.5	169	1.25	
3EZ17D5	17	44	6.0	750	0.25	0.5	150	1.18	
3EZ18D5	18	42	6.0	750	0.25	0.5	137	1.11	
3EZ19D5	19	40	7.0	750	0.25	0.5	142	1.05	
3EZ20D5	20	37	7.0	750	0.25	0.5	152	1.0	
3EZ22D5	22	34	8.0	750	0.25	0.5	16.7	0.91	
3EZ24D5	24	31	9.0	750	0.25	0.5	18.2	0.83	
3EZ27D5	27	28	10	750	0.25	0.5	20.6	0.74	
3EZ28D5	28	27	12	750	0.25	0.5	21	0.71	
3EZ30D5	30	25	16	1000	0.25	0.5	22.5	0.67	
3EZ33D5	33	23	20	1000	0.25	0.5	25.1	0.61	
3EZ36D5	36	21	22	1000	0.25	0.5	27.4	0.56	
3EZ39D5	39	19	28	1000	0.25	0.5	29.7	0.51	
3EZ43D5	43	17	33	1500	0.25	0.5	32.7	0.45	
3EZ47D5	47	16	38	1500	0.25	0.5	35.6	0.42	
3EZ51D5	51	15	45	1500	0.25	0.5	38.8	0.39	
3EZ56D5	56	13	50	2000	0.25	0.5	42.6	0.36	
3EZ62D5	62	12	55	2000	0.25	0.5	47.1	0.32	
3EZ68D5	68	11	70	2000	0.25	0.5	51.7	0.29	
3EZ75D5	75	10	85	2000	0.25	0.5	56	0.27	
3EZ82D5	82	9.1	95	3000	0.25	0.5	62.2	0.24	
3EZ91D5	91	8.2	115	3000	0.25	0.5	69.2	0.22	
3EZ100D5	100	7.5	160	3000	0.25	0.5	76	0.20	
3EZ110D5	110	6.8	275	4000	0.25	0.5	83.6	0.18	
3EZ120D5	120	6.3	300	4500	0.25	0.5	91.2	0.16	
3EZ130D5	130	5.8	375	5000	0.25	0.5	98.8	0.15	
3EZ140D5	140	5.3	475	5000	0.25	0.5	106.4	0.14	
3EZ150D5	150	5.0	550	6000	0.25	0.5	114	0.13	
3EZ160D5	160	4.7	625	6500	0.25	0.5	121.6	0.12	
3EZ170D5	170	4.4	700	7000	0.25	0.5	129.2	0.11	
3EZ180D5	180	4.1	775	7500	0.25	0.5	136.8	0.10	
3EZ190D5	190	3.8	850	8000	0.25	0.5	144.4	0.09	
3EZ200D5	200	3.5	925	8500	0.25	0.5	152	0.08	




FIGURE 1
All dimensions in INCH
m.m.

MECHANICAL CHARACTERISTICS

CASE: Molded encapsulation, axial lead package (Case J).

FINISH: Corrosion resistant. Leads are solderable.

THERMAL RESISTANCE: 45°C/Watt junction to lead at 0.375 inches from body.

POLARITY: Banded end is cathode.

WEIGHT: 0.4 grams (Typical).

3EZ3.9D5 thru 3EZ200D5

NOTE 1 Suffix 1 indicates $\pm 1\%$ tolerance. Suffix 2 indicates $\pm 2\%$ tolerance. Suffix 3 indicates $\pm 3\%$ tolerance. Suffix 4 indicates $\pm 4\%$ tolerance. Suffix 5 indicates $\pm 5\%$ tolerance. Suffix 10 indicates $\pm 10\%$, no suffix indicates $\pm 20\%$.

NOTE 2 V_Z measured by applying $I_Z 40_{MS} \pm 10_{MS}$ prior to reading. Mounting contacts are located $3/8''$ to $1/2''$ from inside edge of mounting clips. Ambient temperature, $T_A = 25^\circ C (+8^\circ C / -2^\circ C)$.

NOTE 3 Dynamic Impedance, Z_Z , measured by superimposing $I_{ac rms}$ at 60 hz on I_{DC} where $I_{ac rms} = 10\% I_{DC}$.

NOTE 4 Maximum surge current is a maximum peak non-recurrent reverse surge with a maximum pulse width of 8.3 milliseconds.





FIGURE 2 POWER DERATING CURVE