

IEC appliance outlet J, snap-in/screw-on mounting, front side, solder/quick connect terminal

new



Snap-in mounting



Screw-on mounting

**Description**

- Panel Mount:  
Snap-in or screw-on mounting, from front side
- 1 Function:  
Outlet, Pin temperature 70 °C Protection class I
- Solder terminals or quick connect terminals Substitute for type 0723

**Characteristics**

- Qualified for use in equipment according IEC/EN 60950

**Other versions on request**

- Other panel thickness
- For protection class II

**Weblinks**

[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

**Technical Data**

Ratings IEC	16 A / 250 VAC; Hz 50
Ratings UL/CSA	20 A / 250 VAC; 60 Hz
Dielectric Strength	> 2.5 kVAC between L-N > 3 kVAC between L/N-PE (1 min/50 Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Protection Class	Suitable for appliances with protection class I or II acc. to IEC 61140
Terminal	Solder terminals or quick connect terminals
Panel Thickness s	Screw-on: max 8 mm Mounting screw torque max 0.5 Nm Snap-in: 0.8 mm to 3 mm
Material: Housing	Thermoplastic, black, UL 94V-0

Appliance-Inlet /-Outlet	J acc. to IEC/EN 60320-2-2 UL 498, CSA C22.2 no. 42 (for cold condition) pin-temperature 70 °C, 16 A, Protection class I
--------------------------	---

**Dimensions**

Snap-in mounting



