

TOSHIBA TRANSISTOR SILICON NPN EPITAXIAL PLANAR TYPE

2SC5260


VHF~UHF BAND LOW NOISE AMPLIFIER APPLICATIONS

- Low Noise Figure : NF=1.7dB (f=2GHz)
- High Gain : Gain=8.5dB (f=2GHz)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V _{CBO}	15	V
Collector-Emitter Voltage	V _{CEO}	7	V
Emitter-Base Voltage	V _{EBO}	1.5	V
Collector Current	I _C	15	mA
Base Current	I _B	7	mA
Collector Power Dissipation	P _C	100	mW
Junction Temperature	T _j	125	°C
Storage Temperature Range	T _{stg}	-55~125	°C

MARKING



MICROWAVE CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Transition Frequency	f _T	V _{CE} =5V, I _C =7mA	9	12	—	GHz
Insertion Gain	S _{21e} ² (1)	V _{CE} =5V, I _C =7mA, f=1GHz	11.5	14.5	—	dB
	S _{21e} ² (2)	V _{CE} =5V, I _C =7mA, f=2GHz	5.5	8.5	—	
Noise Figure	NF (1)	V _{CE} =5V, I _C =3mA, f=1GHz	—	1.3	—	dB
	NF (2)	V _{CE} =5V, I _C =3mA, f=2GHz	—	1.7	3	

ELECTRICAL CHARACTERISTICS (Ta = 25°C)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I _{CBO}	V _{CB} =10V, I _E =0	—	—	1	μA
Emitter Cut-off Current	I _{EBO}	V _{EB} =1V, I _C =0	—	—	1	μA
DC Current Gain	h _{FE} (Note 1)	V _{CE} =5V, I _C =7mA	50	—	160	—
Output Capacitance	C _{ob}	V _{CB} =5V, I _E =0, f=1MHz (Note 2)	—	0.4	—	pF
Reverse Transfer Capacitance	C _{re}		—	0.3	0.7	pF

(Note 1) : h_{FE} Classification R : 50~100, O : 80~160

(Note 2) : C_{re} is measured by 3 terminal method with capacitance bridge.

961001EAA2







Unit in mm





Weight : 6mg

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.







S-PARAMETER Z_o = 50Ω、T_a = 25°C
V_{CE} = 5V、I_C = 3mA

FREQUENCY (MHz)	S11		S21		S12		S22	
	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
200	0.845	-20.2	7.567	159.8	0.037	80.6	0.942	-16.8
400	0.76	-39.4	6.813	142.4	0.069	74	0.861	-31.3
600	0.656	-55.7	5.892	127.9	0.094	69.5	0.767	-42.6
800	0.562	-70.4	5.164	115.9	0.116	67	0.684	-51.7
1000	0.479	-82.5	4.471	106.3	0.134	65.6	0.61	-59.6
1200	0.405	-92.7	3.928	97.8	0.151	64.6	0.553	-65.9
1400	0.349	-104	3.47	90.9	0.167	64.3	0.502	-71.4
1600	0.297	-111.7	3.11	85.3	0.184	64.4	0.462	-76.1
1800	0.251	-118.6	2.792	80.2	0.201	64.5	0.428	-79.8
2000	0.214	-125	2.545	75.5	0.218	64.7	0.398	-82.4

V_{CE} = 5V、I_C = 7mA

FREQUENCY (MHz)	S11		S21		S12		S22	
	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
200	0.69	-29.5	11.905	149.2	0.033	78.1	0.884	-21.7
400	0.547	-52.5	9.332	127.8	0.058	73.2	0.74	-35.6
600	0.434	-68	7.272	113.7	0.079	72.1	0.634	-43.8
800	0.353	-81.7	5.932	103.6	0.1	71.9	0.563	-49.8
1000	0.295	-92.3	4.926	96	0.118	72.2	0.509	-55.5
1200	0.246	-102.3	4.229	89	0.138	72.1	0.469	-60.2
1400	0.209	-114.4	3.687	83.6	0.158	71.9	0.436	-64.5
1600	0.169	-123.5	3.280	78.9	0.178	71.7	0.41	-68.3
1800	0.136	-129.5	2.931	74.8	0.198	71.4	0.388	-71.4
2000	0.112	-138.1	2.657	70.7	0.218	71.1	0.371	-73.7