

54/7495A 54LS/74LS95B

4-BIT RIGHT/LEFT SHIFT REGISTER

DESCRIPTION — The '95 is a 4-bit shift register with serial and parallel synchronous operating modes. The serial shift right and parallel load are activated by separate clock inputs which are selected by a mode control input. The data is transferred from the serial or parallel D inputs to the Q outputs synchronous with the HIGH-to-LOW transition of the appropriate clock input.

- SYNCHRONOUS, EXPANDABLE SHIFT RIGHT
- SYNCHRONOUS SHIFT LEFT CAPABILITY
- SYNCHRONOUS PARALLEL LOAD
- SEPARATE SHIFT AND LOAD CLOCK INPUTS


ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		Vcc = +5.0 V ±5%, TA = 0°C to +70°C	Vcc = +5.0 V ±10%, TA = -55°C to +125°C	
Plastic DIP (P)	A	7495APC, 74LS95BPC		9A
Ceramic DIP (D)	A	7495ADC, 74LS95BDC	5495ADM, 54LS95BDM	6A
Flatpak (F)	A	7495AFC, 74LS95BFC	5495AFM, 54LS95BFM	3I


INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PIN NAMES	DESCRIPTION	54/74 (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
CP ₁	Serial Clock Input (Active Falling Edge)	1.0/1.0	0.5/0.25
CP ₂	Parallel Clock Input (Active Falling Edge)	1.0/1.0	0.5/0.25
D _s	Serial Data Input	1.0/1.0	0.5/0.25
P ₀ —P ₃	Parallel Data Inputs	1.0/1.0	0.5/0.25
PE	Parallel Enable Input (Active HIGH)	2.0/2.0	1.0/0.5
Q ₀ —Q ₃	Parallel Outputs	20/10	10/5.0 (2.5)

CONNECTION DIAGRAM PINOUT A



LOGIC SYMBOL



Vcc = Pin 14
GND = Pin 7

FUNCTIONAL DESCRIPTION — The '95 is a 4-bit shift register with serial and parallel synchronous operating modes. It has a Serial (Ds) and four Parallel (P_0 — P_3) Data inputs and four Parallel Data outputs (Q_0 — Q_3). The serial or parallel mode of operation is controlled by a Parallel Enable input (PE) and two Clock inputs, \bar{CP}_1 and \bar{CP}_2 . The serial (right-shift) or parallel data transfers occur synchronous with the HIGH-to-LOW transition of the selected clock input.

When PE is HIGH, \bar{CP}_2 is enabled. A HIGH-to-LOW transition on enabled \bar{CP}_2 transfers parallel data from the P_0 — P_3 inputs to the Q_0 — Q_3 outputs. When PE is LOW, \bar{CP}_1 is enabled. A HIGH-to-LOW transition on enabled \bar{CP}_1 transfers the data from Serial input (Ds) to Q_0 and shifts the data in Q_0 to Q_1 , Q_1 to Q_2 , and Q_2 to Q_3 respectively (right-shift). A left-shift is accomplished by externally connecting Q_3 to P_2 , Q_2 to P_1 , and Q_1 to P_0 , and operating the '95 in the parallel mode (PE = HIGH). For normal operation, PE should only change states when both Clock inputs are LOW. However, changing PE from LOW to HIGH while \bar{CP}_2 is HIGH, or changing PE from HIGH to LOW while \bar{CP}_1 is HIGH and \bar{CP}_2 is LOW will not cause any changes on the register outputs.


MODE SELECT TABLE

OPERATING MODE	INPUTS					OUTPUTS			
	PE	\bar{CP}_1	\bar{CP}_2	Ds	P_n	Q_0	Q_1	Q_2	Q_3
Shift	L	L	X	I	X	L	q_0	q_1	q_2
	L	L	X	h	X	H	q_0	q_1	q_2
Parallel Load	H	X	L	X	p_n	p_0	p_1	p_2	p_3
Mode Change	L	L	L	X	X	No Change			
	J	L	L	X	X	No Change			
	L	H	L	X	X	No Change			
	J	H	L	X	X	Undetermined			
	L	L	H	X	X	Undetermined			
	J	L	H	X	X	No Change			
	L	H	H	X	X	Undetermined			
	J	H	H	X	X	No Change			

I = LOW Voltage Level one set-up time prior to the HIGH-to-LOW clock transition.
h = HIGH Voltage Level one set-up time prior to the HIGH-to-LOW clock transition.
 p_n = Lower case letters indicate the state of the referenced input or output one set-up time prior to the HIGH-to-LOW clock transition.

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial

LOGIC DIAGRAM



95

DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)							
SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS
		Min	Max	Min	Max		
I _{cc}	Power Supply Current	63		21		mA	V _{CC} = Max

AC CHARACTERISTICS: V_{CC} = +5.0 V, T_A = +25°C (See Section 3 for waveforms and load configurations)

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITONS
		C _L = 15 pF	R _L = 400 Ω	C _L = 15 pF	R _L = 400 Ω		
		Min	Max	Min	Max		
f _{max}	Maximum Shift Frequency	25		30		MHz	Figs. 3-1, 3-9
t _{PPLH}	Propagation Delay CP ₁ or CP ₂ to Q _n	27		27		ns	Figs. 3-1, 3-9
t _{PHL}		32		27			

AC OPERATING REQUIREMENTS: V_{CC} = +5.0 V, T_A = +25°C

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS
		Min	Max	Min	Max		
t _s (H) t _s (L)	Setup Time HIGH or LOW D _s or P _n to CP _n	15 15		20 20		ns	Fig. 3-7
t _h (H) t _h (L)	Hold Time HIGH or LOW D _s or P _n to CP _n	0 0		10 10		ns	Fig. 3-7
t _w (H)	CP _n Pulse Width HIGH	20		20		ns	Fig. 3-9
t _{en} (L)	Enable Time LOW PE to CP ₁	15		25		ns	Fig. a
t _{inh} (H)	Inhibit Time HIGH PE to CP ₁	5.0		20		ns	Fig. a
t _{en} (H)	Enable Time HIGH PE to CP ₂	15		25		ns	Fig. a
t _{inh} (L)	Inhibit Time LOW PE to CP ₂	5.0		20		ns	Fig. a




Fig. a