



Integrated Device Technology, Inc.

# FAST CMOS 16-BIT BIDIRECTIONAL 3.3V TO 5V TRANSLATOR

IDT54/74FCT164245T

## FEATURES:


- 0.5 MICRON CMOS Technology
- Bidirectional interface between 3.3V and 5V busses
- Control inputs can be driven from either 3.3V or 5V circuits
- ESD >2000V per MIL-STD-883, Method 3015; >200V using machine model (C = 200pF, R = 0)
- 25 MIL Center SSOP and Cerpack Packages
- Extended commercial range of -40°C to +85°C
- VCC1 = 5V ±10%, VCC2 = 2.7V to 3.6V
- High drive outputs (-32mA IOH, 64mA IOL) on 5V port
- Power-off disable on both ports permits "live insertion"
- Typical VOLP (Output Ground Bounce) < 0.9V at VCC1 = 5V, VCC2 = 3.3V, TA = 25°C

## DESCRIPTION:


The FCT164245T 16-bit 3.3V-to-5V translator is built using advanced dual metal CMOS technology. This high-speed, low-power transceiver is designed to interface between a 3.3V bus and a 5V bus in a mixed 3.3V/5V supply environment. This enables system designers to interface TTL compatible 3.3V components with 5V components. The direction and output enable controls operate these devices as either two independent 8-bit transceivers or one 16-bit transceiver. The A port interfaces with the 3.3V bus; the B port interfaces with the 5V bus. The direction control (xDIR) pin controls the direction of data flow. The output enable (xOE) overrides the direction control and disables both ports. These control signals can be driven from either 3.3V or 5V devices.

The FCT164245T is ideally suited for driving high capacitance loads and low impedance backplanes. The output buffers are designed with Power-Off Disable capability to allow "hot insertion" of boards when used as backplane drivers. They also allow interface between a mixed supply system and external 5V peripherals.

## FUNCTIONAL BLOCK DIAGRAM




2555 drw 01



2555 drw 02

PIN CONFIGURATIONS



POWER SUPPLY SEQUENCING

In the IDT54/74FCT164245T the condition of Vcc1 ≥ (Vcc2 –0.5V) must be maintained at all times. For the range of Vcc1 = (Vcc2 –0.5V) to Vcc1 = (Vcc2 +0.9V), both the A and B ports will remain in a high impedance state.

## PIN DESCRIPTION

| Pin Names | Description                                  |
|-----------|----------------------------------------------|
| xOE       | Output Enable Input (Active LOW)             |
| xDIR      | Direction Control Input                      |
| xAx       | Side A Inputs or 3-State Outputs (3.3V Port) |
| xBx       | Side B Inputs or 3-State Outputs (5V Port)   |

2555 tbl 01

## FUNCTION TABLE<sup>(1)</sup>

| Inputs |      | Outputs             |
|--------|------|---------------------|
| xOE    | xDIR |                     |
| L      | L    | Bus B Data to Bus A |
| L      | H    | Bus A Data to Bus B |
| H      | X    | High Z State        |

2555 tbl 03

### NOTE:

1. H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Don't Care  
Z = High Impedance

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

| Symbol               | Rating                               | Commercial           | Military             | Unit |
|----------------------|--------------------------------------|----------------------|----------------------|------|
| VTERM <sup>(2)</sup> | Terminal Voltage with Respect to GND | −0.5 to +7.0         | −0.5 to +7.0         | V    |
| VTERM <sup>(3)</sup> | Terminal Voltage with Respect to GND | −0.5 to VCC1<br>+0.5 | −0.5 to VCC1<br>+0.5 | V    |
| TA                   | Operating Temperature                | −40 to +85           | −55 to +125          | °C   |
| TBIAS                | Temperature Under Bias               | −55 to +125          | −65 to +135          | °C   |
| TSTG                 | Storage Temperature                  | −55 to +125          | −65 to +150          | °C   |
| PT                   | Power Dissipation                    | 1.0                  | 1.0                  | W    |
| IOUT                 | DC Output Current                    | −60 to +120          | −60 to +120          | mA   |

2555 lmk 02

### NOTES:

1. Stresses greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
2. All device terminals except VCC2.
3. Power supply terminals VCC2.

## CAPACITANCE (TA = +25°C, f = 1.0MHz)

| Symbol | Parameter <sup>(1)</sup> | Conditions | Typ. | Max. | Unit |
|--------|--------------------------|------------|------|------|------|
| CIN    | Input Capacitance        | VIN = 0V   | 3.5  | 6.0  | pF   |
| CI/O   | I/O Capacitance          | VOU = 0V   | 3.5  | 8.0  | pF   |

2555 lmk 04

### NOTE:

1. This parameter is measured at characterization but not tested.

## DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE (A PORT - 3.3V)

Following Conditions Apply Unless Otherwise Specified:

VCC1 = 5V ± 10%, VCC2 = 2.7V to 3.6V; Commercial: TA = -40°C to +85°C, Military: TA = -55°C to +125°C,

| Symbol                  | Parameter                                | Test Conditions <sup>(1)</sup>                                      |                                                              | Min.     | Typ. <sup>(2)</sup> | Max. | Unit |
|-------------------------|------------------------------------------|---------------------------------------------------------------------|--------------------------------------------------------------|----------|---------------------|------|------|
| V <sub>IH</sub>         | Input HIGH Level<br>(Input and I/O pins) | Guaranteed Logic HIGH Level                                         |                                                              | 2.0      | —                   | 5.5  | V    |
| V <sub>IL</sub>         | Input LOW Level<br>(Input and I/O pins)  | Guaranteed Logic LOW Level                                          |                                                              | -0.5     | —                   | 0.8  | V    |
| I <sub>IH</sub>         | Input HIGH Current (Input pins)          | VCC1 = Max.                                                         | V <sub>I</sub> = 5.5V                                        | —        | —                   | ±5   | μA   |
|                         | Input HIGH Current (I/O pins)            | VCC2 = Max.                                                         | V <sub>I</sub> = VCC2                                        | —        | —                   | ±15  |      |
| I <sub>IL</sub>         | Input LOW Current (Input pins)           |                                                                     | V <sub>I</sub> = GND                                         | —        | —                   | ±5   |      |
|                         | Input LOW Current (I/O pins)             |                                                                     | V <sub>I</sub> = GND                                         | —        | —                   | ±15  |      |
| V <sub>IK</sub>         | Clamp Diode Voltage                      | VCC2 = Min., I <sub>IN</sub> = -18mA                                |                                                              | —        | -0.7                | -1.2 | V    |
| V <sub>OH</sub>         | Output HIGH Voltage                      | VCC1 = VCC2 = Min.                                                  | I <sub>OH</sub> = -0.1mA                                     | VCC2-0.2 | —                   | —    | V    |
|                         |                                          | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub>                | I <sub>OH</sub> = -3mA MIL.                                  | 2.4      | 3.0                 | —    |      |
|                         |                                          | VCC2 = 3.0V<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OH</sub> = -6mA MIL.<br>I <sub>OH</sub> = -8mA COM'L. | 2.4      | 3.0                 | —    |      |
| V <sub>OL</sub>         | Output LOW Voltage                       | VCC1 = Min.                                                         | I <sub>OL</sub> = 0.1mA                                      | —        | —                   | 0.2  | V    |
|                         |                                          | VCC2 = Min.                                                         | I <sub>OL</sub> = 16mA                                       | —        | 0.2                 | 0.4  |      |
|                         |                                          | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub>                | I <sub>OL</sub> = 24mA                                       | —        | 0.3                 | 0.55 |      |
|                         |                                          | VCC = 3.0V<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub>  | I <sub>OL</sub> = 24mA                                       | —        | 0.3                 | 0.50 |      |
| I <sub>OFF</sub>        | Input/Output Power Off Leakage           | VCC1 = 0V, VCC2 = 0V, V <sub>IN</sub> or V <sub>O</sub> ≤ 4.5V      |                                                              | —        | —                   | ±100 | μA   |
| I <sub>OS</sub>         | Short Circuit Current <sup>(4)</sup>     | VCC1 = Max., VCC2 = Max., V <sub>O</sub> = GND <sup>(3)</sup>       |                                                              | -70      | -105                | -150 | mA   |
| I <sub>O</sub>          | Output Drive Current                     | VCC1 = Max., VCC2 = Max., V <sub>O</sub> = 1.5V <sup>(3)</sup>      |                                                              | -40      | -60                 | -90  | mA   |
| V <sub>H</sub>          | Input Hysteresis                         | —                                                                   |                                                              | —        | 150                 | —    | mV   |
| ICC2L<br>ICC2H<br>ICC2Z | Quiescent Power Supply Current           | VCC1 = Max., V <sub>IN</sub> = GND or VCC2<br>VCC2 = Max.           |                                                              | —        | 0.35                | 2.0  | mA   |

### NOTES:

- For conditions shown as Max. or Min., use appropriate value specified under Electrical Characteristics for the applicable device type.
- Typical values are at VCC1 = 5.0V, VCC2 = 3.3V, +25°C ambient.
- Not more than one output should be tested at one time. Duration of the test should not exceed one second.
- This parameter is guaranteed but not tested.

## DC ELECTRICAL CHARACTERISTICS OVER OPERATING RANGE (B PORT - 5V)

Following Conditions Apply Unless Otherwise Specified:

VCC1 = 5V ± 10%, VCC2 = 2.7V to 3.6V; Commercial: TA = -40°C to +85°C, Military: TA = -55°C to +125°C,

| Symbol                  | Parameter                                | Test Conditions <sup>(1)</sup>                                                      |                                                                               | Min. | Typ. <sup>(2)</sup> | Max. | Unit |
|-------------------------|------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|------|---------------------|------|------|
| V <sub>IH</sub>         | Input HIGH Level<br>(Input and I/O pins) | Guaranteed Logic HIGH Level                                                         |                                                                               | 2.0  | —                   | 5.5  | V    |
| V <sub>IL</sub>         | Input LOW Level<br>(Input and I/O pins)  | Guaranteed Logic LOW Level                                                          |                                                                               | -0.5 | —                   | 0.8  | V    |
| I <sub>IH</sub>         | Input HIGH Current (Input pins)          | VCC1 = Max.                                                                         | V <sub>I</sub> = VCC1                                                         | —    | —                   | ±5   | μA   |
|                         | Input HIGH Current (I/O pins)            | VCC2 = Max.                                                                         |                                                                               | —    | —                   | ±15  |      |
| I <sub>IL</sub>         | Input LOW Current (Input pins)           |                                                                                     | V <sub>I</sub> = GND                                                          | —    | —                   | ±5   |      |
|                         | Input LOW Current (I/O pins)             |                                                                                     |                                                                               | —    | —                   | ±15  |      |
| V <sub>IK</sub>         | Clamp Diode Voltage                      | VCC1 = Min., I <sub>IN</sub> = -18mA                                                |                                                                               | —    | -0.7                | -1.2 | V    |
| V <sub>OH</sub>         | Output HIGH Voltage                      | VCC1 = Min.                                                                         | I <sub>OH</sub> = -3mA                                                        | 2.5  | 3.5                 | —    | V    |
|                         |                                          | VCC2 = Min.                                                                         | I <sub>OH</sub> = -12mA MIL.<br>I <sub>OH</sub> = -15mA COM'L.                | 2.4  | 3.5                 | —    |      |
|                         |                                          | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                | I <sub>OH</sub> = -24mA MIL.<br>I <sub>OH</sub> = -32mA COM'L. <sup>(5)</sup> | 2.0  | 3.0                 | —    |      |
| V <sub>OL</sub>         | Output LOW Voltage                       | VCC1 = Min.,<br>VCC2 = Min.<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | I <sub>OL</sub> = 48mA MIL.<br>I <sub>OL</sub> = 64mA COM'L.                  | —    | 0.2                 | 0.55 | V    |
| I <sub>OFF</sub>        | Input/Output Power Off Leakage           | VCC1 = 0V, VCC2 = 0V, V <sub>IN</sub> or V <sub>O</sub> ≤ 4.5V                      |                                                                               | —    | —                   | ±100 | μA   |
| I <sub>OS</sub>         | Short Circuit Current <sup>(4)</sup>     | VCC1 = Max., VCC2 = Max., V <sub>O</sub> = GND <sup>(3)</sup>                       |                                                                               | -80  | -140                | -225 | mA   |
| I <sub>O</sub>          | Output Drive Current                     | VCC1 = Max., VCC2 = Max., V <sub>O</sub> = 2.5V <sup>(3)</sup>                      |                                                                               | -50  | -75                 | -180 | mA   |
| V <sub>H</sub>          | Input Hysteresis                         | —                                                                                   |                                                                               | —    | 150                 | —    | mV   |
| ICC1L<br>ICC1H<br>ICC1Z | Quiescent Power Supply Current           | VCC1 = Max., V <sub>IN</sub> = GND or VCC2<br>VCC2 = Max.                           |                                                                               | —    | 0.08                | 1.5  | mA   |

### NOTES:

- For conditions shown as Max. or Min., use appropriate value specified under Electrical Characteristics for the applicable device type.
- Typical values are at VCC1 = 5.0V, VCC2 = 3.3V, +25°C ambient.
- Not more than one output should be tested at one time. Duration of the test should not exceed one second.
- This parameter is guaranteed but not tested.
- Duration of the condition can not exceed one second.

2555 tbl 06

## POWER SUPPLY CHARACTERISTICS

| Symbol          | Parameter                                         | Test Conditions <sup>(1)</sup>                                                                                                                                      |                                             | Min. | Typ. <sup>(2)</sup> | Max.               | Unit             |
|-----------------|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|------|---------------------|--------------------|------------------|
| $\Delta I_{CC}$ | Quiescent Power Supply Current<br>TTL Inputs HIGH | $V_{CC1} = \text{Max.}, V_{CC2} = \text{Max.},$<br>$V_{IN} = V_{CC2} - 0.6V^{(3)}$                                                                                  |                                             | —    | 12                  | 30                 | $\mu A$          |
| $I_{CCD}$       | Dynamic Power Supply<br>Current <sup>(4)</sup>    | $V_{CC1} = \text{Max.}, V_{CC2} = \text{Max.}$<br>Outputs Open<br>$\overline{xOE} = xDIR = GND$<br>One Input Toggling<br>50% Duty Cycle                             | $V_{IN} = V_{CC2}$<br>$V_{IN} = GND$        | —    | 75                  | 120                | $\mu A /$<br>MHz |
| $I_C$           | Total Power Supply Current <sup>(6)</sup>         | $V_{CC1} = \text{Max.}, V_{CC2} = \text{Max.}$<br>Outputs Open<br>$f_i = 10\text{MHz}$<br>50% Duty Cycle<br>$\overline{xOE} = xDIR = GND$<br>One Bit Toggling       | $V_{IN} = V_{CC2} - 0.6V$<br>$V_{IN} = GND$ | —    | 1.2                 | 4.7                | mA               |
|                 |                                                   | $V_{CC1} = \text{Max.}, V_{CC2} = \text{Max.}$<br>Outputs Open<br>$f_i = 2.5\text{MHz}$<br>50% Duty Cycle<br>$\overline{xOE} = xDIR = GND$<br>Sixteen Bits Toggling | $V_{IN} = V_{CC2} - 0.6V$<br>$V_{IN} = GND$ | —    | 3.5                 | 8.5 <sup>(5)</sup> |                  |

### NOTES:

2555 tbl 07

- For conditions shown as Max. or Min., use appropriate value specified under Electrical Characteristics for the applicable device type.
- Typical values are at  $V_{CC1} = 5.0V$ ,  $V_{CC2} = 3.3V$ ,  $+25^\circ C$  ambient.
- Per TTL driven input; all other inputs at  $V_{CC}$  or GND.
- This parameter is not directly testable, but is derived for use in Total Power Supply Calculations.
- Values for these conditions are examples of the  $I_{CC}$  formula. These limits are guaranteed but not tested.
- $I_C = I_{QUIESCENT} + I_{INPUTS} + I_{DYNAMIC}$   
 $I_C = I_{CC1} + I_{CC2} + \Delta I_{CC} D_H N_T + I_{CCD} (f_{CP} N_{CP} / 2 + f_i N_i)$   
 $I_{CC1}$  = Quiescent Current ( $I_{CC1L}$ ,  $I_{CC1H}$  and  $I_{CC1Z}$ )  
 $I_{CC2}$  = Quiescent Current ( $I_{CC2L}$ ,  $I_{CC2H}$  and  $I_{CC2Z}$ )  
 $\Delta I_{CC}$  = Power Supply Current for a TTL High Input  
 $D_H$  = Duty Cycle for TTL Inputs High  
 $N_T$  = Number of TTL Inputs at  $D_H$   
 $I_{CCD}$  = Dynamic Current Caused by an Input Transition Pair (HLH or LHL)  
 $f_{CP}$  = Clock Frequency for Register Devices (Zero for Non-Register Devices)  
 $N_{CP}$  = Number of Clock Inputs at  $f_{CP}$   
 $f_i$  = Input Frequency  
 $N_i$  = Number of Inputs at  $f_i$

## SWITCHING CHARACTERISTICS OVER OPERATING RANGE


| Symbol       | Parameter                                       | Condition <sup>(1)</sup> | Com'l.              |      | Mil.                |      | Unit |
|--------------|-------------------------------------------------|--------------------------|---------------------|------|---------------------|------|------|
|              |                                                 |                          | Min. <sup>(2)</sup> | Max. | Min. <sup>(2)</sup> | Max. |      |
| tPLH<br>tPHL | Propagation Delay<br>A to B                     | CL = 50pF<br>RL = 500Ω   | 1.5                 | 5.0  | —                   | —    | ns   |
| tPLH<br>tPHL | Propagation Delay<br>B to A                     |                          | 1.5                 | 5.0  | —                   | —    | ns   |
| tPZH<br>tPZL | Output Enable Time<br>$\overline{xOE}$ to B     |                          | 1.5                 | 6.5  | —                   | —    | ns   |
| tPHZ<br>tPLZ | Output Disable Time<br>$\overline{xOE}$ to B    |                          | 1.5                 | 6.0  | —                   | —    | ns   |
| tPZH<br>tPZL | Output Enable Time<br>$\overline{xOE}$ to A     |                          | 1.5                 | 6.5  | —                   | —    | ns   |
| tPHZ<br>tPLZ | Output Disable Time<br>$\overline{xOE}$ to A    |                          | 1.5                 | 6.0  | —                   | —    | ns   |
| tPZH<br>tPZL | Output Enable Time<br>xDIR to B <sup>(3)</sup>  |                          | 1.5                 | 6.5  | —                   | —    | ns   |
| tPHZ<br>tPLZ | Output Disable Time<br>xDIR to B <sup>(3)</sup> |                          | 1.5                 | 6.0  | —                   | —    | ns   |
| tPZH<br>tPZL | Output Enable Time<br>xDIR to A <sup>(3)</sup>  |                          | 1.5                 | 6.5  | —                   | —    | ns   |
| tPHZ<br>tPLZ | Output Disable Time<br>xDIR to A <sup>(3)</sup> |                          | 1.5                 | 6.0  | —                   | —    | ns   |

### NOTES:

1. See test circuit and waveforms.
2. Minimum limits are guaranteed but not tested on Propagation Delays.
3. This parameter is guaranteed but not tested.

2555 tbl 08

TEST CIRCUITS AND WAVEFORMS  
TEST CIRCUITS FOR ALL OUTPUTS




SWITCH POSITION


| Test                                    | Switch |
|-----------------------------------------|--------|
| Open Drain<br>Disable Low<br>Enable Low | 6V     |
| Disable High<br>Enable High             | GND    |
| All Other tests                         | Open   |

DEFINITIONS:  
C<sub>L</sub> = Load capacitance: includes jig and probe capacitance.  
R<sub>T</sub> = Termination resistance: should be equal to Z<sub>OUT</sub> of the Pulse Generator.


SET-UP, HOLD AND RELEASE TIMES




PULSE WIDTH



PROPAGATION DELAY



ENABLE AND DISABLE TIMES



NOTES:  
1. Diagram shown for input Control Enable-LOW and input Control Disable-HIGH  
2. Pulse Generator for All Pulses: Rate ≤ 1.0MHz; t<sub>F</sub> ≤ 2.5ns; t<sub>R</sub> ≤ 2.5ns

ORDERING INFORMATION

| IDT         | XX | FCT         | XXXX | X       | X             |                                                                                                       |                                   |
|-------------|----|-------------|------|---------|---------------|-------------------------------------------------------------------------------------------------------|-----------------------------------|
| Temp. Range |    | Device Type |      | Package | Process       |                                                                                                       |                                   |
|             |    |             |      |         | Blank<br>B    | Commercial<br>MIL-STD-883, Class B                                                                    |                                   |
|             |    |             |      |         | PV<br>PA<br>E | Shrink Small Outline Package (SO48-1)<br>Thin Shrink Small Outline Package(SO48-2)<br>Cerpack (E48-1) |                                   |
|             |    |             |      | 164245T |               | Non-Inverting 16-Bit Bidirectional Translator                                                         |                                   |
|             |    |             |      |         |               | 54<br>74                                                                                              | −55°C to +125°C<br>−40°C to +85°C |