

Part Number: SL15 60002

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL15 60002-A



### Electrical Specifications:

Resistance @ 25°C	60.0 $\Omega$ $\pm$ 20%
Max Steady State Current Up to 65°C	2.0 A
Max Recommended Energy Rating (Joules)	50.0 J
Resistance @ 100% of Max Current	0.930 $\Omega$
Resistance @ 50% of Max Current	1.940 $\Omega$
Body Temperature @ 100% Current Rating	174 °C
Dissipation Constant	15mW/°C
Thermal Time Constant	45 seconds
Material Type	"M"
Max Capacitance @ 120VAC/240VAC	3200 $\mu$ F/800 $\mu$ F

### Mechanical Specifications:

D	15.0 $\pm$ 0.5 mm
T	5.0 $\pm$ 0.2 mm
Lead Diameter	0.8 $\pm$ 0.1 mm
S	7.8 $\pm$ 0.30 mm
L	38.0 $\pm$ 1.50 mm
Straight Leads	Standard
B	7.50 $\pm$ 0.70 mm
C	3.60 $\pm$ 0.40 mm
Coating Run Down on the Straight Leads	5.00 $\pm$ 0.5 mm