

International
IR Rectifier
 SCHOTTKY RECTIFIER
 HIGH EFFICIENCY SERIES

PD-20504C

60LQ045

60A, 30V


Major Ratings and Characteristics

Characteristics	60LQ045	Units
$I_{F(AV)}$	60	A
V_{RRM}	45	V
I_{FSM} @ $t_p = 8.3ms$ half-sine	400	A
V_F @ 60Apk, $T_J = 125^\circ C$	0.6	V
T_J, T_{stg} Operating and storage	-55 to 150	$^\circ C$

Description/Features

The 60LQ045 Schottky rectifier has been expressly designed to meet the rigorous requirements of hi-rel environments. It is packaged in the hermetic surface mount SMD-1 ceramic package. The device's forward voltage drop and reverse leakage current are optimized for the lowest power loss and the highest circuit efficiency for typical high frequency switching power supplies and resonant power convertors. Full MIL-PRF-19500 quality conformance testing is available on control drawings to TX, TXV and S quality levels.

- Hermetically Sealed
- Low Forward Voltage Drop
- High Frequency Operation
- Guard Ring for Enhanced Ruggedness and Long term Reliability
- Surface Mount
- Lightweight



www.irf.com

1



Voltage Ratings

Part number	60LQ045
V _R Max. DC Reverse Voltage (V)	45
V _{RWM} Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	Limits	Units	Conditions
I _{F(AV)} Max. Average Forward Current See Fig. 5	60	A	50% duty cycle @ T _C = 105°C, square waveform
I _{FSM} Max. Peak One Cycle Non - Repetitive Surge Current	400	A	@ t _p = 8.3 ms half-sine

Electrical Specifications

Parameters	Limits	Units	Conditions	
V _{FM} Max. Forward Voltage Drop See Fig. 1 ①	0.68	V	@ 60A	T _J = 25°C ②
	0.82	V	@ 120A	
	0.6	V	@ 60A	T _J = 125°C ②
	0.74	V	@ 120A	
I _{RM} Max. Reverse Leakage Current See Fig. 2 ①	0.8	mA	T _J = 25°C	V _R = rated V _R ②
	45	mA	T _J = 125°C	
C _T Max. Junction Capacitance	2900	pF	V _R = 5V _{DC} , (1MHz, 25°C) ②	
L _S Typical Series Inductance	5.9	nH	Measured from center of cathode pad to center of anode pad	

Thermal-Mechanical Specifications

Parameters	Limits	Units	Conditions	
T _J Max. Junction Temperature Range	-55 to 150	°C		
T _{stg} Max. Storage Temperature Range	-55 to 150	°C		
R _{thJC} Max. Thermal Resistance, Junction to Case	1.0	°C/W	DC operation	See Fig. 4
wt Weight (Typical)	2.6	g		
Die Size	200X200	mils		
Case Style	SMD-1			

① Pulse Width < 300μs, Duty Cycle < 2%

② Pins 2 and 3 externally tied together




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current