

International IR Rectifier

PD-2.269 rev. A 12/97

62CNQ030

SCHOTTKY RECTIFIER

60 Amp

Major Ratings and Characteristics


Characteristics	62CNQ030	Units
$I_{F(AV)}$ Rectangular waveform	60	A
V_{RRM}	30	V
I_{FSM} @ $t_p=5\mu s$ sine	4600	A
V_F @ 30Apk, $T_J=125^\circ C$ (per leg)	0.35	V
T_J	-55 to 150	°C

Description/Features

The 62CNQ030 center tap Schottky rectifier module has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to 150 °C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 150 °C T_J operation
- Center tap module
- Very low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Low profile, small footprint, high current package

CASE STYLE AND DIMENSIONS



62CNQ030

PD-2.269 rev. A 12/97

International
 Rectifier

Voltage Ratings

Part number	62CNQ030	
V_R Max. DC Reverse Voltage (V)		
V_{RWM} Max. Working Peak Reverse Voltage (V)		30

Absolute Maximum Ratings

Parameters	62CNQ	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	60	A	50% duty cycle @ $T_C = 135^\circ\text{C}$, rectangular waveform
I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7	4600	A	5μs Sine or 3μs Rect. pulse
	780		10ms Sine or 6ms Rect. pulse Following any rated load condition and with rated V_{RRM} applied
E_{AS} Non-Repetitive Avalanche Energy (Per Leg)	27	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 6$ Amps, $L = 1.5$ mH
I_{AR} Repetitive Avalanche Current (Per Leg)	6	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	62CNQ	Units	Conditions
V_{FM} Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)	0.46	V	$T_J = 25^\circ\text{C}$
	0.53	V	$T_J = 25^\circ\text{C}$
	0.35	V	$T_J = 30^\circ\text{C}$
	0.44	V	$T_J = 125^\circ\text{C}$
I_{RM} Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1)	5	mA	$T_J = 25^\circ\text{C}$
	280	mA	$T_J = 125^\circ\text{C}$
C_T Max. Junction Capacitance (Per Leg)	3700	pF	$V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) 25°C
L_S Typical Series Inductance (Per Leg)	6.0	nH	Measured lead to lead 5mm from package body
dv/dt Max. Voltage Rate of Change (Rated V_R)	10,000	V/ μs	

(1) Pulse Width < 300μs, Duty Cycle <2%

Thermal-Mechanical Specifications

Parameters	62CNQ	Units	Conditions
T_J Max. Junction Temperature Range	-55 to 150	°C	
T_{stg} Max. Storage Temperature Range	-55 to 150	°C	
R_{thJC} Max. Thermal Resistance Junction to Case (Per Leg)	0.85	°C/W	DC operation * See Fig. 4
R_{thJC} Max. Thermal Resistance Junction to Case (Per Package)	0.42	°C/W	DC operation
R_{thCS} Typical Thermal Resistance, Case to Heatsink	0.30	°C/W	Mounting surface, smooth and greased
wt Approximate Weight	7.8(0.28)	g(oz.)	
T Mounting Torque	Min.	Kg-cm (lbf-in)	
	Max.	58(50)	
Case Style	D-61-6		




Fig. 1-Max. Forward Voltage Drop Characteristics
 (PerLeg)




Fig. 2-Typical Values Of Reverse Current
 Vs. Reverse Voltage (PerLeg)




Fig. 3-Typical Junction Capacitance
 Vs. Reverse Voltage (PerLeg)




Fig. 4-Max. Thermal Impedance Z_{thJC} Characteristics (PerLeg)

62CNQ030

PD-2.269 rev. A 12/97

International
IR Rectifier




Fig.5-Max. Allowable Case Temperature Vs. Average Forward Current (PerLeg)




Fig.6-Forward Power Loss Characteristics (PerLeg)




Fig.7-Max. Non-Repetitive Surge Current (PerLeg)




Fig.8-Unclamped Inductive Test Circuit