

Intelligent Power Module (R-Series)

Maximum Ratings and Characteristics

Absolute Maximum Ratings (T_c=25°C)

Items	Symbols	Ratings		Units
		Min.	Max.	
DC Bus Voltage	V _{DC}	0	450	V
DC Bus Voltage (surge)	V _{DC(Surge)}	0	500	
DC Bus Voltage (short operating)	V _{SC}	200	400	
Collector-Emitter Voltage	V _{CES}	0	600	
Inverter	Continuous	I _C	150	A
Collector		I _{CP}	300	
Current	Duty=58.8%	-I _C	150	
Collector Power Dissipation	One Transistor	P _C	595	W
Voltage of Power Supply for Driver	V _{CC} *1	0	20	V
Input Signal Voltage	V _{IN} *2	0	V _Z	V
Input Signal Current	I _{IN}		1	mA
Alarm Signal Voltage	V _{ALM} *3	0	V _{CC}	V
Alarm Signal Current	I _{ALM} *4		15	mA
Junction Temperature	T _J		150	°C
Operating Temperature	T _{OP}	-20	100	
Storage Temperature	T _{stg}	-40	125	
Isolation Voltage	A.C. 1min.	V _{iso}	2500	V
Screw Torque	Mounting *1		3.5	Nm
	Terminals *1		3.5	

Note: *1: Recommendable Value; 2.5 - 3.0 Nm (M5)

Outline Drawing




Fig. 1

Electrical Characteristics of Power Circuit (at T_f=25°C, V_{CC}=15V)

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
INV	Collector Current At Off Signal Input	I _{CES}	V _{CE} =600V, Input Terminal Open		1.0	mA
	Collector-Emitter Saturation Voltage	V _{CE(Sat)}	I _C =150A		2.8	V
	Forward Voltage of FWD	V _F	-I _C =150A		3.0	V

Electrical Characteristics of Control Circuit (at T_f=25°C, V_{CC}=15V)

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
Current of P-Line Side Driver (One Unit)	I _{CCP}	f _{SW} =0~15kHz, T _C =-20~100°C	3		18	mA
Current of N-Line Side Driver (Three Units)	I _{CCN}	f _{SW} =0~15kHz, T _C =-20~100°C	10		65	
Input Signal Threshold Voltage	V _{IN(th)}	On	1.00	1.35	1.70	V
		Off	1.25	1.60	1.95	
Input Zener Voltage	V _Z	R _{IN} =20kΩ		8.0		°C
Over Heating Protection Temperature Level	T _{COH}	V _{DC} =0V, I _C =0A, Case Temp.	110		125	
Hysteresis	T _{CH}			20		
IGBT Chips Over Heating Protec. Temp. Level	T _{JOH}	Surface of IGBT Chip	150			
Hysteresis	T _{JH}			20		
Inverter Collector Current Protection Level	I _{OC}	T _f =125°C	225			A
Over Current Detecting Time	t _{DOC}	T _f =25°C		10		μs
Alarm Signal Hold Time	t _{ALM}		1.5	2		ms
Limiting Resistor for Alarm	R _{ALM}		1425	1500	1575	Ω
Under Voltage Protection Level	V _{UV}		11.0		12.5	V
Hysteresis	V _H		0.2			

Dynamic Characteristics (at T_C=T_f=125°C, V_{CC}=15V)


Items	Symbols	Conditions	Min.	Typ.	Max.	Units
Switching Time	t _{ON}	I _C =150A, V _{DC} =300V	0.3			μs
	t _{OFF}				3.6	
	t _{RR}	I _F =150A, V _{DC} =300V			0.4	

Thermal Characteristics

Items	Symbols	Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	R _{th(i-c)}	Inverter IGBT			0.21	°C/W
	R _{th(i-e)}	Diode			0.47	
	R _{th(c-f)}	With Thermal Compound		0.05		









■ Equivalent Circuit



Drivers include following functions


- Short circuit protection circuit
- Amplifier for driver
- Undervoltage protection circuit
- Overcurrent protection circuit
- IGBT Chip overheating protection

Control Circuit




■ Inverter


Collector Current vs. Collector-Emitter Voltage




Collector Current vs. Collector-Emitter Voltage




Switching Time vs. Collector Current




Switching Time vs. Collector Current










Forward Voltage vs. Forward Current




Reverse Recovery Characteristics







■ Outline Drawing



Weight: 440g