



PANEL CUTOUT THICKNESS FOR PLASTIC PANEL 0.8mm~1.5mm
 PANEL CUTOUT THICKNESS FOR STEEL PANEL 0.8mm~2.0mm

Revision			
Rev.	Description	Date	Approved

Material:

Housing: Thermoplastic
 Terminal: Copper Alloy

Characteristics:

Rating: 15A 250V AC for UL, CSA
 10A 250V AC for VDE, DEMKO, SEMKO
 FIMKO, NEMKO, SEV, KEMA
 Insulation Resistance: Over 100 OHM 500V DC
 Dielectric Strength: 2000V AC One Minute

ITEM	PART NAME	QTY	SPECS	MATERIAL	REMARK
2	TERMINAL	1SET	4.0	COPPER ALLOY	TIN-PLATED
1	HOUSING	1	SNAP-IN TYPE	94 V-2	
Dim range (mm)		Tolerance +/- (mm)		Qualtek Electronics Corp. PPC DIVISION	
0-1		0.15		Part Number: 701W-X2/02	
1-6		0.20		Description: UNIVERSAL SNAP-IN INLET,65°C	
6-18		0.30		Unit: mm	Rev A
18-50		0.50		Drawn/Date	Checked/Date
50-120		0.70		B.ZHANG	RF/10-25-04
120-250		0.90		10-25-04	JJH/10-25-04
250-500		1.20			