



PANEL CUTOUT THICKNESS FOR PLASTIC PANEL: 0.8mm~1.5mm
 PANEL CUTOUT THICKNESS FOR STEEL PANEL: 0.8mm~2.0mm

Revision			
Rev.	Description	Date	Approved

Material:

Housing: Thermoplastic
 Terminal: Copper Alloy

Characteristics:

Rating: 10A/15A 250V AC for UL, CSA, VDE, DEMKO, SEMKO
 FIMKO, NEMKO, SEV, KEMA
 Insulation Resistance: Over 100 OHM 500V DC
 Dielectric Strength: 2000V AC One Minute

2	Contact PIN Bronze Strip t=2mm Ni-Plated			
1	Body Insulator Nylon A216-BK			
Dim range (mm)	Tolerance +/- (mm)	Qualtek Electronics Corp. PPC DIVISION		
		Part Number: 701W-X2/04		
0-1	0.15	Description: UNIVERSAL SNAP-IN INLET, 65°C		
1-6	0.20			
6-18	0.30	Unit: mm	Rev A	
18-50	0.50			
50-120	0.70	Drawn/Date	Checked/Date	Approved/Date
120-250	0.90			
250-500	1.20	B.ZHANG 10-25-04	RF/10-25-04	JJH/10-25-04