

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS			DOC. NO. SPC-F004 * Effective: 12/21/98 * DCP No: 680					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1190	A	Released	JWM	1/30/02	HO	2/13/02	DJC	2/13/02

OUTPUT SPECIFICATIONS

Operating modes: Constant voltage or constant current with automatic crossover.

Voltage range: 0V to 18V

Current range: 0A to 20A

Overvoltage protection: 10% to 110% of max. Output voltage.

Setting resolution: 10mV, 10mA.

Load regulation: <0.01% of max. O/P for 90% change.

Line regulation: <0.01% of max. O/P for 10% change.

Output impedance: <1milliohm in constant voltage mode.

>5kilo-ohm in constant current mode.

Ripple & noise: <1mV RMS typical in constant voltage.

<3mA RMS typical in constant current

HF common mode noise: Typically <3mV RMS, <10mV pk.

Transient load response: <20us to within 50mV of set level for 90% load change.

Temperature coefficient: typically <100ppm/°C.

Overvoltage protection delay: <200us.

Protection functions: Overvoltage trip, Regulator overtemperature Sense miswiring.

Status indication: Output on/off lamp, Constant voltage mode lamp Constant current mode lamp, Trip message.

Output switch: Electronic.

Output terminals: 4mm output terminals at front, screw terminals for output and sense at rear.

Output protection: Full forward and reverse protection via OVP and diode damp.



INPUT SPECIFICATIONS

Input voltage range: 180V to 270V RMS, 90V to 135V RMS, 47 to 63Hz -

Power requirement: 750VA max.

Voltage range selection: Rear panel slide switch.

METER SPECIFICATIONS

Meter types: Separate 4 digit meters for voltage and current with 12.5mm (0.5") LED displays.

Meter resolutions: 10mV, 10mA.

Meter accuracies: Voltage: $\pm(0.2\% + 1 \text{ digit})$

Current: $\pm(0.5\% + 1 \text{ digit})$.

MECHANICAL & ENVIRONMENTAL

Electrical safety: Complies with EN61010-1.

EMC: Complies with EN50081-1 and EN50082-1.

Temperature: +5°C to +40°C operating, 20% to 80% RH, -40°C to +70°C storage.

Size: 210 x 130 x 350mm (WxHxD)

Weight: 5.0kg

FRONT PANEL CONTROLS

Voltage setting: Via single rotary controls for coarse and fine control.

Current setting: Via single tum semi-logarithmic rotary control.

Overvoltage setting: Via screwdriver adjustable preset potentiometer

Output On/Off Via large paddle lever switch.

SPC-F004.DWG

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TENMA[®]

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	1/30/02	High Current Laboratory Power Supply			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Hisham Odish	2/13/02	A	72-6852	19C7705.dwg	A
APPROVED BY:	DATE:	SCALE: NTS		U.O.M.: INCHES [mm]		SHEET: 1 OF 1
Daniel Carey	2/13/02					