

[Return to search](#)

[Print Page](#)



**Product Number:** 76314  
**Order Abbreviation:** 8018  
**General Description:** 15 watt, nonhalogen, low voltage

**Product Information**

Abbrev. With Packaging Info.	8018 6V 100/CS 1/SKU
Application	Projector
Average Rated Life (hr)	100
Base	B15d Double Contact Bayonet
Class	C (gas)
Color Rendering Index (CRI)	100
Diameter d (in)	0.741
Diameter d (mm)	19
Distance a (in)	0.195
Distance a (mm)	5
Filament Dimensions Length (in)	0.074
Filament Dimensions Length (mm)	1.9
Filament Dimensions Width (in)	0.059
Filament Dimensions Width (mm)	1.5
Lamp Finish	Clear
Length l (in)	2.028
Length l (mm)	52
Length l max. (in)	2.028
Length l max. (mm)	52
LIF Code	M/20
Maximum Overall Length - MOL (in)	2.028
Maximum Overall Length - MOL (mm)	52
Nominal Voltage (V)	6.00
Nominal Wattage (W)	15.00
Operating Position	h 30
Type of Current	AC

**Additional Product Information**

[Product Documents, Graphs, and Images](#)



**Packaging Information**

**Footnotes**

- Lamp has a flat core filament with filament area perpendicular to the lamp axis.
- h (Operating Position) = Vertical, base up

[Print Page](#)