查询2SK2148-01供应商 捷多邦，专业PCB打样工厂，24小时加急出货

FUJI ELECTRIC

2SK2148-01

FAP-IIA Series

N-channel MOS-FET			
600V	0,75Ω	12A	80W

> Features

- High Speed Switching
- Low On-Resistance
- No Secondary Breakdown
- Low Driving Power
- High Voltage
- VGS = ± 30V Guarantee
- Avalanche Proof

> Outline Drawing

TO-3PF



> Applications

- Switching Regulators
- UPS
- DC-DC converters
- General Purpose Power Amplifier

> Maximum Ratings and Characteristics

- Absolute Maximum Ratings (T_C=25°C), unless otherwise specified

Item	Symbol	Rating	Unit
Drain-Source-Voltage	V_{DS}	600	V
Drain-Gate-Voltage (R_{GS}=20KΩ)	V_{DGR}	600	V
Continous Drain Current	I_D	12	A
Pulsed Drain Current	$I_{D(puls)}$	48	A
Gate-Source-Voltage	V_{GS}	±30	V
Max. Power Dissipation	P_D	80	W
Operating and Storage Temperature Range	T_{ch}	150	°C
	T_{stg}	-55 ~ +150	°C

> Equivalent Circuit



- Electrical Characteristics (T_C=25°C), unless otherwise specified

Item	Symbol	Test conditions		Min.	Typ.	Max.	Unit
Drain-Source Breakdown-Voltage	$V_{(BR)DSS}$	I_D=1mA	V_{GS}=0V	600			V
Gate Threshhold Voltage	$V_{GS(th)}$	I_D=1mA	V_{DS}=V_{GS}	2,5	3,0	3,5	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=600V	T_{ch}=25°C		10	500	µA
		V_{GS}=0V	T_{ch}=125°C		0,2	1,0	mA
Gate Source Leakage Current	I_{GSS}	V_{GS}=±30V	V_{DS}=0V		10	100	nA
Drain Source On-State Resistance	$R_{DS(on)}$	I_D=6A	V_{GS}=10V		0,55	0,75	Ω
Forward Transconductance	g_{fs}	I_D=6A	V_{DS}=25V	6	12		S
Input Capacitance	C_{iss}	V_{DS}=25V			2500	3800	pF
Output Capacitance	C_{oss}	V_{GS}=0V			220	330	pF
Reverse Transfer Capacitance	C_{rss}	f=1MHz			50	75	pF
Turn-On-Time t_{on} (t_{on}=$t_{d(on)}$+t_r)	$t_{d(on)}$	V_{CC}=300V			30	45	ns
	t_r	I_D=12A			60	90	ns
Turn-Off-Time t_{off} (t_{on}=$t_{d(off)}$+t_f)	$t_{d(off)}$	V_{GS}=10V			140	210	ns
	t_f	R_{GS}=10 Ω			80	120	ns
Avalanche Capability	I_{AV}	L = 100µH	T_{ch}=25°C	12			A
Continous Reverse Drain Current	I_{DR}					12	A
Pulsed Reverse Drain Current	I_{DRM}					48	A
Diode Forward On-Voltage	V_{SD}	I_F=2xI_{DR} V_{GS}=0V	T_{ch}=25°C		1,05	1,58	V
Reverse Recovery Time	t_{rr}	I_F=I_{DR} V_{GS}=0V			450		ns
Reverse Recovery Charge	Q_{rr}	-dI_F/dt=100A/µs T_{ch}=25°C			3		µC

- Thermal Characteristics

Item	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Thermal Resistance	$R_{th(ch-a)}$	channel to air			30	°C/W
	$R_{th(ch-c)}$	channel to case			1,56	°C/W

找PDF 维库一下 pdf.dzsc.com

N-channel MOS-FET			
600V	0,75Ω	12A	80W

2SK2148-01

FAP-IIA Series

FUJI ELECTRIC

> Characteristics

Typical Output Characteristics



Drain-Source-On-State Resistance vs. T_{ch}



Typical Transfer Characteristics



Typical Drain-Source-On-State-Resistance vs. I_D



Typical Forward Transconductance vs. I_D



Gate Threshold Voltage vs. T_{ch}



Typical Capacitance vs. V_{DS}



Typical Input Charge



Forward Characteristics of Reverse Diode



Allowable Power Dissipation vs. T_C



Safe operation area



Transient Thermal impedance