


SML80B13F


TO-247AD Package Outline.
Dimensions in mm (inches)



Pin 1 – Gate

Pin 2 – Drain

Pin 3 – Source



N-CHANNEL ENHANCEMENT MODE HIGH VOLTAGE POWER MOSFETS

V_{DSS} **800V**
 $I_{D(cont)}$ **13A**
 $R_{DS(on)}$ **0.650Ω**

- Faster Switching
- Lower Leakage
- 100% Avalanche Tested
- Popular TO-247 Package

StarMOS is a new generation of high voltage N-Channel enhancement mode power MOSFETs. This new technology minimises the JFET effect, increases packing density and reduces the on-resistance. StarMOS also achieves faster switching speeds through optimised gate layout.

ABSOLUTE MAXIMUM RATINGS (T_{case} = 25°C unless otherwise stated)

V_{DSS}	Drain – Source Voltage	800	V
I_D	Continuous Drain Current	13	A
I_{DM}	Pulsed Drain Current ¹	52	A
V_{GS}	Gate – Source Voltage	±30	V
V_{GSM}	Gate – Source Voltage Transient	±40	
P_D	Total Power Dissipation @ T _{case} = 25°C	280	W
	Derate Linearly	2.24	W/°C
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55 to 150	°C
T_L	Lead Temperature : 0.063" from Case for 10 Sec.	300	
I_{AR}	Avalanche Current ¹ (Repetitive and Non-Repetitive)	13	A
E_{AR}	Repetitive Avalanche Energy ¹	30	mJ
E_{AS}	Single Pulse Avalanche Energy ²	1210	

1) Repetitive Rating: Pulse Width limited by maximum junction temperature.

2) Starting T_J = 25°C, L = mH, R_G = 25Ω, Peak I_L = 13A

STATIC ELECTRICAL RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)


	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain – Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	800			V
I_{DSS}	Zero Gate Voltage Drain Current ($V_{GS} = 0V$)	$V_{DS} = V_{DSS}$			25	μA
		$V_{DS} = 0.8V_{DSS}, T_C = 125^{\circ}C$			1000	
I_{GSS}	Gate – Source Leakage Current	$V_{GS} = \pm 30V, V_{DS} = 0V$			± 100	nA
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 1.0mA$	2		4	V
$I_{D(ON)}$	On State Drain Current ²	$V_{DS} > I_{D(ON)} \times R_{DS(ON)} \text{ Max}$ $V_{GS} = 10V$	13			A
$R_{DS(ON)}$	Drain – Source On State Resistance ²	$V_{GS} = 10V, I_D = 0.5 I_D [\text{Cont.}]$			0.65	Ω

DYNAMIC CHARACTERISTICS

	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0V$		3050	3700	pF
C_{oss}	Output Capacitance	$V_{DS} = 25V$		300	420	
C_{rss}	Reverse Transfer Capacitance	$f = 1MHz$		140	225	
Q_g	Total Gate Charge ³	$V_{GS} = 10V$		150	225	nC
Q_{gs}	Gate – Source Charge	$V_{DD} = 0.5 V_{DSS}$		17	25	
Q_{gd}	Gate – Drain (“Miller”) Charge	$I_D = I_D [\text{Cont.}] @ 25^{\circ}C$		70	105	
$t_{d(on)}$	Turn-on Delay Time	$V_{GS} = 15V$		12	24	ns
t_r	Rise Time	$V_{DD} = 0.5 V_{DSS}$		11	22	
$t_{d(off)}$	Turn-off Delay Time	$I_D = I_D [\text{Cont.}] @ 25^{\circ}C$		60	90	
t_f	Fall Time	$R_G = 1.6\Omega$		12	24	

SOURCE – DRAIN DIODE RATINGS AND CHARACTERISTICS

	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	(Body Diode)			13	A
I_{SM}	Pulsed Source Current ¹	(Body Diode)			52	
V_{SD}	Diode Forward Voltage ²	$V_{GS} = 0V, I_S = -I_D [\text{Cont.}]$			1.3	V
dv / dt	Peak Diode Recovery	$I_S \leq I_D [\text{cont}]$ $dl / dt = 100A/\mu s$ $V_{DD} \leq V_{DSS}$ $V_R = 200V$ $T_J \leq 150^{\circ}C$ $R_G = 2.0\Omega$			5	V/ns
t_{rr}	Reverse Recovery Time	$I_S = -I_D [\text{Cont.}]$ $dl / dt = 100A/\mu s$	$T_J = 25^{\circ}C$		200	ns
			$T_J = 125^{\circ}C$		350	
Q_{rr}	Reverse Recovery Charge	$I_S = -I_D [\text{Cont.}]$ $dl / dt = 100A/\mu s$	$T_J = 25^{\circ}C$	0.7		μC
			$T_J = 125^{\circ}C$	1.8		
I_{rrm}	Peak Recovery Current	$I_S = -I_D [\text{Cont.}]$ $dl / dt = 100A/\mu s$	$T_J = 25^{\circ}C$	11		A
			$T_J = 125^{\circ}C$	17		



SML80B13F

THERMAL CHARACTERISTICS

	Characteristic	Min.	Typ.	Max.	Unit
R _{θJC}	Junction to Case			0.45	°C/W
R _{θJA}	Junction to Ambient			40	

- 1) Repetitive Rating: Pulse Width limited by maximum junction temperature.
- 2) Pulse Test: Pulse Width < 380μS , Duty Cycle < 2%
- 3) See MIL-STD-750 Method 3471



CAUTION — Electrostatic Sensitive Devices. Anti-Static Procedures Must Be Followed.