



Search This Product Catalog

[Product Catalog for Global Telecommunications OEM Site](#) > [Products for Equipment Manufacturers](#) . . . [FC Connectors and Couplings](#) > [FC Couplings](#) >

 **Printer-friendly format 8210 Coupling FC SM**



**The FC/PC Connector is a field mountable, pull-proof connector that is fully compatible with all FC connectors adhering to the NTT specification.**

[\[click to enlarge\]](#)

3M Id : 80-6104-4239-6  
GTIN(UPC/EAN) : 0 00 54007 48805 7

**Additional Information**

The FC/PC connector maximizes termination yield through ease of mounting and a high performance polishing procedure. The three-piece connector design (connector, crimp ring, and boot) is mounted using the same simple process used for other 3M connectors. The FC/PC connector is available in single-mode and multimode utilizing epoxy adhesive. It is also available in multimode preloaded with 3M's

[Full Text . . .](#)

**Learn More . . .**

[Packaging Data](#)

[FC/PC Connector and Accessories - Illustration/Line Art- \(TIFF\)](#)

[FC/PC Connector and Accessories - Illustration/Line Art- \(TIFF\)](#)

[FC/PC Connector Features and Benefits - Features and Benefits- \(JPG\)](#)

[Fiber Optic ST and FC Connectors - Instructions/Manual \(PDF 662.8 K\)](#)

**Please Note:**

Adobe® Acrobat® Reader is required to view PDF documents.



**Characteristics**

<b>Operating Temperature Range</b>	-40 to 85 Degree Celsius
<b>Primary Trademark Name</b>	3M

Return to Solutions for Network Equipment Manufacturers

Product Catalog for Global Telecommunications OEM Site

- Products for Business Enterprise
- Products for Carriers
- **Products for Equipment Manufacturers**

Related Solution Sites

- 3M Access Network
- Enterprise Networks