

# **Material Safety Data Sheet**

Revision Date Prepared by Technical Information

March 28<sup>th</sup>, 2005 David MacKinnon 1-800-201-8822 or support@mgchemicals.com

Head Office Emergency

9347 - 193 Street, Surrey, B.C., V4N 4E7 Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

#### **Section 1: Product Identification**

MSDS Code: 824 - liquid Name: Isopropyl Alcohol

Related Part Numbers: 824-100ML; 824-500ML; 824-1L; 824-4L; 824-20L; 824-

1G; 824-W

Use: For removing flux, light oils and residues. Cleaning tape heads, contacts, and circuit

boards.

#### Section 2: Hazardous Ingredients

CAS# Chemical Name Percentage by weight ACGIH TWA Osha Pel Osha Stel 67-63-0 2-propanol 100 200ppm 400ppm 500ppm

### **Section 3: Hazards Identification**

WHMIS Codes: B2, D2B

NFPA Ratings: Health 1 Flammability 3 Reactivity 0 HMIS Ratings: Health 1 Flammability 4 Reactivity 0

Eyes: May cause eye irritation, characterized by a burning sensation, redness, tearing, inflammation, and

possible corneal injury.

**Skin:** May cause skin irritation with pain and stinging, especially if skin is abraded.

Inhalation: May cause respiratory tract irritation. Inhaling high concentrations may cause central nervous system

effects characterized by headache, and dizziness.

Ingestion: Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting, and diarrhea. May

cause central nervous system depression.

Chronic: No effects known

## Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush with water or saline for 20 minutes. Get medical aid.

**Skin:** Wash skin with large quantities of soap and water. Get medical aid if symptoms persist.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical aid.

Ingestion: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.



# Section 5: Fire Fighting Measures

**Autoignition** 432°C Flash Point: 12°C LEL / UEL: 2 / 12 Temperature:

Extinguishing

Use water spray, dry chemical, carbon dioxide, or chemical foam. Media:

General Will burn if involved in a fire. Vapors can travel to a source of ignition and flash back. This product is

Information: an explosion hazard.

#### Section 6: Accidental Release Measures

Spill Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection.

Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further Procedure:

residue with paper towel and place in container. Wash spill area with soap and water.

## Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do

not expose container to heat or flame.

Keep away from sources of ignition. Store in a cool, dry, well ventilated area, away from incompatible Storage:

substances.

## **Section 8: Exposure Controls**

Routes of Eyes, ingestion, inhalation, and skin.

entry:

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure

Personal Protection: Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when adequate ventilation or local

exhaust ventilation to keep airborne concentrations below exposure limits cannot be achieved.

#### Section 9: Physical and Chemical Properties

**Physical** Solubility: completely liquid Odor: alcohol Evaporation

State: Rate: (ether=1)

**Boiling** 82°C Specific 0.79 Vapor 1 PSI **Vapor** 2.1(Air=1) pH: n/a

Point: Gravity: Pressure: @21°C Density:

## Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures.

Conditions to

Temperatures over 40°C, ignition sources, and incompatible substances. avoid:

Strong oxidizers, acetaldehyde, chlorine, ethylene oxide, acids and isocyanates, hydrogen +

palladium, nitroform, oleum, phosgene, oxygen, aluminum, aluminum triisopropoxide, Incompatibilities:

trinitromethane, barium perchlorate, tetrafluoroborate, chromium trioxide, sodium dichromate

+ sulfuric acid.

Polymerization: Will not occur.

Decomposition: Carbon monoxide, carbon dioxide, acrid smoke and fumes.

#### Section 11: Toxicological Information

Sensitization: (effects of repeated exposure) Repeated skin contact may cause defatting of the skin resulting

in dermatitis.

(LD50):



Carcinogenicity: (risk of cancer) No

Teratogenicity: (risk of malformation in an

unborn fetus)

Reproductive Toxicity: (risk of sterility) No

Mutangenicity: (risk of heritable genetic effects) No

Lethal Exposure Ingestion(LD50): 6400 Inhalation 16000 Skin n/e

No

Concentrations: mg/kg (rat) (LC50): ppm/8h (rat)

## Section 12: Ecological Information

General Avoid runoff into storms and sewers which lead into waterways. Water runoff can cause

**Information:** environmental damage.

Environmental Impact Data: (percentage by weight)

**CFC**: 0 **HFC**: 0 **CI.Solv**.: 0 **VOC**: 100 **HCFC**: 0 **ODP**: 0

## **Section 13: Disposal Information**

General Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff

**Information:** can cause environmental damage.

#### Section 14: Transportation Information

**Ground:** (all sizes 1 liter or less)

Consumer Commodity, ORM-D.

Ground: - Large Sizes: (all sizes larger than 1 liter)

Shipping Name – Isopropanol, Flash Point 12°C, Class 3, UN# 1219, Packing Group II, Subsidiary Risk – nil, Use only MG Chemicals certified outer cartons. Tape all seems on the carton. Hazard Label required – Flammable Liquid. A double arrow orientation label is required and is already printed on the original outer carton. Shipper must be trained and certified to handle dangerous documented goods. Refer to CFR 49, TDG regulations (Canada).

Air:

Shipper must be trained and certified. Refer to IATA regulations.

Sea - All Sizes:

Shipper must be trained and certified. Refer to IMDG regulations.

#### Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain any chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

## Section 15: Regulatory Information cont'd

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

PAGE 3 / 4 MSDS Code: 824 - Liquid