

8471 Paired - High-Conductivity Copper Speaker Cable Twisted Jacketed Con

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Related Documents : No. 1.pdf</p>
--	--

Description:

16 AWG stranded (19x29) tinned copper conductors, PVC insulation, twisted pair, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	16
Stranding	19x29
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.023 in.
Lay Length	2 in.
Twists/ft.	6

Pair Color Code Chart :

Number	Color
1	Black & White

INNER SHIELD:

Inner Shield Material	Unshielded
-----------------------	------------

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.032 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.274 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

8471 Paired - High-Conductivity Copper Speaker Cable Twisted Jacketed Con

Operating Temperature Range	-20°C To +80°C
Non-UL Temperature Rating	60°C (UL AWM Style 2598)
Bulk Cable Weight	35.9 lbs/1000 ft.
Max. Recommended Pulling Tension	61 lbs.
Min. Bend Radius (Install)	5.1 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMG
CEC/C(UL) Specification	CMG
AWM Specification	UL Style 2598 (300 V 60°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
C(UL) Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	0.184 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	33 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	4.49 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (UL AWM Style 2598)
Max. Recommended Current	7.1 Amps per conductor @ 25°C

NOTES:

Notes	Nominal Breakdown Voltage - Jacket 20 KV RMS; Nominal Breakdown Voltage Between Conductors 20 KV RMS.
-------	---

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8471 0601000	1 PR #16 PVC FRPVC	1000	43	CHROME	C
8471 060500	1 PR #16 PVC FRPVC	500	20	CHROME	C
8471 060U1000	1 PR #16 PVC FRPVC	U1000	41	CHROME	
8471 060U500	1 PR #16 PVC FRPVC	U500	21	CHROME	

C = CRATE REEL PUT-UP.

8471 Paired - High-Conductivity Copper Speaker Cable Twisted Jacketed Con

Revision Number: 1 Revision Date: 07-28-2006

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.