







Power MOSFETs

Logic Level - L²FETs — N-Channel Types

Maximum Ratings				Package					
									
BV _{DSS} (V)	I _{DS} (A)	r _{DS(ON)} OHMS	EAS (m)	TO-204	TO-205	TO-220	TO-251	TO-252	TO-247
50	2	0.75	N.R.	RFM15N05L	RFL2N05L	RFP4N05L RFP15N05L RFP14N05L RFP25N05L RFP50N05L	RFD14N05L RFD16N05L	RFD14N05LSM RFD16N05LSM	RFG50N05L
	4	0.60	N.R.						
	15	0.14	N.R.						
	14	0.100	100						
	16	0.047	200						
	25	0.047	200						
50	0.22**								
60	2	0.75	N.R.	RFM15N06L	RFL2N06L	RFP4N06L RFP12N06RLE RFP3055RLE RFP15N06L RFP17N06L RFP25N06L	RFD13N06RLE RFD3055RLE	RFD12N06RLESM RFD3055RLESM	
	4	0.60	N.R.						
	12	0.135**							
	12	0.180**							
	15	0.14	N.R.						
	17	0.100	N.R.						
25	0.07	N.R.							
80	1	1.20	N.R.	RFM12N08L	RFL1N08L	RFP2N08L RFP12N08L			
	2	1.05	N.R.						
	12	0.20	N.R.						
100	1	1.20	N.R.	2N6902* RFM12N10L	RFL1N10L 2N6901*	RFP2N10L RFP12N10L			
	1.50	1.40	N.R.						
	2	1.05	N.R.						
	12	0.20	N.R.						
120	1	1.90	N.R.	RFM10N12L	RFL1N12L	RFP2N12L RFP10N12L			
	2	1.75	N.R.						
	10	0.30	N.R.						
150	1	1.90	N.R.	RFM10N15L	RFL1N15L	RFP2N15L RFP10N15L			
	2	1.75	N.R.						
	10	0.30	N.R.						
180	1	3.65	N.R.	RFM8N18L	RFL1N18L	RFP2N18L RFP8N18L			
	2	3.50	N.R.						
	8	0.50	N.R.						
200	1	3.65	N.R.	2N6904* RFM8N20L	RFL1N20L 2N6903*	RFP2N20L RFP8N20L			
	1.5	3.65	N.R.						
	2	3.50	N.R.						
	8	0.65	N.R.						
	8	0.50	N.R.						

N.R. = Not Rated

*QPL Approved Types

**More Complete Ruggedness Capability Now Specified

