328 – 865 SIP industrial generators

Medusa









IP's Medusa Briggs & Stratton range of petrol powered industrial generators are very robust, highly portable, frame mounted and provide reliable and independant power wherever its needed.

Alternators used are self exciting heavy duty, maintenance free, highly reliable, brushless (115 / 230V) units fitted with twin outlet sockets and overload


Engines used are Briggs & Stratton new Industrial Plus or Vanguard units. Both ranges boast electronic ignition and low oil shutdown. All meet strict EEC noise and safety regulations.

The Industrial Plus range feature easy one pull first time starting, large fuel tank and air cleaner. Cast iron cylinder sleeve ensures longer life.

The Vanguard engines are Japanese built CHV units featuring a 2 year warranty. They are constructed to run all day, every day under the most demanding conditions with low fuel consumption. Other design features include: Cast iron cylinder sleeve, large fuel tank and air cleaner (for longer life), up to 25% less noise, 19% more torque and 11% more horse power than competitive models.

> FIRST PULL A S

ENGINES





FIET WWW.	
	1

MGIP 5.0 F	MGIP 3.5 F	MGVG 2.5 F	MGIP 2.2 F	MGIP 2.2 H	MGIP 1.5 F	MGIP 1.5 H	MODEL
04520	04510	04508	04506	04505	04502	04500	
5.0	3.5	2.5	2.2	2.2	1.5		ITEM NO
115/230	115 / 230	115 / 230				1.5	MAX. OUTPUT KVA
			115 / 230	115 / 230	115 / 230	115 / 230	VOLTAGE
FULL	FULL	FULL	FULL	HALF	FULL	HALF	FRAME
VP	I/P	V/G	VP	L/P	VP.	VP.	
11.0	8.0	5.5	5.0	5.0			ENGINE
3.8					3.5	3.5	HP
	3.8	4.0	3.8	3.8	3.8	3.8	FUEL TANK CAP LTRS
2.4	2.5	2.8	2.4	2.4	2.4	2.4	APPROX RUNNING TIME HRS
	-						
540x510x750	540x510x750	540 540 350				•	LOW OIL SHUTDOWN
		540x510x750	540x610x750	505x380x665	540x510x750	385x380x666	PACKED DIM. (HxWxL) MM
71	51	42	38	36	31	29	WEIGHT KGS

VP = INDUSTRIAL PLUS V/G = VANGUARD

renerc