


查询74LS21DC供应商


捷多邦，专业PCB打样工厂 24小时

CONNECTION DIAGRAMS

PINOUT A



PINOUT B



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$, $T_A = 0^\circ\text{C to } +70^\circ\text{C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$, $T_A = -55^\circ\text{C to } +125^\circ\text{C}$	
Plastic DIP (P)	A	7421PC, 74H21PC 74LS21PC		9A
Ceramic DIP (D)	A	7421DC, 74H21DC 74LS21DC	5421DM, 54H21DM 54LS21DM	6A
Flatpak (F)	A	7421FC, 74LS21FC	5421FM, 54LS21FM	3I
	B	74H21FC	54H21FM	

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74H		54/74LS		UNITS	CONDITIONS		
		Min	Max	Min	Max	Min	Max				
I _{CC} H	Power Supply Current	10		20		2.4		mA	V _{IN} = Open	V _{CC} = Max	
I _{CC} L		16		32		4.4			V _{IN} = Gnd		
t _{PLH}	Propagation Delay	27		12		15		ns	Figs. 3-1, 3-5		
t _{PHL}		19		12		15					

*Temperature range: AC limits apply at $T_A = +25^\circ\text{C}$ and $V_{CC} = +5.0\text{ V}$.