



UNISONIC TECHNOLOGIES CO., LTD

UT2309



Power MOSFET

P-CHANNEL ENHANCEMENT MODE

DESCRIPTION

The **UT2309** is P-channel Power MOSFET, designed with high density cell with fast switching speed, ultra low on-resistance, excellent thermal and electrical capabilities. Used in commercial and industrial surface mount applications and suited for low voltage applications such as DC/DC converters.

SYMBOL



SOT-23


*Pb-free plating product number: UT2309L

ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Normal	Lead Free Plating		1	2	3	
UT2309-AE3-R	UT2309L-AE3-R	SOT-23	S	G	D	Tape Reel

UT2309L-AE3-R 	(1)Packing Type	(1) R: Tape Reel
	(2)Package Type	(2) AE3: SOT-23
	(3)Lead Plating	(3) L: Lead Free Plating, Blank: Pb/Sn

MARKING



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current (Note 3)	I_D	-3.7	A
Pulsed Drain Current (Note 1, 2)	I_{DM}	-12	A
Total Power Dissipation	P_D	1.38	W
Junction Temperature	T_J	+150	°C
Storage Temperature	T_{STG}	-55 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Junction to Ambient (Note 3)	θ_{JA}			90	°C/W

■ ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$, unless otherwise specified)







PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0 V, I _D =-250 μA	-30			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =-30V, V _{GS} =0V			-0.5	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} = ±20V			5	nA
Breakdown Voltage Temperature Coefficient	Δ BV _{DSS} /ΔT _J	Reference to 25°C, I _D =-1mA		-0.02		V/°C
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =-250uA	-1		-3	V
Static Drain-Source On-Resistance (Note 2)	R _{DS(ON)}	V _{GS} =-10V, I _D =-5A			65	mΩ
		V _{GS} =-4.5V, I _D =-5A			85	mΩ
DYNAMIC CHARACTERISTICS						
Input Capacitance	C _{ISS}	V _{GS} =0V, V _{DS} =-25V, f=1.0MHz		412	660	pF
Output Capacitance	C _{OSS}			91		
Reverse Transfer Capacitance	C _{RSS}			62		
SWITCHING CHARACTERISTICS						
Turn-ON Delay Time (Note 2)	t _{D(ON)}	V _{DS} =-15V, I _D =-1A, R _G =3.3Ω, V _{GS} =-10V, R _D =15Ω		8		ns
Turn-ON Rise Time	t _R			5		
Turn-OFF Delay Time	t _{D(OFF)}			20		
Turn-OFF Fall Time	t _F			7		
Total Gate Charge (Note 2)	Q _G	V _{DS} =-24V, V _{GS} =-4.5V, I _D =-3A		5	8	nC
Gate-Source Charge	Q _{GS}			1		
Gate-Drain Charge	Q _{GD}			3		
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Forward On Voltage	V _{SD}	I _S =-1A, V _{GS} =0V		-0.76	-1.2	V
Reverse Recovery Time	t _{RR}	I _S =-3A, V _{GS} =0V,		20		ns
Reverse Recovery Charge	Q _{RR}	dI/dt=-100A/μs		15		nC

Notes: 1. Pulse width limited by $T_{J(MAX)}$





2. Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.

3. Surface mounted on 1 in^2 copper pad of FR4 board.

TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.