

HU-232CB

USB2.0 Card Bus Adapter



Key Features:

- Provides two USB2.0 downstream ports.
- Compliant with EHCI and OHCI specifications.
- Provides USB2.0 interface fully backward compatibility with USB 1.1 devices.
- Supports high-speed data transfer rate up to 480Mbps.
- Supports hot swapping and Plug-and-Play capability.
- Provides Bus fault detection and over current protection.

Specifications:

Interface:	32-bit card bus type II slot
Connectors:	Two USB2.0 downstream ports
Date Transfer Rate:	Supports high-speed 480Mbps / full-speed 12Mbps / low-speed 1.5Mbps
Output Voltage Per-port:	DC+5V
Output Current Per-port:	500mA
Protection:	By power switching IC protected
Environmental:	Operating Temperature: 5°C~40 °C Storage Temperature: -20°C~60°C Operating Humidity: 0%~80% RH, non-condensing
Dimensions:	120*64 mm
Certification:	FCC Class B, CE
System Support:	Windows® 98/SE, Windows® ME, Windows® 2000, Windows® XP Mac® OS. 10.1 or higher
Ordering Information:	HU-232CB USB2.0 Card Bus Adapter HU-232CBD USB2.0 Card Bus Adapter (No auxiliary power requires for low-powered device connection.)

