

K790 display panelpc



- ✓ High bright TFT/LCD display
- ✓ 12" 15" 17" och 19"
- ✓ Metallchassi
- ✓ Inbyggd multimedia PC
- ✓ VESA standard
- ✓ Ultra Slim

Model No.	K792	K795	K797	K799
MB	B78			
Core Logic	Intel 852GM + ICH4 supports FSB400 CPU, DDR 200/266Mhz			
CPU	Intel Celeron M 1.3GHz, Pentium M 1.8GHz			
System Memory RAM	2 x DDR SO-DIMM slot, up to 2 GB			
LCD Panel	12.1"	15"	17"	19"
Resolution	800*600	1024*768	1280*1024	1280*1024
Touch Panel	Resistive eTT	Resistive eTT(default) / SAW touch (option)		
Storage Device	2,5" Slim HDD or Compact Flash daughter board (default 40GB)			
I/O Port	DC Jack, LAN 1xRJ-45, Cash Drawerx1, Line in, Line out, COM x4 (COM1/COM2 standard, COM3/COM4 with power), USB x4, Printer x1, Power button, optional 2nd VGA DB 15-pin connector			
Slot expansion	Mini PCI slot for wireless LAN card expansion			
Audio	Audio Codec and amplifier on Motherboard			
Speaker	1x 8 ohm 3W	2 x 8 ohm 3W		
Power Adapter	External 19V 90W			
Temperature	Operation 0 ~40°C, storage -20 - 60°C			
Humidity	Operation 5% to 95% RH, Non-condensing, storage 5% to 95% RH, Non-condensing			
EMI /Safety	FCC Class A,/ CE, LVD			
Front Bezel Protection	NEMA3 / IP55 dust and water proof compliance			
OS support	WinXP Pro, Xpe, WEPOS, Windos NT 4.0/2000			
Mounting	75mm x 75mm Standard VESA	100mm x 100mm Standard VESA mounting holes		
Dimension (W x H x D)	317.4x256x 54mm	367.4x292.4x56.8mm	406x338x65.7mm	442x366x65.8mm

