

TOSHIBA

TD62707AP

TOSHIBA BIPOLAR DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC


TD62707AP

4CH HIGH-VOLTAGE SOURCE DRIVER WITH ENABLE

The TD62707AP is comprised of four source current output stages and enable inputs which can gate the outputs. All outputs feature integral clamp diodes for switching inductive loads. Applications include relay, hammer and lamp drivers.


FEATURES

- High output voltage $V_{CC}-V_{OUT}=50V$ MIN.
- Output current (single output) $I_{OUT} = -750mA$ MIN.
- Input compatible with TTL, 5V CMOS
- Output clamp diodes
- Enable inputs E1, $\bar{E}2$
- GND terminal = HEAT SINK
- Package type-AP : DIP-16pin




Weight : 1.11g (Typ.)

PIN CONNECTION (TOP VIEW)



SCHEMATICS (EACH DRIVER)



(Note) The output parasitic diodes cannot be used as clamp diodes.

961001EBA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.



TRUTH TABLE

E1	$\bar{E}2$	IN1~4	OUT1~4
H	H	H	OFF
H	L	H	ON
L	H	H	OFF
H	H	L	OFF
L	L	H	OFF
L	L	L	OFF
H	L	L	OFF

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V _{CC}	50	V
Output Voltage	V _{OUT}	- 50	V
Output Current	I _{OUT}	- 0.75	A / ch
Input Voltage	V _{IN1}	- 0.5~15	V
	V _{IN2} (Note 1)	- 0.5~V _{CC}	
Clamp Diode Reverse Voltage	V _R	50	V
Clamp Diode Forward Current	I _F	- 0.75	A
Power Dissipation	P _D	1.47 / 2.7 (Note 2)	W
Operating Temperature	T _{opr}	- 40~85	°C
Storage Temperature	T _{stg}	- 55~150	°C

(Note 1) V_{CC} ≤ 15V

(Note 2) On PCB (50×50×1.6mm Cu 50%)

RECOMMENDED OPERATING CONDITIONS (Ta = - 40~85°C)

CHARACTERISTIC	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Supply Voltage	V _{CC}	—	—	—	50	V	
Output Voltage	V _{OUT}	—	0	—	- 50	V	
Output Current	I _{OUT} (Note)	DC 1 Circuits, Ta = 25°C	0	—	- 600	mA / ch	
		T _{pw} = 25ms, 4 Circuits	0	—	- 600		
		Ta = 85°C, T _j = 120°C	0	—	- 160		
Input Voltage	"H" level "L" level	V _{IN}	0	—	15	V	
		V _{IH1}	V _{CC} > 15V	2.0	—		15
		V _{IH2}	V _{CC} ≤ 15V	2.0	—		V _{CC}
		V _{IL}	—	0	—		0.8
Clamp Diode Reverse Voltage	V _R	—	—	—	50	V	
Clamp Diode Forward Current	I _F	—	—	—	600	mA	
Power Dissipation	P _D	Ta = 85°C (Note)	—	—	1.2	W	

(Note) On PCB (50×50×1.6mm Cu 50%)

961001EBA2'


- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C unless otherwise noted V_{CC} = 50V, "H" = V_{IH}, "L" = V_{IL})


CHARACTERISTIC		SYMBOL	TEST CIR-CUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Voltage	"H" level	V _{IH}	1	—	2.0	—	—	V
	"L" level	V _{IL}			—	—	0.8	
Input Current	"H" level	IN	4	V _{IN} = H	—	70	100	μA
		E1		V _{E1} = H	—	0	10	
		E2		V _{E2} = H	—	66	100	
Input Current	"L" level	IN	5	V _{IN} = L	—	-40	-100	μA
		E1		V _{E1} = L	—	-20	-50	
		E2		V _{E2} = H	—	-40	-100	
Output Leakage Current		I _{OL}	2	V _{CC} = 50V, OUTPUT OFF	—	—	100	μA
Supply Current		I _{CCH}	4	V _{IN} = H, V _{E1} = H V _{E2} = L, OUTPUT OPEN	—	5.5	7.0	mA
		I _{CCL}	5	V _{IN} = L, V _{E1} = H V _{E2} = L, OUTPUT OFF	—	5.5	7.0	
Output Voltage	"H" level	V _{OH}	3	V _{IN} = H, V _{E1} = "H" V _{E2} = L, I _{OUT} = -500mA	V _{CC} -2.5	V _{CC} -2.0	—	V
Clamp Diode Reverse Current		I _R	6	V _R = 50V	—	—	100	μA
Clamp Diode Forward Voltage		V _F	7	I _F = 500mA	—	1.5	2.0	V
Turn-On Delay		t _{ON}	8	V _{CE} = 50V, R _L = 83Ω	—	0.5	—	μs
Turn-Off Delay		t _{OFF}			—	6.0	—	

TEST CIRCUIT


1. V_{IH}, V_{IL}




2. I_{OL}




3. V_{OH}




4. I_{IH}, I_{CCH}




5. I_{iL}, I_{CCL}





6. I_R



7. V_F









8. t_{ON}, t_{OFF}





- (Note 1) Pulse Width $50\mu s$, Duty Cycle 10%
Output Impedance 50Ω , $t_r \leq 5ns$, $t_f \leq 10ns$
- (Note 2) $V_{IH} = 3V$, $E1 = V_{IH}$, $\bar{E}2 = GND$, $V_{CC} = 50V$
- (Note 3) C_L includes probe and jig capacitance

PRECAUTIONS for USING


Utmost care is necessary in the design of the output line, V_{CC} and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.





OUTLINE DRAWING
DIP16-P-300-2.54A

Unit : mm



Weight : 1.11g (Typ.)