



High Voltage Transistors

NPN Silicon

**BSS71****CASE 22-03, STYLE 1
TO-18 (TO-206AA)**

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector–Emitter Voltage	V_{CEO}	200	Vdc
Collector–Base Voltage	V_{CBO}	200	Vdc
Emitter–Base Voltage	V_{EBO}	6.0	Vdc
Collector Current — Continuous	I_C	0.5	Adc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	0.5 2.86	Watts mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	2.5 14.3	Watts mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-65 to $+200$	$^\circ\text{C}$

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	70	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Collector–Emitter Breakdown Voltage ($I_C = 10$ mAdc, $I_B = 0$) ⁽¹⁾	$V_{(BR)CEO}$	200	—	—	Vdc
Collector–Base Breakdown Voltage ($I_C = 100$ μ Adc, $I_E = 0$)	$V_{(BR)CBO}$	200	—	—	Vdc
Emitter–Base Breakdown Voltage ($I_E = 100$ μ Adc, $I_C = 0$)	$V_{(BR)EBO}$	6.0	—	—	Vdc
Collector Cutoff Current ($V_{CB} = 150$ Vdc, $I_E = 0$)	I_{CBO}	—	—	50	nAdc
Collector–Emitter Cutoff Current ($V_{CE} = 150$ Vdc, $I_B = 0$)	I_{CEO}	—	—	500	nAdc
Emitter Cutoff Current ($V_{EB} = 5.0$ Vdc, $I_C = 0$)	I_{EBO}	—	—	50	nAdc

ON CHARACTERISTICS

DC Current Gain ($I_C = 0.1$ mAdc, $V_{CE} = 1.0$ Vdc) ($I_C = 1.0$ mAdc, $V_{CE} = 10$ Vdc) ($I_C = 10$ mAdc, $V_{CE} = 10$ Vdc) ⁽¹⁾ ($I_C = 30$ mAdc, $V_{CE} = 10$ Vdc) ⁽¹⁾	h_{FE}	20 30 50 40	40 45 120 140	— — — 250	—
Collector–Emitter Saturation Voltage ⁽¹⁾ ($I_C = 10$ mAdc, $I_B = 1.0$ mAdc) ($I_C = 30$ mAdc, $I_B = 3.0$ mAdc) ($I_C = 50$ mAdc, $I_B = 5.0$ mAdc)	$V_{CE(sat)}$	— — —	0.15 0.25 0.35	0.3 0.4 0.5	Vdc
Base–Emitter Saturation Voltage ⁽¹⁾ ($I_C = 10$ mAdc, $I_B = 1.0$ mAdc) ($I_C = 30$ mAdc, $I_B = 3.0$ mAdc) ($I_C = 50$ mAdc, $I_B = 5.0$ mAdc)	$V_{BE(sat)}$	— — —	0.7 0.8 0.85	0.8 0.9 1.0	Vdc

⁽¹⁾ Pulse Test: Pulse Width ≤ 300 μ s, Duty Cycle $\leq 2.0\%$.

BSS71

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Typ	Max	Unit
DYNAMIC CHARACTERISTICS					
Current–Gain — Bandwidth Product ($I_C = 20\text{ mAdc}$, $V_{CE} = 20\text{ Vdc}$, $f = 20\text{ MHz}$)	f_t	50	70	200	MHz
Output Capacitance ($I_E = 0$, $V_{CB} = 20\text{ Vdc}$, $f = 1.0\text{ MHz}$)	C_{ob}	—	3.5	—	pF
Input Capacitance ($I_C = 0$, $V_{EB} = 0.5\text{ Vdc}$, $f = 1.0\text{ MHz}$)	C_{ib}	—	45	—	pF
Turn–On Time ($I_{B1} = 10\text{ mAdc}$, $I_C = 50\text{ mAdc}$, $V_{CC} = 100\text{ Vdc}$)	t_{on}	—	100	—	ns
Turn–Off Time ($I_{B2} = 10\text{ mAdc}$, $I_C = 50\text{ mAdc}$, $V_{CC} = 100\text{ Vdc}$)	t_{off}	—	400	—	ns




Figure 1. DC Current Gain




Figure 2. Capacitances




Figure 3. Current–Gain — Bandwidth Product




Figure 4. Active–Region Safe Operating Area




Figure 5. "On" Voltages




Figure 6. Temperature Coefficients




Figure 7. Turn-On Time





Figure 8. Turn-Off Time

DUTY CYCLE < 1%
 $t_r, t_f < 5\text{ ns}$



	V_{IN}	V_{BB}
t_{on}	10.6 V	
t_{off}	20 V	-9.2 V





Figure 9. Switching Time Test Circuit

PACKAGE DIMENSIONS



CASE 22-03
 (TO-206AA)
 ISSUE R

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION J MEASURED FROM DIMENSION A MAXIMUM.
4. DIMENSION F APPLIES BETWEEN DIMENSION P AND L. DIMENSION D APPLIES BETWEEN DIMENSION L AND K MINIMUM. LEAD DIAMETER IS UNCONTROLLED IN DIMENSION P AND BEYOND DIMENSION K MINIMUM.
5. DIMENSION E INCLUDES THE TAB THICKNESS. (TAB THICKNESS IS 0.01(0.002) MAXIMUM).

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.209	0.230	5.31	5.84
B	0.178	0.195	4.52	4.95
C	0.170	0.210	4.32	5.33
D	0.016	0.021	0.406	0.533
E	—	0.030	—	0.762
F	0.016	0.019	0.406	0.483
G	0.100 BSC	—	2.54 BSC	—
H	0.036	0.046	0.914	1.17
J	0.028	0.048	0.711	1.22
K	0.500	—	12.70	—
L	0.250	—	6.35	—
M	45° BSC	—	45° BSC	—
N	0.050 BSC	—	1.27 BSC	—
P	—	0.050	—	1.27

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

How to reach us:

USA / EUROPE / Locations Not Listed: Motorola Literature Distribution;
 P.O. Box 5405, Denver, Colorado 80217. 303-675-2140 or 1-800-441-2447

Mfax™: RMFAX0@email.sps.mot.com – TOUCHTONE 602-244-6609
 INTERNET: <http://Design-NET.com>

JAPAN: Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, 6F Seibu-Butsuryu-Center,
 3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 81-3-3521-8315

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
 51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

