

# SN54ALS74A, SN54AS74, SN74ALS74A, SN74AS74

## DUAL D-TYPE POSITIVE-EDGE-TRIGGERED FLIP-FLOPS WITH CLEAR AND PRESET

SDAS143A – D2661, APRIL 1982 – REVISED SEPTEMBER 1987

- Package Options Include Plastic Small Outline Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas instruments Quality and Reliability

TYPE	TYPICAL MAXIMUM CLOCK FREQUENCY ( $C_L = 50$ pF)	TYPICAL POWER DISSIPATION PER FLIP-FLOP
'ALS74A	50 MHz	6 mW
'AS74	134 MHz	26 mW

### description

These devices contain two independent D-type positive-edge triggered flip-flops. A low level at the Preset or Clear inputs sets or resets the outputs regardless of the levels of the other inputs. When Preset and Clear are inactive (high), data at the D input meeting the setup time requirements are transferred to the outputs on the positive-going edge of the clock pulse. Clock triggering occurs at a voltage level and is not directly related to the rise time of the clock pulse. Following the hold time interval, data at the D input may be changed without affecting the levels at the outputs.


The SN54ALS74A and SN54AS74 are characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74ALS74A and SN74AS74 are characterized for operation from  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ .

FUNCTION TABLE


INPUTS				OUTPUTS	
PRESET	CLEAR	CLOCK	D	Q	$\bar{Q}$
L	H	X	X	H	L
H	L	X	X	L	H
L	L	X	X	H <sup>†</sup>	H <sup>†</sup>
H	H	↑	H	H	L
H	H	↑	L	L	H
H	H	L	X	Q <sub>O</sub>	$\bar{Q}_O$

<sup>†</sup> The output levels in this configuration are not guaranteed to meet the minimum levels for  $V_{OH}$  if the lows at Preset and Clear are near  $V_{IL}$  maximum. Furthermore, this configuration is nonstable; that is, it will not persist when Preset or Clear; returns to their inactive (high) level.

SN54ALS74A, SN54AS74 ... J PACKAGE  
SN74ALS74A, SN74AS74 ... D OR N PACKAGE  
(TOP VIEW)




SN54ALS74A, SN54AS74 ... FK PACKAGE  
(TOP VIEW)



NC – No internal connection

### logic symbol<sup>‡</sup>



<sup>‡</sup> This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

# SN54ALS74A, SN54AS74, SN74ALS74A, SN74AS74

## DUAL D-TYPE POSITIVE-EDGE-TRIGGERED FLIP-FLOPS WITH CLEAR AND PRESET

SDAS143A – D2661, APRIL 1982 – REVISED SEPTEMBER 1987

### absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, $V_{CC}$	7 V
Input voltage	7 V
Operating free-air temperature range: SN54ALS74A, SN54ALS74	–55°C to 125°C
SN74ALS74A, SN74ALS74	0°C to 70°C
Storage temperature range	–65°C to 150°C

### recommended operating conditions

		SN54AS74			SN74AS74			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
$V_{CC}$	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
$V_{IH}$	High-level input voltage	2			2			V
$V_{IL}$	Low-level input voltage						0.8	V
				0.8†				
				0.7‡				
$I_{OH}$	High-level output current			–0.4			–0.4	mA
$I_{OL}$	Low-level output current			4			8	mA
$f_{clock}$	Clock frequency	0		25	0		34	MHz
$t_w$	Pulse duration	$\overline{PRE}$ or $\overline{CLR}$ low		15	15			ns
		CLK high		16.5	14.5			
		CLK low		16.5	14.5			
$t_{su}$	Setup time before CLK↑	Data		15	15			ns
		$\overline{PRE}$ or $\overline{CLR}$ inactive		10	10			
$t_h$	Hold time, data after CLK↑	0			0			ns
$T_A$	Operating free-air temperature	–55		125	0		70	°C

† Tested at –55°C to 70°C.

‡ Tested at 70°C 125°C, per MIL-STD-883, method 5005, sub-group 1, 2, and 3. Static tests are performed at 25°C, 125°C, and –55°C.

### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54AS74			SN74AS74			UNIT
				MIN	TYP§	MAX	MIN	TYP§	MAX	
$V_{IK}$		$V_{CC} = 4.5\text{ V}$ , $I_I = -18\text{ mA}$					–1.2		–1.5	V
$V_{OH}$		$V_{CC} = 4.5\text{ V to } 5.5\text{ V}$ , $I_{OH} = -2\text{ mA}$		$V_{CC} - 2$			$V_{CC} - 2$			V
$V_{OL}$		$V_{CC} = 4.5\text{ V}$ , $I_{OL} = 4\text{ mA}$			0.25	0.4		0.25	0.4	V
$V_{OL}$		$V_{CC} = 4.5\text{ V}$ , $I_{OL} = 8\text{ mA}$						0.35	0.5	
$I_I$	CLK or D	$V_{CC} = 4.5\text{ V}$ , $V_I = 7\text{ V}$				0.1			0.1	mA
	$\overline{PRE}$ or $\overline{CLR}$					0.2			0.2	
$I_{IH}$	CLK or D	$V_{CC} = 4.5\text{ V}$ , $V_I = 2.7\text{ V}$				20			20	$\mu\text{A}$
	$\overline{PRE}$ or $\overline{CLR}$					40			40	
$I_{IL}$	CLK or D	$V_{CC} = 4.5\text{ V}$ , $V_I = 0.4\text{ V}$				–0.2			–0.2	mA
	$\overline{PRE}$ or $\overline{CLR}$					–0.4			–0.4	
$I_{O\uparrow}$		$V_{CC} = 5.5\text{ V}$ , $V_O = 2.25\text{ V}$		–30		–112	–30		–112	mA
$I_{CC}$		$V_{CC} = 5.5\text{ V}$ , See Note 1			2.4	4		2.4	4	mA

§ All typical values are at  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

¶ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current,  $I_{OS}$ .

NOTE 1:  $I_{CC}$  is measured with D, CLK, and  $\overline{PRE}$  grounded, then with D, CLK, and  $\overline{CLR}$  grounded.

**SN54ALS74A, SN74ALS74A**  
**DUAL D-TYPE POSITIVE-EDGE-TRIGGERED**  
**FLIP-FLOPS WITH CLEAR AND PRESET**  
SDAS143A – D2661, APRIL 1982 – REVISED SEPTEMBER 1987

**switching characteristics (see Note 2)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	VCC = 4.5 V to 5.5 V, CL = 50 pF, RL = 500 Ω, TA = MIN TO MAX†				UNIT
			SN54ALS74A		SN74ALS74A		
			MIN	MAX	MIN	MAX	
fmax			25		34		MHz
tPLH	PRE or CLR	Q or Q̄	3	13.5	3	13	ns
tPHL			5	17	5	15	
tPLH	CLK	Q or Q̄	5	17	5	16	ns
tPHL			5	18	5	18	

† For conditions shown MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTE 2: Load circuit and voltage waveforms are shown in Section 1 of the *ALS/AS Logic Data Book*, 1986.

# SN54AS74, SN74AS74

## DUAL D-TYPE POSITIVE-EDGE-TRIGGERED FLIP-FLOPS WITH CLEAR AND PRESET

SDAS143A – D2661, APRIL 1982 – REVISED SEPTEMBER 1987

### recommended operating conditions

			SN54AS74			SN74AS74			UNIT
			MIN	NOM	MAX	MIN	NOM	MAX	
V <sub>CC</sub>	Supply voltage		4.5	5	5.5	4.5	5	5.5	V
V <sub>IH</sub>	High-level input voltage		2			2			V
V <sub>IL</sub>	Low-level input voltage				0.8			0.8	V
I <sub>OH</sub>	High-level output current				−2			−2	mA
I <sub>OL</sub>	Low-level output current				20			20	mA
f <sub>clock</sub>	Clock frequency		0		90	0		105	MHz
t <sub>w</sub>	Pulse duration	$\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ low	4			4			ns
		CLK high	4			4			
		CLK low	5.5			5.5			
t <sub>su</sub>	Setup time before CLK↑	Data	4.5			4.5			ns
		$\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ inactive	2			2			
t <sub>h</sub>	Hold time, data after CLK↑		0			0			ns
T <sub>A</sub>	Operating free-air temperature		−55		125	0		70	°C

### electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS	SN54AS74			SN74AS74			UNIT
			MIN	TYP†	MAX	MIN	TYP†	MAX	
$V_{IK}$		$V_{CC} = 4.5\text{ V}$ , $I_I = -18\text{ mA}$				–1.2		–1.2	V
$V_{OH}$		$V_{CC} = 4.5\text{ V to } 5.5\text{ V}$ , $I_{OH} = -2\text{ mA}$	$V_{CC} - 2$			$V_{CC} - 2$			V
$V_{OL}$		$V_{CC} = 4.5\text{ V}$ , $I_{OL} = 20\text{ mA}$	0.25		0.5	0.25		0.5	V
$I_I$		$V_{CC} = 5.5\text{ V}$ , $V_I = 7\text{ V}$			0.1			0.1	mA
$I_{IH}$	CLK or D	$V_{CC} = 5.5\text{ V}$ , $V_I = 2.7\text{ V}$			20			20	$\mu\text{A}$
	$\overline{PRE}$ or $\overline{CLR}$				40			40	
$I_{IL}$	CLK or D	$V_{CC} = 5.5\text{ V}$ , $V_I = 0.4\text{ V}$			–0.5			–0.5	mA
	$\overline{PRE}$ or $\overline{CLR}$				–1.8			–1.8	
$I_{O\ddagger}$		$V_{CC} = 5.5\text{ V}$ , $V_O = 2.25\text{ V}$	–30		–112	–30		–112	mA
$I_{CC}$		$V_{CC} = 5.5\text{ V}$ , See Note 1		10.5	16		10.5	16	mA

† All typical values are at  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

‡ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current,  $I_{OS}$ .

NOTE 1:  $I_{CC}$  is measured with D, CLK, and  $\overline{PRE}$  grounded, then with D, CLK, and  $\overline{CLR}$  grounded.

### switching characteristics (see Note 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V <sub>CC</sub> = 4.5 V to 5.5 V, C <sub>L</sub> = 50 pF, R <sub>L</sub> = 500 Ω, T <sub>A</sub> = MIN TO MAX§				UNIT
			SN54AS74A		SN74AS74A		
			MIN	MAX	MIN	MAX	
f <sub>max</sub>			90		105		MHz
t <sub>PLH</sub>	PRE or CLR	Q or Q̄	3	8.5	3	7.5	ns
t <sub>PHL</sub>			3.5	11.5	3.5	10.5	
t <sub>PLH</sub>	CLK	Q or Q̄	3.5	9	3.5	8	ns
t <sub>PHL</sub>			4.5	10.5	4.5	9	

§ For conditions shown MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTE 2: Load circuit and voltage waveforms are shown in Section 1 of the *ALS/AS Logic Data Book*, 1986.

## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.