

December 2000

LP2989

Micropower/Low Noise, 500 mA Ultra Low-Dropout Regulator

For Use with Ceramic Output Capacitors

General Description

The LP2989 is a fixed-output 500 mA precision LDO regulator designed for use with ceramic output capacitors.

Output noise can be reduced to 18 μ V (typical) by connecting an external 10 nF capacitor to the bypass pin.

Using an optimized VIP™ (Vertically Integrated PNP) process, the LP2989 delivers superior performance:

Dropout Voltage: Typically 310 mV @ 500 mA load, and 1 mV @ 100 μ A load.

Ground Pin Current: Typically 3 mA @ 500 mA load, and 110 μ A @ 100 μ A load.

Sleep Mode: The LP2989 draws less than 0.8 μ A quiescent current when shutdown pin is pulled low.

Error Flag: The built-in error flag goes low when the output drops approximately 5% below nominal.

Precision Output: Guaranteed output voltage accuracy is 0.75% ("A" grade) and 1.25% (standard grade) at room temperature.


Features

- Ultra low dropout voltage
- Guaranteed 500 mA continuous output current
- Very low output noise with external capacitor
- SO-8, Mini SO-8, 8 Lead LLP surface mount packages
- <0.8 μ A quiescent current when shutdown
- Low ground pin current at all loads
- 0.75% output voltage accuracy ("A" grade)
- High peak current capability (800 mA typical)
- Wide supply voltage range (16V max)
- Overtemperature/overcurrent protection
- -40°C to +125°C junction temperature range

Applications

- Notebook/Desktop PC
- PDA/Palmtop Computer
- Wireless Communication Terminals
- SMPS Post-Regulator

Block Diagram




DS101339-1

LP2989 Micropower/Low Noise, 500 mA Ultra Low-Dropout Regulator For Use with Ceramic Output Capacitors



Connection Diagrams


Surface Mount Packages:



SO-8/Mini SO-8 Package

See NS Package Drawing Numbers M08A/MUA08A


8 Lead LLP Surface Mount Package



Top View

See NS Package Number LDC08A

Basic Application Circuit



*Capacitance values shown are minimum required to assure stability, but may be increased without limit. Larger output capacitor provides improved dynamic response. See Application Hints.

**Shutdown must be actively terminated (see App. Hints). Tie to INPUT (Pin4) if not used

Ordering Information

TABLE 1. Package Marking and Ordering Information

| Output Voltage | Grade | Order Information | Package Marking | Supplied as: |
|-------------------------|-------|-------------------|-----------------|-----------------------------|
| 8 Lead LLP | | | | |
| 2.5 | A | LP2989AILD-2.5 | L01FA | 1000 Units on Tape and Reel |
| 2.5 | A | LP2989AILDX-2.5 | L01FA | 4500 Units on Tape and Reel |
| 2.5 | STD | LP2989ILD-2.5 | L01FB | 1000 Units on Tape and Reel |
| 2.5 | STD | LP2989ILDX-2.5 | L01FB | 4500 Units on Tape and Reel |
| 2.8 | A | LP2989AILD-2.8 | L000A | 1000 Units on Tape and Reel |
| 2.8 | A | LP2989AILDX-2.8 | L000A | 4500 Units on Tape and Reel |
| 2.8 | STD | LP2989ILD-2.8 | L000B | 1000 Units on Tape and Reel |
| 2.8 | STD | LP2989ILDX-2.8 | L000B | 4500 Units on Tape and Reel |
| 3.0 | A | LP2989AILD-3.0 | L01HA | 1000 Units on Tape and Reel |
| 3.0 | A | LP2989AILDX-3.0 | L01HA | 4500 Units on Tape and Reel |
| 3.0 | STD | LP2989ILD-3.0 | L01HB | 1000 Units on Tape and Reel |
| 3.0 | STD | LP2989ILDX-3.0 | L01HB | 4500 Units on Tape and Reel |
| 3.3 | A | LP2989AILD-3.3 | L01JA | 1000 Units on Tape and Reel |
| 3.3 | A | LP2989AILDX-3.3 | L01JA | 4500 Units on Tape and Reel |
| 3.3 | STD | LP2989ILD-3.3 | L01JB | 1000 Units on Tape and Reel |
| 3.3 | STD | LP2989ILDX-3.3 | L01JB | 4500 Units on Tape and Reel |
| 4.0 | A | LP2989AILD-4.0 | L01LA | 1000 Units on Tape and Reel |
| 4.0 | A | LP2989AILDX-4.0 | L01LA | 4500 Units on Tape and Reel |
| 4.0 | STD | LP2989ILD-4.0 | L01LB | 1000 Units on Tape and Reel |
| 4.0 | STD | LP2989ILDX-4.0 | L01LB | 4500 Units on Tape and Reel |
| 5.0 | A | LP2989AILD-5.0 | L01KA | 1000 Units on Tape and Reel |
| 5.0 | A | LP2989AILDX-5.0 | L01KA | 4500 Units on Tape and Reel |
| 5.0 | STD | LP2989ILD-5.0 | L01KB | 1000 Units on Tape and Reel |
| 5.0 | STD | LP2989ILDX-5.0 | L01KB | 4500 Units on Tape and Reel |
| 8 Lead MSOP (MM) | | | | |
| 2.5 | A | LP2989AIMM-2.5 | LA0A | 1000 Units on Tape and Reel |
| 2.5 | A | LP2989AIMMX-2.5 | LA0A | 3500 Units on Tape and Reel |
| 2.5 | STD | LP2989IMM-2.5 | LA0B | 1000 Units on Tape and Reel |
| 2.5 | STD | LP2989IMMX-2.5 | LA0B | 3500 Units on Tape and Reel |
| 2.8 | A | LP2989AIMM-2.8 | LA6A | 1000 Units on Tape and Reel |
| 2.8 | A | LP2989AIMMX-2.8 | LA6A | 3500 Units on Tape and Reel |
| 2.8 | STD | LP2989IMM-2.8 | LA6B | 1000 Units on Tape and Reel |
| 2.8 | STD | LP2989IMMX-2.8 | LA6B | 3500 Units on Tape and Reel |
| 3.0 | A | LP2989AIMM-3.0 | LA1A | 1000 Units on Tape and Reel |
| 3.0 | A | LP2989AIMMX-3.0 | LA1A | 3500 Units on Tape and Reel |
| 3.0 | STD | LP2989IMM-3.0 | LA1B | 1000 Units on Tape and Reel |
| 3.0 | STD | LP2989IMMX-3.0 | LA1B | 3500 Units on Tape and Reel |
| 3.3 | A | LP2989AIMM-3.3 | LA2A | 1000 Units on Tape and Reel |
| 3.3 | A | LP2989AIMMX-3.3 | LA2A | 3500 Units on Tape and Reel |
| 3.3 | STD | LP2989IMM-3.3 | LA2B | 1000 Units on Tape and Reel |
| 3.3 | STD | LP2989IMMX-3.3 | LA2B | 3500 Units on Tape and Reel |
| 5.0 | A | LP2989AIMM-5.0 | LA4A | 1000 Units on Tape and Reel |
| 5.0 | A | LP2989AIMMX-5.0 | LA4A | 3500 Units on Tape and Reel |
| 5.0 | STD | LP2989IMM-5.0 | LA4B | 1000 Units on Tape and Reel |
| 5.0 | STD | LP2989IMMX-5.0 | LA4B | 3500 Units on Tape and Reel |

Ordering Information (Continued)

TABLE 1. Package Marking and Ordering Information (Continued)

| Output Voltage | Grade | Order Information | Package Marking | Supplied as: |
|-----------------|-------|-------------------|-----------------|------------------------------|
| SO-8 (M) | | | | |
| 2.5 | A | LP2989AIMX-2.5 | LP2989AIM2.5 | 2500 Units on Tape and Reel |
| 2.5 | A | LP2989AIM-2.5 | LP2989AIM2.5 | Shipped in Anti-Static Rails |
| 2.5 | STD | LP2989IMX-2.5 | LP2989IM2.5 | 2500 Units on Tape and Reel |
| 2.5 | STD | LP2989IM-2.5 | LP2989IM2.5 | Shipped in Anti-Static Rails |
| 3.3 | A | LP2989AIMX-3.3 | LP2989AIM3.3 | 2500 Units on Tape and Reel |
| 3.3 | A | LP2989AIM-3.3 | LP2989AIM3.3 | Shipped in Anti-Static Rails |
| 3.3 | STD | LP2989IMX-3.3 | LP2989IM3.3 | 2500 Units on Tape and Reel |
| 3.3 | STD | LP2989IM-3.3 | LP2989IM3.3 | Shipped in Anti-Static Rails |
| 5.0 | A | LP2989AIMX-5.0 | LP2989AIM5.0 | 2500 Units on Tape and Reel |
| 5.0 | A | LP2989AIM-5.0 | LP2989AIM5.0 | Shipped in Anti-Static Rails |
| 5.0 | STD | LP2989IMX-5.0 | LP2989IM5.0 | 2500 Units on Tape and Reel |
| 5.0 | STD | LP2989IM-5.0 | LP2989IM5.0 | Shipped in Anti-Static Rails |

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

| | |
|---|--------------------|
| Storage Temperature Range | -65°C to +150°C |
| Operating Junction Temperature Range | -40°C to +125°C |
| Lead Temperature (Soldering, 5 seconds) | 260°C |
| ESD Rating (Note 2) | 2 kV |
| Power Dissipation (Note 3) | Internally Limited |

| | |
|--|-------------------------|
| Input Supply Voltage (Survival) | -0.3V to +16V |
| Input Supply Voltage (Operating) | 2.1V to +16V |
| Sense Pin | -0.3V to +6V |
| Output Voltage (Survival) (Note 4) | -0.3V to +16V |
| I _{OUT} (Survival) | Short Circuit Protected |
| Input-Output Voltage (Survival) (Note 5) | -0.3V to +16V |

Electrical Characteristics

Limits in standard typeface are for T_J = 25°C, and limits in **boldface type** apply over the full operating temperature range. Unless otherwise specified: V_{IN} = V_O(NOM) + 1V, I_L = 1 mA, C_{OUT} = 4.7 μF, C_{IN} = 2.2 μF, V_{S/D} = 2V.

| Symbol | Parameter | Conditions | Typical | LP2989AI-X.X (Note 6) | | LP2989I-X.X (Note 6) | | Units |
|--|--------------------------------|---|------------|-----------------------|--------------|----------------------|--------------|-------------------|
| | | | | Min | Max | Min | Max | |
| V _O | Output Voltage Tolerance | | | -0.75 | 0.75 | -1.25 | 1.25 | %V _{NOM} |
| | | 1 mA < I _L < 500 mA V _O (NOM) + 1V ≤ V _{IN} ≤ 16V | | -1.5 | 1.5 | -2.5 | 2.5 | |
| | | 1 mA < I _L < 500 mA V _O (NOM) + 1V ≤ V _{IN} ≤ 16V -25°C ≤ T _J ≤ 125°C | | -4.0 | 2.5 | -5.0 | 3.5 | |
| $\frac{\Delta V_O}{\Delta V_{IN}}$ | Output Voltage Line Regulation | V _O (NOM) + 1V ≤ V _{IN} ≤ 16V | 0.005 | | 0.014 | | 0.014 | %V |
| | | | | | 0.032 | | 0.032 | |
| $\frac{\Delta V_O}{\Delta I_L}$ | Load Regulation | 1 mA < I _L < 500 mA | 0.4 | | | | | %V _{NOM} |
| V _{IN} -V _O | Dropout Voltage (Note 7) | I _L = 100 μA | 1 | | 3 | | 3 | mV |
| | | I _L = 200 mA | 150 | | 200 | | 200 | |
| | | I _L = 500 mA | 310 | | 300 | | 300 | |
| I _{GND} | Ground Pin Current | I _L = 100 μA | 110 | | 175 | | 175 | μA |
| | | | | | 200 | | 200 | |
| | | I _L = 200 mA | 1 | | 2 | | 2 | mA |
| | | | | | 3.5 | | 3.5 | |
| | | I _L = 500 mA | 3 | | 6 | | 6 | |
| | | | | 9 | | 9 | | |
| | | V _{S/D} < 0.18V | 0.5 | | 2 | | 2 | μA |
| | | V _{S/D} < 0.4V | 0.05 | | 0.8 | | 0.8 | |
| I _O (PK) | Peak Output Current | V _{OUT} ≥ V _O (NOM) - 5% | 800 | 600 | | 600 | | mA |
| I _O (MAX) | Short Circuit Current | R _L = 0 (Steady State) (Note 9) | 1000 | | | | | |
| e _n | Output Noise Voltage (RMS) | BW = 100 Hz to 100 kHz, C _{OUT} = 10 μF C _{BYPASS} = .01 μF V _{OUT} = 2.5V | 18 | | | | | μV(RMS) |
| $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$ | Ripple Rejection | f = 1 kHz, C _{OUT} = 10 μF | 60 | | | | | dB |

Electrical Characteristics (Continued)

Limits in standard typeface are for $T_J = 25^\circ\text{C}$, and limits in **boldface type** apply over the full operating temperature range. Unless otherwise specified: $V_{IN} = V_O(\text{NOM}) + 1\text{V}$, $I_L = 1\text{ mA}$, $C_{OUT} = 4.7\ \mu\text{F}$, $C_{IN} = 2.2\ \mu\text{F}$, $V_{S/D} = 2\text{V}$.

| Symbol | Parameter | Conditions | Typical | LP2989AI-X.X (Note 6) | | LP2989I-X.X (Note 6) | | Units |
|-----------------------------------|--|---|-----------|--------------------------|--------------|-------------------------|--------------|---------------|
| | | | | Min | Max | Min | Max | |
| $\frac{\Delta V_{OUT}}{\Delta T}$ | Output Voltage Temperature Coefficient | (Note 8) | 20 | | | | | ppm/°C |
| SHUTDOWN INPUT | | | | | | | | |
| $V_{S/D}$ | S/D Input Voltage | $V_H = \text{O/P ON}$ | 1.4 | 1.6 | | 1.6 | | V |
| | | $V_L = \text{O/P OFF}$ $I_{IN} \leq 2\ \mu\text{A}$ | 0.50 | | 0.18 | | 0.18 | |
| $I_{S/D}$ | S/D Input Current | $V_{S/D} = 0$ | 0.001 | | -1 | | -1 | μA |
| | | $V_{S/D} = 5\text{V}$ | 5 | | 15 | | 15 | |
| ERROR COMPARATOR | | | | | | | | |
| I_{OH} | Output "HIGH" Leakage | $V_{OH} = 16\text{V}$ | 0.001 | | 1 | | 1 | μA |
| | | | | | 2 | | 2 | |
| V_{OL} | Output "LOW" Voltage | $V_{IN} = V_O(\text{NOM}) - 0.5\text{V}$, $I_O(\text{COMP}) = 150\ \mu\text{A}$ | 150 | | 220 | | 220 | mV |
| | | | | | 350 | | 350 | |
| $V_{THR}(\text{MAX})$ | Upper Threshold Voltage | | -4.8 | | -6.0 | -3.5 | -6.0 | % V_{OUT} |
| | | | | | -8.3 | -2.5 | -8.3 | |
| $V_{THR}(\text{MIN})$ | Lower Threshold Voltage | | -6.6 | | -8.9 | -4.9 | -8.9 | |
| | | | | | -13.0 | -3.0 | -13.0 | |
| HYST | Hysteresis | | 2.0 | | | | | |

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the component may occur. Electrical specifications do not apply when operating the device outside of its rated operating conditions.

Note 2: ESD testing was performed using Human Body Model, a 100 pF capacitor discharged through a 1.5 k Ω resistor.

Note 3: The maximum allowable power dissipation is a function of the maximum junction temperature, $T_J(\text{MAX})$, the junction-to-ambient thermal resistance, θ_{J-A} , and the ambient temperature, T_A . The maximum allowable power dissipation at any ambient temperature is calculated using:

$$P(\text{MAX}) = \frac{T_J(\text{MAX}) - T_A}{\theta_{J-A}}$$

The value of θ_{J-A} for the SO-8 (M) package is 160°C/W and the mini SO-8 (MM) package is 200°C/W. The value θ_{J-A} for the LLP (LD) package is specifically dependent on PCB trace area, trace material, and the number of layers and thermal vias. For improved thermal resistance and power dissipation for the LLP package, refer to Application Note AN-1187. Exceeding the maximum allowable power dissipation will cause excessive die temperature, and the regulator will go into thermal shutdown.

Note 4: If used in a dual-supply system where the regulator load is returned to a negative supply, the LP2989 output must be diode-clamped to ground.

Note 5: The output PNP structure contains a diode between the V_{IN} and V_{OUT} terminals that is normally reverse-biased. Forcing the output above the input will turn on this diode and may induce a latch-up mode which can damage the part (see Application Hints).

Note 6: Limits are 100% production tested at 25°C. Limits over the operating temperature range are guaranteed through correlation using Statistical Quality Control (SQC) methods. The limits are used to calculate National's Average Outgoing Quality Level (AOQL).


Note 7: Dropout voltage is defined as the input to output differential at which the output voltage drops 100 mV below the value measured with a 1V differential.

Note 8: Temperature coefficient is defined as the maximum (worst-case) change divided by the total temperature range.

Note 9: See Typical Performance Characteristics curves.


Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_O(\text{NOM}) + 1\text{V}$, $I_L = 1 \text{ mA}$, $V_{OUT} = 2.5\text{V}$.

Dropout Characteristics




DS101339-21

Dropout Voltage vs Temperature




DS101339-20

Dropout Voltage vs Load Current




DS101339-19

GND Pin Current vs Temperature and Load




DS101339-23

Ground Pin Current vs Load Current



DS101339-22


Input Current vs V_{IN}




DS101339-25

Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_{O(NOM)} + 1\text{V}$, $I_L = 1 \text{mA}$, $V_{OUT} = 2.5\text{V}$. (Continued)


Input Current vs V_{IN}




Input Current vs V_{IN}




Line Transient Response




Line Transient Response



Line Transient Response




Line Transient Response




Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_O(\text{NOM}) + 1\text{V}$, $I_L = 1 \text{mA}$, $V_{OUT} = 2.5\text{V}$. (Continued)


Load Transient Response




Load Transient Response




Short Circuit Current




Short Circuit Current vs Temperature



Short Circuit Current




Short Circuit Current vs V_{OUT}




Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_{O(NOM)} + 1\text{V}$, $I_L = 1 \text{mA}$, $V_{OUT} = 2.5\text{V}$. (Continued)


Ripple Rejection




Ripple Rejection




Ripple Rejection




Ripple Rejection



Ripple Rejection




Ripple Rejection




Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_{O(NOM)} + 1\text{V}$, $I_L = 1 \text{mA}$, $V_{OUT} = 2.5\text{V}$. (Continued)

Ripple Rejection




DS101339-45

Ripple Rejection In Dropout




DS101339-46

Ripple Rejection vs Load




DS101339-47

Output Noise Density




DS101339-36

Output Noise Density



DS101339-37


Turn-ON Waveform




DS101339-28

Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_{O(NOM)} + 1\text{V}$, $I_L = 1 \text{mA}$, $V_{OUT} = 2.5\text{V}$. (Continued)


Turn-ON Waveform




Turn-ON Waveform




Turn-ON Waveform




I_{GND} vs Shutdown



I_{GND} vs Shutdown




I_{GND} vs Shutdown




Typical Performance Characteristics Unless otherwise specified: $T_A = 25^\circ\text{C}$, $C_{OUT} = 4.7 \mu\text{F}$, $C_{IN} = 2.2 \mu\text{F}$, S/D is tied to V_{IN} , $V_{IN} = V_O(\text{NOM}) + 1\text{V}$, $I_L = 1 \text{mA}$, $V_{OUT} = 2.5\text{V}$. (Continued)

I_{GND} vs Shutdown



V_{OUT} vs Shutdown



Application Hints

LLP Package Devices

The LP2989 is offered in the 8 lead LLP surface mount package to allow for increased power dissipation compared to the SO-8 and Mini SO-8. For details on thermal performance as well as mounting and soldering specifications, refer to Application Note AN-1187.

EXTERNAL CAPACITORS

Like any low-dropout regulator, the LP2989 requires external capacitors for regulator stability. These capacitors must be correctly selected for good performance.

INPUT CAPACITOR: An input capacitor whose size is at least 2.2 μF is required between the LP2989 input and ground (the amount of capacitance may be increased without limit).


Characterization testing performed on the LP2989 has shown that if the amount of actual input capacitance drops below about 1.5 μF , an unstable operating condition may result. Therefore, the next larger standard size (2.2 μF) is specified as the minimum required input capacitance. Capacitor tolerance and temperature variation must be considered when selecting a capacitor (see **Capacitor Characteristics** section) to assure the minimum requirement of 1.5 μF is met over all operating conditions.

The input capacitor must be located at a distance of not more than 0.5" from the input pin and returned to a clean analog ground. Any good quality ceramic or tantalum may be used for this capacitor, assuming the minimum capacitance requirement is met.

OUTPUT CAPACITOR: The LP2989 requires a ceramic output capacitor whose size is at least 4.7 μF . The actual amount of capacitance on the output must never drop below about 3.5 μF or unstable operation may result. For this reason, capacitance tolerance and temperature characteristics must be considered when selecting an output capacitor.

The LP2989 is designed specifically to work with ceramic output capacitors, utilizing circuitry which allows the regulator to be stable across the entire range of output current with an output capacitor whose ESR is as low as 4 m Ω . It may also be possible to use Tantalum or film capacitors at the output, but these are not as attractive for reasons of size and cost (see next section Capacitor Characteristics).

The output capacitor must meet the requirement for minimum amount of capacitance and also have an ESR (equivalent series resistance) value which is within the stable range. Curves are provided which show the stable ESR range as a function of load current (see ESR graph below).



Stable Region For output Capacitor ESR

Important: The output capacitor must maintain its ESR within the stable region *over the full operating temperature range of the application* to assure stability.

It is important to remember that capacitor tolerance and variation with temperature must be taken into consideration when selecting an output capacitor so that the minimum required amount of output capacitance is provided over the full operating temperature range. (See Capacitor Characteristics section).

The output capacitor must be located not more than 0.5" from the output pin and returned to a clean analog ground.

NOISE BYPASS CAPACITOR: Connecting a 10 nF capacitor to the Bypass pin significantly reduces noise on the regulator output. However, the capacitor is connected directly to a high-impedance circuit in the bandgap reference.

Because this circuit has only a few microamperes flowing in it, any significant loading on this node will cause a change in the regulated output voltage. For this reason, DC leakage current through the noise bypass capacitor must never exceed 100 nA, and should be kept as low as possible for best output voltage accuracy.

The types of capacitors best suited for the noise bypass capacitor are ceramic and film. High-quality ceramic capacitors with either NPO or COG dielectric typically have very low leakage. 10 nF polypropylene and polycarbonate film capacitors are available in small surface-mount packages and typically have extremely low leakage current.

CAPACITOR CHARACTERISTICS

CERAMIC: The LP2989 was designed to work with ceramic capacitors on the output to take advantage of the benefits they offer: for capacitance values in the 4.7 μF range, ceramics are the least expensive and also have the lowest ESR values (which makes them best for eliminating high-frequency noise). The ESR of a typical 4.7 μF ceramic capacitor is in the range of 10 m Ω to 15 m Ω , which easily meets the ESR limits required for stability by the LP2989.

One disadvantage of ceramic capacitors is that their capacitance can vary with temperature. Many large value ceramic capacitors ($\geq 2.2 \mu\text{F}$) are manufactured with the Z5U or Y5V temperature characteristic, which results in the capacitance dropping by more than 50% as the temperature goes from 25°C to 85°C.

This could cause problems if a 4.7 μF capacitor were used on the output since it will drop down to approximately 2.4 μF at high ambient temperatures (which could cause the LP2989 to oscillate). Another significant problem with Z5U

Application Hints (Continued)

and Y5V dielectric devices is that the capacitance drops severely with applied voltage. A typical Z5U or Y5V capacitor can lose 60% of its rated capacitance with half of the rated voltage applied to it.

For these reasons, X7R and X5R type ceramic capacitors must be used on the input and output of the LP2989.

TANTALUM: Tantalum capacitors are less desirable than ceramics for use as output capacitors because they are typically more expensive when comparing equivalent capacitance and voltage ratings in the 1 μF to 4.7 μF range.

Another important consideration is that Tantalum capacitors have higher ESR values than equivalent size ceramics. This means that while it may be possible to find a Tantalum capacitor with an ESR value within the stable range, it would have to be larger in capacitance (which means bigger and more costly) than a ceramic capacitor with the same ESR value.

It should also be noted that the ESR of a typical Tantalum will increase about 2:1 as the temperature goes from 25°C down to -40°C, so some guard band must be allowed.

Tantalum capacitors may be used on the input as long as the requirement for minimum capacitance is met.

FILM: Polycarbonate and polypropylene film capacitors have excellent electrical performance: their ESR is the lowest of the three types listed, their capacitance is very stable with temperature, and DC leakage current is extremely low.

One disadvantage is that film capacitors are larger in physical size than ceramic or tantalum which makes film a poor choice for either input or output capacitors.

However, their low leakage makes them a good choice for the noise bypass capacitor. Since the required amount of capacitance is only .01 μF , small surface-mount film capacitors are available in this size.

SHUTDOWN INPUT OPERATION

The LP2989 is shut off by driving the Shutdown input low, and turned on by pulling it high. If this feature is not to be used, the Shutdown input should be tied to V_{IN} to keep the regulator output on at all times.

To assure proper operation, the signal source used to drive the Shutdown input must be able to swing above and below the specified turn-on/turn-off voltage thresholds listed in the Electrical Characteristics section under $V_{\text{ON/OFF}}$.

To prevent mis-operation, the turn-on (and turn-off) voltage signals applied to the Shutdown input must have a slew rate which is $\geq 40 \text{ mV}/\mu\text{s}$.

CAUTION: the regulator output voltage can not be guaranteed if a slow-moving AC (or DC) signal is applied that is in the range between the specified turn-on and turn-off voltages listed under the electrical specification $V_{\text{ON/OFF}}$ (see Electrical Characteristics).

REVERSE INPUT-OUTPUT VOLTAGE

The PNP power transistor used as the pass element in the LP2989 has an inherent diode connected between the regulator output and input.




During normal operation (where the input voltage is higher than the output) this diode is reverse-biased.

However, if the output is pulled above the input, this diode will turn ON and current will flow into the regulator output.

In such cases, a parasitic SCR can latch which will allow a high current to flow into V_{IN} (and out the ground pin), which can damage the part.

In any application where the output may be pulled above the input, an external Schottky diode must be connected from V_{IN} to V_{OUT} (cathode on V_{IN} , anode on V_{OUT}), to limit the reverse voltage across the LP2989 to 0.3V (see Absolute Maximum Ratings).





Physical Dimensions inches (millimeters) unless otherwise noted



M08A (REV H)

**SO-8 Package
NS Package Number M08A**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




MUA08A (REV B)

Mini SO-8 Package
NS Package Number MUA08A



**LP2989 Micropower/Low Noise, 500 mA Ultra Low-Dropout Regulator
For Use with Ceramic Output Capacitors**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



DIMENSIONS ARE IN MILLIMETERS

RECOMMENDED LAND PATTERN
1:1 RATION WITH PKG SOLDER PADS



LDC08A (Rev A)

**8 Lead LLP Surface Mount Package
NS Package Number LDC08A**

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com
www.national.com

National Semiconductor Europe
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor Asia Pacific Customer Response Group
Tel: 65-2544466
Tel: 65-2544466
Fax: 65-2504466
Email: ap.support@nsc.com

National Semiconductor Japan Ltd.
Tel: 81-3-5639-7560
Fax: 81-3-5639-7507